

## 产品概览

## AR0138AT: CMOS Digital Image Sensor, 1/2.6-Inch

欲看完整文档，请参阅数据表。

ON Semiconductor AR0138AT is a 1/2.6-inch CMOS digital image sensor with a 1288 H x 968 V active-pixel array. This advanced automotive sensor captures images in either linear, or high dynamic range, with rolling-shutter readout. AR0138AT is optimized for both low light and challenging high dynamic range scene performance, with a 4.2 m BSI pixel and on-sensor 120 dB HDR capture capability. The sensor includes flexible functions such as in-pixel binning, windowing, and both video and single frame modes. The sophisticated sensor fault detection features and embedded data on AR0138AT are designed to enable camera ASIL B compliance. The device is programmable through a simple two-wire serial interface, and supports multiple output interface options, including MIPI and Parallel. The AR0138AT sensor is also supported by ON Semiconductor automotive co-processor products, delivering a total HDR video solution for the latest automotive viewing applications (RVC, Surround View, and CMS applications).

## 特性

- High Performance 4.2 m Automotive Grade Backside Illuminated (BSI) Pixel with DR-Pix Technology
- Advanced On-Sensor HDR Reconstruct with Flexible Exposure Ratio Control
- Fast 69 FPS Video Capture at 1280 x 960 and 3-exposure HDR
- Sensor Fault Detection for ASIL-B Compliance Support
- 2x2 In-pixel Binning Mode
- Data Interfaces: 4-lane MIPI CSI-2, or Parallel
- Selectable Automatic or User Controlled Black Level Control
- Frame to Frame Switching Among up to 4 Contexts to Enable Multi-function Systems
- Spread-spectrum Input Clock Support
- Multi-Camera Synchronization Support

For more features, see the data sheet

## 应用

- 1.2 MP, High Performance ADAS (Automotive Driver Assistant System)
- 960p, 720p Automotive Rear View or Backup
- 960p, 720p Automotive Surround View

## 器件电气规格

产品	Compliance	Status	Type	Megapixels	Frame Rate (fps)	Optical Format	Shutter Type	Pixel Size (µm)	Output Interface	Color	Package Type
AR0138AT3C00XUEA 0-DPBR-E	Pb-free Halide free	Active	CMOS	1.2	69 fps		Electronic Rolling		Parallel MIPI	Other	IBGA-109
AR0138AT3C00XUEA 0-DRBR-E	Pb-free Halide free	Active	CMOS	1.2	69 fps		Electronic Rolling		MIPI Parallel	Other	IBGA-109
AR0138AT3R00XUD20 -E	Pb-free Halide free	Active	CMOS	1.2	69 fps		Electronic Rolling		Parallel MIPI	Other	
AR0138AT3R00XUEA 0-DPBR-E	Pb-free Halide free	Active	CMOS	1.2	69 fps		Electronic Rolling		MIPI Parallel	Other	IBGA-109
AR0138AT3R00XUEA 0-DRBR-E	Pb-free Halide free	Active	CMOS	1.2	69 fps		Electronic Rolling		MIPI Parallel	Other	IBGA-109

欲了解更多信息，请联系您当地的销售支援 [www.onsemi.cn](http://www.onsemi.cn)。

创建于：11/27/2017