

产品概览

1N5223B: Zener 2.7V 0.5W 5%

欲看完整文档，请参阅数据表。

General Data Applicable to all series in this group.
500 Milliwatt
Hermetically Sealed
Glass Silicon Zener Diodes

特性

- Complete Voltage Range - 1.8 to 200 Volts
- DO-204AH Package - Smaller than Conventional DO-204AA Package
- Double Slug Type Construction
- Metallurgically Bonded Construction

Mechanical Characteristics:

- CASE: Double slug type, hermetically sealed glass
- MAXIMUM LEAD TEMPERATURE FOR SOLDERING PURPOSES: 230°C, 1/16", from case for 10 seconds
- FINISH: All external surfaces are corrosion resistant with readily solderable leads
- POLARITY: Cathode indicated by color band. When operated in zener mode, cathode will be positive with respect to anode
- MOUNTING POSITION: Any
- WAFER FAB LOCATION: Phoenix, Arizona

For more features, see the data sheet

器件电气规格

| 产品 | Compliance | Status | V _Z Typ (V) | P Max (W) | Package Type |
|---------|------------------------|--------|------------------------|-----------|--------------|
| 1N5223B | Pb-free Halide free | Active | 2.7 | 0.5 | Axial Lead |

欲了解更多信息，请联系您当地的销售支援 www.onsemi.cn。

创建于：11/27/2017