

## ams' new temperature sensor offers best-in-class combination of accuracy, ultra-low power consumption and small size

### New AS6200 digital temperature sensor in 1.6 mm x 1mm package is easy to design into IoT, mobile and battery-powered applications

Premstaetten, Austria (22 June, 2016) -- ams AG (SIX: AMS), a leading provider of high performance sensors and analog ICs, today launched an integrated digital temperature sensor which offers an industry-best combination of low power consumption and high accuracy in a small package. The 1.6mm x 1mm AS6200's typical current is 6µA at a measurement rate of 4 samples per second, and its digital measurement outputs are accurate to  $\pm 0.4^{\circ}\text{C}$ .

The factory calibrated AS6200 integrates in a single chip the functions required in a temperature sensing system, making it easy for users to design the sensor into their space-constrained or battery-powered products.

The device consists of a silicon bandgap sensor, an analog-to-digital converter, a digital signal processor and a serial I<sup>2</sup>C interface. The on-chip DSP handles all linearization and calibration, producing a 12-bit (0.0625°C resolution) binary output.

Despite its high level of integration, the AS6200 draws very little current. Operating from a supply range of 1.8V-3.6V, the AS6200 draws just 1.5µA at a measurement rate of 1 sample. The conversion rate can be set in a range from 0.25Hz to 8Hz. At lower conversion frequencies, power consumption is lower. In stand-by mode, in which all the chip's functions are turned off except the serial interface, it draws just 0.1µA (typical).

Small and ultra low power, the AS6200 creates new opportunities for manufacturers of battery-powered, mobile and wearable devices to implement digital temperature sensing into new designs without paying a power or space penalty. Industrial process control solutions, and Internet of Things applications such as cold-chain monitoring are significantly enhanced as space and power savings are realized when using the AS6200.

"Backed by ams' proprietary low-power, high-sensitivity analog process, this results in the factory calibrated AS6200's industry-best combination of accuracy ( $\pm 0.4^{\circ}\text{C}$ , max between 0°C to 65°C), low power consumption and small size (1.6mm<sup>2</sup>)", said Christian Feierl, marketing manager at ams.

The sensor's I<sup>2</sup>C interface allows for two devices to be connected to one bus. The sensor also has a pin dedicated to an Alert function, which triggers an interrupt at the host microcontroller when the measured temperature crosses a high or low temperature threshold set by the user.



The AS6200 is available immediately in production volumes. Unit pricing is €0.49 in order quantities of 1,000.

An evaluation board is available online from the ams ICdirect online store. For more technical information and for sample requests, go to [www.ams.com/temperature-sensor/AS6200](http://www.ams.com/temperature-sensor/AS6200) and watch our [video](#).

In addition ams is demonstrating AS6200 at Sensors Expo in San Jose (US), June 21 – 23, 2016, booth **1016**.

#### **About ams**

ams is a global leader in the design and manufacture of advanced sensor solutions and analog ICs. Our mission is to shape the world with sensor solutions by providing a seamless interface between humans and technology. ams' high-performance analog products drive applications requiring extreme precision, dynamic range, sensitivity, and ultra-low power consumption. Products include sensors, sensor interfaces, power management and wireless ICs for consumer, communications, industrial, medical, and automotive markets.

With headquarters in Austria, ams employs over 2,100 people globally and serves more than 8,000 customers worldwide. ams is listed on the SIX Swiss stock exchange (ticker symbol: AMS). More information about ams can be found at [www.ams.com](http://www.ams.com).

#### **Join ams social media channels:**

Follow us on twitter <https://twitter.com/amsAnalog> or

Share with <https://www.linkedin.com/company/ams-ag>

#### **for further information**

##### **Media Relations**

**ams AG**  
Ulrike Anderwald  
Head of Marketing Communications  
T +43 (0) 3136 500 31200  
[press@ams.com](mailto:press@ams.com)  
[www.ams.com](http://www.ams.com)

##### **Technical Contact**

**ams AG**  
Christian Feierl  
Marketing Manager  
T +43 3136 500 31207  
[christian.feierl@ams.com](mailto:christian.feierl@ams.com)  
[www.ams.com](http://www.ams.com)