







超快速恢复整流二极管

| 参数 | 绝对最大额定值 | | | | | 电特性 (Ta = 25 °C) | | | | | | | OTHERS | | |
|---------|---------------------|--------------------------------------|--------------------------------------|---------|-----------|--|---------------------|---|----------------------|----------------------|-------------------------|---------|--------|-----|-----|
| | V _{RM} (V) | I _{RM} (A) 50% 占空比 脉冲 | I _{SM} (A) 50% 占空比 脉冲 | TJ (°C) | TSTG (°C) | V _F (V) 正向电压 I _F (A) | I _F (mA) | I _F (A) I _F = V _{RM} 脉宽由数据手册规定 | t _{rr} (纳秒) | t _{rr} (纳秒) | R _{θJC} (°C/W) | Q1 | Q2 | 注 | |
| FML-22S | 200 | | 65 | | | 0.98 | | 0.25 | 1.0 | 40 | | | | | |
| FML-23S | 300 | 10.0 | 70 | 40 | 150 | 1.30 | 5.0 | 0.1 | 0.5 | 50 | 100/100 | 100/200 | 4.0 | 2.1 | (A) |
| FML-24S | 400 | | | | | | | | 0.2 | | | | | | |

FML-22S



FML-23S



FML-24S

