



RECOMMEND P. C. B. LAYOUT

目錄 MAPX	變更內容 MODIFICATION	日期 DATE
------------	----------------------	------------

NOTES:

- MATERIAL SPECIFICATION:
 - HOUSING MATERIAL:SEE PART NO.
 - SHELL MATERIAL:SEE PART NO. T:0.35mm PLATING:SEE PART NO.
 - BACK COVER MATERIAL:SPCC T:0.35mm PLATING:NICKE.
 - SHRAPHVEL MATERIAL:SEE PART NO. T:0.25mm
 - TERMINAL: COPPER ALLOY T:0.25mm
 - ELECTRICAL CHARACTERISTIC:
 - VOLTAGE CURRENT RATING: 1AMP, 30V DC;
 - INSULATION RESISTANCE: 1000MΩ MIN;
 - CONTACT RESISTANCE: 30mΩ MAX;
 - WITHSTANDING VOLTAGE: 500V AC;
 - MECHANICAL:
 - MATING FORCE:3.57 KG MAX
 - UNMATING FORCE:1.02 KG MIN.
 - 02-1X XAX X XNX X XN-001
 - 1 2 3 4 5 6 7 8
- 1:外壳材质代码: A:黄铜(2680), B:磷铜(C5191),
 D:单光铁 E:双光铁
 2:外壳电镀代码: A:镀镍12H, B:镀镍24H, C:镀镍48H, D:镀雾镍
 3:中夹片材质及电镀代码: A:SPCC 镀镍 E:黄铜 镀镍
 I:磷铜 镀镍 K:不锈钢
 L:不锈钢 镀镍
 4:主体胶芯材质代码: A:FR7, B:LCP, F:PA66
 5:主体胶芯颜色代码: 1:白色 2:黑色 3:木色
 6:端子材质代码: 1:黄铜 2:磷铜(C5191),
 7:端子电镀代码: A:半金锡(G/F, B:半金锡3u",
 C:半金锡15u", D:半金锡30u",
 E:半金雾锡(G/F, F:半金雾锡3u",
 G:半金雾锡15u", H:半金雾锡30u",
 8: 环保代码: N:非环保, R:ROHS, S:SONY, F:ROHS-无卤

深圳市精拓金电子有限公司

公差一览表 TOLERANCE UNLESS OTHERWISE		单位 UNITS	MM	制图 DRAWING	Z-V-B	产品料号 PRODUCT PART NO.	
X	±0.15	X'	±5'	审核	郭治富	产品名称 PRODUCT NO.	USB A/F双层全包长弯脚无弹
X	±0.10	X'	±2'	日期	2012/10/20	角法	
XX	±0.05	XX'	±1'	核准	叶文国	版本	40
XXX	±0.03	XXX'	±0.5'	DATE			