

ZV series


Part number	ZV470M035E055ETR	
Capacitance	47	μF
Voltage	35	VDC
Surge Voltage	40	VDC
Capacitance Tolerance (@120Hz, +20°C)	±20	%
Ripple current (max, @100KHz,+105°C)	200	mA
Dissipation factor (tanδ @120Hz, +20°C)	14	%
Leakage Current (max, @ +20°C)*	16.45	μA
Impedance (max. @ 100KHz,+20°C)	1	Ω
Size	6.3x5.5	mm
Operating temperature	-55 to 105	°C
Endurance	2000	h



*L.C. $I \leq 0.01CV$ or $3\mu A$ ($C = CAP.$, $V = W.V.$)

After 2 minutes, whichever is greater measured with rated working voltage applied.

Test conditions	Endurance	Shelf Life
Duration time	2000h @ 105°C	1000h @ 105°C
Applied voltage	Rated DC working voltage, I_R	None
After test requirements (+20°C):		
Capacitance change	≤ ±25% of initial measured value	
Dissipation factor change	≤ 200% of the initial specified value	
Leakage current	≤ the initial specified value	
comment		Pre-treatment for measurements shall be conducted after application of DC working voltage for 30 min.



D	L	A	B	C	W	P±0.2
6.3	5.5	6.6	6.6	7.2	0.5~0.8	2.2

Series	Cap	Tol.	Voltage	Case D	Case L	Type	Cust.
1_2	3_4_5	6	7_8_9	10	11_12_13	14_15_16	17_18_19_20
ZV	470	M	035	E	055	ETR	
	=47μF	=±20%	=35V	=6.3mm	=5.5mm	=tape and reel	no request
	...						