ROHS COMPLIED

















SEC:A-A
Image of plug match with contact point





Recommended PCB Layout
Tolerance:±0.1



SEC:B-B
Image of plug match with contact point

SPECIFIATIINS:
规格：
1.INSULATION RESISTANCEA VILTAGE OF 500V D.C.
SHALL BE APPLIED TO THE TERMINALSAFTER WHICH
MEASUREMENT SHALL BE MADE.A GAUGE FIR THE
MEASVREMENT SHALL BE USED THE INSVLATEDGAUGE
绝缘电阻应在端子上施加500V直流电压，然后进行测量。
2.CONTACT RESISTANCE:30mA OR LESS
接触电阻:30mA 或以下
3.VOLTAGE PROOF:500V AC FOR ONE MINUTE.
耐压性： 500V AC FOR ONE MINUTE.
4.DURABILITY:10000 INSERTION/REMOVAL CYCLES(MINIMUM)
耐久性:10000 INSERTION/REMOVAL CYCLES(MINIMUM)
5.INSETION FORCE:0.4KGF-2.0KGF
插入力:0.4KGF-2.0KGF
6.WITHDRAWALFIRCE:0.4KGF~2.0KGF
拔出力:0.4KGF~ 2.0KGF
7.WATER PROFNESS:THIS PRODUCT IS CINFIRM
To JIS STANDARD IPX7 BY WATERPROIF JACK
防水性：本产品符合WATERPROIF JACK的JIS标准IPX7
8.USING PLUG:43.5MM、4-POLE STEREO
EARPHINE(LCH/RCH/GND/MIC)
PRIVIDED THAT THEY CINFORM TI VIS C6560
使用插头:43.5MM、4-POLE STEREO
EARPHINE(LCH/RCH/GND/MIC)
PRIVIDED THAT THEY CINFORM TI VIS C6560
9.1VAL RING
阀环
9-1.Hordness af silicane rudder:70'
硅胶舵数：70

ITEM	PART NAME	TERMINAL	QTY	MATERIAL
⑩	OVAL RING	----	1	SILICONE
⑨	BOND	----	1	----
⑧	TERMINAL	----	2	C2680 t=0.2
⑦	TIP SPRING-2	5	1	Ti-Cut=0.2
⑥	RING SPRING-2	4	1	Ti-Cut=0.2
⑤	RING SPRING-1	3	1	Ti-Cut=0.2
④	TIP SPRING-1	2	1	Ti-Cut=0.2
③	EARTH SPRING	1	1	Ti-Cut=0.2
②	COVER	----	1	PA9T(BLACK)
①	HOUSING	----	1	PA9T(BLACK)

广东星坤科技股份有限公司

生效日期		
ΔX		
ΔX		
ΔX		
MARK	DESCRIPTION	DATE / REVISED / APPROVED

文件工程章

REVISIONS

ANGLAR	±5°		
X.X	±0.2mm		
X.XX	±0.1mm		
X.XXX	±0.05mm		

UNSPECIFIED TOLERANCES

www.xk-dg.cn www.helloxkb.com www.helloxkb.cn

DSND		DATE		SCALE: N/A	MODEL TYPE: 3.5 PHONE JACK
DWN		DATE		VIEW:	PART NO.:
CHKD		DATE		UNIT: mm/in	
APPD		DATE		SIZE: A4	DWG NO.: PJ-3255A

XKB INDUSTRIAL PRECISION CO.,LIMITED

WEIGHT	SHEET	REVISION
1.0g	1/1	A0