



# B12WS THRU B120WS

Reverse Voltage 20 to 200Volts Forward Current - 1.0 Ampere


## SURFACE MOUNT SCHOTTKY BARRIER RECTIFIER

### Features

- ◆ Metal silicon junction, majority carrier conduction
- ◆ For surface mounted applications
- ◆ Low power loss, high efficiency
- ◆ High forward surge current capability
- ◆ For use in low voltage, high frequency inverters, free wheeling, and polarity protection applications

**SOD-323**

ROHS  
COMPLIANT



### Mechanical Data

Case : UOD-323

Terminals : Solderable per MIL-STD-750, Method 2026A

Weight : 0.00€19 ounce, 0.00548 grams

Dimensions in inches and (millimeters)

### Maximum Ratings And Electrical Characteristics

Ratings at 25°C ambient temperature unless otherwise specified.

Single phase half-wave 60Hz, resistive or inductive load, for capacitive load current derate by 20%.

Parameter	SYMBOLS	B12WS	B14WS	B16WS	B18WS	B110WS	B112WS	B115WS	B120WS	UNITS
Marking code		B12S	B14S	B16S	B18S	110S	112S	115S	120S	
Maximum repetitive peak reverse voltage	V <sub>RMM</sub>	20	40	60	80	100	120	150	200	V
Maximum RMS voltage	V <sub>RMS</sub>	14	28	42	56	70	84	105	140	V
Maximum DC blocking voltage	V <sub>DC</sub>	20	40	60	80	100	120	150	200	V
Maximum average forward rectified current	I <sub>(AV)</sub>						1.0			A
Peak forward surge current 8.3ms single half sine-wave superimposed on rated load (JEDEC Method)	I <sub>FSM</sub>						25			A
Maximum instantaneous forward voltage at 1.0A	V <sub>F</sub>		0.55		0.70		0.85		0.90	V
Maximum DC reverse current TA=25°C at rated DC blocking voltage TA=100°C	I <sub>R</sub>			0.3			0.2		0.1	mA
				10			5		2	
Typical junction capacitance (NOTE 1)	C <sub>J</sub>		110				80			pF
Operating junction temperature range	T <sub>J</sub>				-55 to +125					°C
Storage temperature range	T <sub>STG</sub>				-55 to +150					°C

Note:1.Measured at 1.0MHz and applied reverse voltage of 4.0V D.C.



# B12WS THRU B120WS

Reverse Voltage 20 to 200Volts Forward Current - 1.0 Ampere

## Typical Characteristics

Fig.1 Forward Current Derating Curve




Fig.2 Typical Reverse Characteristics




Fig.3 Typical Forward Characteristic




Fig.4 Typical Junction Capacitance





Fig.5 Maximum Non-Repetitive Peak Forward Surge Current




The curve above is for reference only.



# B12WS THRU B120WS

Reverse Voltage 20 to 200Volts Forward Current - 1.0 Ampere

## Packing information




Item	Symbol	Tolerance	unit:mm
Carrier width	A	0.1	1.46
Carrier length	B	0.1	2.90
Carrier depth	C	0.1	1.25
Sprocket hole	d	0.05	1.50
13" Reel outside diameter	D	2.0	330.00
13" Reel inner diameter	D1	min	50.00
7" Reel outside diameter	D	2.0	178.00
7" Reel inner diameter	D1	min	54.40
Feed hole diameter	D2	0.5	13.00
Sprocket hole position	E	0.1	1.75
Punch hole position	F	0.1	3.50
Punch hole pitch	P	0.1	4.00
Sprocket hole pitch	P0	0.1	4.00
Embossment center	P1	0.1	2.00
Overall tape thickness	T	0.1	0.06
Tape width	W	0.3	8.00
Reel width	W1	1.0	12.30

Note:Devices are packed in accordance with EIA standard RS-481-A and specifications listed above.

## Reel packing

PACKAGE	REEL SIZE	REEL (pcs)	COMPONENT SPACING (m/m)	BOX (pcs)	INNER BOX (m/m)	REEL DIA, (m/m)	CARTON SIZE (m/m)	CARTON (pcs)	APPROX. GROSS WEIGHT (kg)
SOD-323	7"	3,000	4.0	45,000	210*208*203	178	430*430*235	180,000	9.0

## Suggested Pad Layout



Symbol	Unit (mm)	Unit (inch)
A	1.2	0.047
B	1.2	0.047
C	2.6	0.102
D	1.4	0.055
E	3.8	0.149

## Important Notice and Disclaimer

Microdiode Electronics (Jiangsu) reserves the right to make changes to this document and its products and specifications at any time without notice. Customers should obtain and confirm the latest product information and specifications before final design, purchase or use.

Microdiode Electronics (Jiangsu) makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does Microdiode Electronics (Jiangsu) assume any liability for application assistance or customer product design. Microdiode Electronics (Jiangsu) does not warrant or accept any liability with products which are purchased or used for any unintended or unauthorized application.

No license is granted by implication or otherwise under any intellectual property rights of Microdiode Electronics (Jiangsu).

Microdiode Electronics (Jiangsu) products are not authorized for use as critical components in life support devices or systems without express written approval of Microdiode Electronics (Jiangsu).