

Material

Housing Material: LCP, UL94V-0, black

Contact Terminal: Copper Alloy

Metallic Shell: Sus

Electrical

Voltage Rating: 30 V AC

Current Rating: Signal (Pins 2,3,4): 1.0A, Power (Pins 1,5): 1.8A

Contact Resistance: 30mΩ Max

Insulation resistance: 1000MΩ Min


Dielectric withstanding voltage: 250V AC/Minute

Mechanical

Durability: 10,000 cycles

Mating Force: 35N (3.57Kg) Max

Unmating Force: 8N (0.82Kg) Min.



RECOMMENDED PCB LAYOUT(TOP VIEW)
GENERAL TOLERANCES:±0.05

U254-05XX-4BH23-X2S
 1:AU 1U"
 6:AU 30U"
 T:TIN
 N:NICKEL
 S:Sus
 2:WITHOUT
 S:Scrolls F:Flat

广东星坤科技股份有限公司

生		日期
效		

文件工程章

REVISIONS

www.xkcg.cn www.helloxkb.com www.helloxkb.cn

UNSPECIFIED TOLERANCES

DSND		DATE		SCALE: N/A	MODEL TYPE:
DWN		DATE		VIEW:	MICRO USB
CHKD		DATE		UNIT: mm/in	PART NO.:
APPD		DATE		SIZE: A4	DWG NO.:
					U254-05XX-4BH23-S2S
			WEIGHT	SHEET	REVISION
			1.0g	1/1	A0

KXB INDUSTRIAL PRECISION CO., LIMITED