



SD103AW THRU SD103CW


Reverse Voltage 20-40 Volts Forward Current - 0.35 Ampere

SCHOTTKY DIODES

Features


- ◆ Fast switching speed
- ◆ Guard ring construction for transient protection
- ◆ Negligible reverse recovery time
- ◆ low reverse capacitance

SOD-123



Mechanical Data

Case: JEDEC SOD-123 molded plastic body
 Terminals: Plated leads solderable per MIL-STD-750, Method 2026
 Polarity: Polarity symbols marked on case
 Weight : 0.0007 ounce, 0.02 grams
 Marking: SD103AW:S4, SD103BW:S5, SD103CW:S6



Dimensions in inches and (millimeters)

Absolute Maximum Ratings at 25 °C

PARAMETER	SYMBOLS	SD103AW	SD103BW	SD103CW	UNITS
Peak repetitive peak reverse voltage	V_{RRM}				VOLTS
Working peak reverse voltage	V_{RWM}	40	30	20	
DC Blocking voltage	V_{DC}				
RMS Reverse voltage	$V_{R(RMS)}$	28	21	14	V
Forward continuous current	I_{FM}	350			mA
Repetitive peak forward current @ $t \leq 1.0s$	I_{FRM}	1.5			A
Power dissipation	P_d	400			mW
Thermal resistance junction to ambient	$R_{\theta JA}$	300			°C/W
Storage temperature	T_{STG}	-65 to +125			°C

Characteristics at $T_a = 25\text{ °C}$

PARAMETER	SYMBOLS	Min.	Typ.	Max.	Unit	Conditions
Reverse breakdown voltage	$V_{(BR)R}$	40			V	$I_R = 100\mu A$
Reverse voltage		30				$I_R = 100\mu A$
Reverse		20				$I_R = 100\mu A$
Forward voltage	V_F			0.37 0.60	V	$I_F = 20mA$ $I_F = 200mA$
Reverse current	I_{RM}			5.0	μA	$V_R = 30V$
						$V_R = 20V$
						$V_R = 10V$
Capacitance between terminals	C_T		50		pF	$V_R = 0V, f = 1.0MHz$
Reverse recovery time	t_{rr}		10		ns	$I_F = I_R = 200mA$ $I_{rr} = 0.1 \times I_R, R_L = 100\ \Omega$



SD103AW THRU SD103CW

Reverse Voltage 20-40 Volts Forward Current - 0.35 Ampere

Typical Characteristics

FIG. 1- TYPICAL FORWARD CHARACTERISTICS





FIG. 2-TYP. JUNCTION CAPACITANCE VS REVERSE VOLTAGE




The curve above is for reference only.



SD103AW THRU SD103CW

Reverse Voltage 20-40 Volts Forward Current - 0.35 Ampere

Packing information



unit:mm


Item	Symbol	Tolerance	SOD-123
Carrier width	A	0.1	2.1
Carrier length	B	0.1	4.0
Carrier depth	C	0.1	1.60
Sprocket hole	d	0.05	1.55
7" Reel outside diameter	D	2.0	178.00
7" Reel inner diameter	D ₁	min	50.0
Feed hole diameter	D ₂	0.5	13.00
Sprocket hole position	E	0.1	1.75
Punch hole position	F	0.1	3.50
Punch hole pitch	P	0.1	4.00
Sprocket hole pitch	P ₀	0.1	4.00
Embossment center	P ₁	0.1	2.00
Overall tape thickness	T	0.1	0.25
Tape width	W	0.3	8.15
Reel width	W ₁	1.0	10.5

Note: Devices are packed in accordance with EIA standard RS-481-A and specifications listed above.

Reel packing

PACKAGE	REEL SIZE	REEL (pcs)	COMPONENT SPACING (m/m)	BOX (pcs)	INNER BOX (m/m)	REEL DIA, (m/m)	CARTON SIZE (m/m)	CARTON (pcs)	APPROX. GROSS WEIGHT (kg)
SOD-123	7"	3,000	4.0	45,000	210*208*203	178	430*430*235	180,000	9.0

Suggested Pad Layout



Symbol	Unit (mm)	Unit (inch)
A	1.2	0.047
B	1.2	0.047
C	3.2	0.126
D	2.0	0.079
E	4.4	0.173

Important Notice and Disclaimer

Microdiode Electronics (Jiangsu) reserves the right to make changes to this document and its products and specifications at any time without notice. Customers should obtain and confirm the latest product information and specifications before final design, purchase or use.

Microdiode Electronics (Jiangsu) makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, not does Microdiode Electronics (Jiangsu) assume any liability for application assistance or customer product design. Microdiode Electronics (Jiangsu) does not warrant or accept any liability with products which are purchased or used for any unintended or unauthorized application.

No license is granted by implication or otherwise under any intellectual property rights of Microdiode Electronics (Jiangsu).

Microdiode Electronics (Jiangsu) products are not authorized for use as critical components in life support devices or systems without express written approval of Microdiode Electronics (Jiangsu).