

USB-C Multiport Adapter, DVI, USB-A Port, Gbe and PD Charging, White

MODEL NUMBER: U444-06N-DGU-C



Mini docking station adds DVI, USB-A, USB-C PD charging and Gigabit Ethernet ports to the USB-C or Thunderbolt 3 port on your tablet, laptop, notebook, MacBook, Chromebook, smartphone or PC.

Features

Mini Docking Station Turns Your Device's USB-C Port into a Multiport Workstation Ideal for transmitting video to a large display, adding a USB peripheral, powering and charging a PD Charging-compliant mobile device, and connecting to a Gigabit Ethernet network simultaneously. Plug-and-play operation with no software, drivers or external power required. About the size of a credit card for easy carrying in a pocket, purse or laptop bag.

Transmit Crystal-Clear 1080p Video to DVI Display Compatible with USB-C or Thunderbolt 3 source devices that support USB DisplayPort Alternate Mode. Supports DVI single-link video resolutions up to 1920 x 1080 (1080p) @ 60 Hz. Supports DVI digital transfer rates up to 6.75 Gbps (2.25 Gbps per channel). Extends video from your primary display to another. Duplicates the same video on 2 displays. Converts a secondary display to your primary display.

Connect a USB Peripheral USB-A port accepts flash drives, mice, keyboards, printers and other USB peripherals. Supports USB 3.1 Gen 1 data transfer rates up to 5 Gbps. Backward compatible with USB 2.0 and USB 1.1. BC 1.2-compliant port provides up to 1.5A of fast-charging power to mobile devices. Note: Host must support USB OTG (On-the-Go).

Charge a Connected Device USB-C PD port connects to wall charger to power and charge the connected PD Charging-compliant USB-C/Thunderbolt 3 device. Supports power input up to 20V 3A (60W). Note: USB-C PD port does not support Quick Charge (QC).

Access a Wired Gigabit Ethernet Network RJ45 port supports true 10/100/1000 Mbps network speeds. Recommended for a faster wired network connection or getting online when no Wi-Fi is available.

Built-In Cable with Reversible USB-C Connector Fumble-free reversible USB-C plug connects in either direction for quick connection every time.

Specifications

Highlights

- Supports USB DisplayPort Alternate Mode for transmitting video
- Supports DVI video resolutions up to 1920 x 1080 (1080p) @ 60 Hz
- Supports true 10/100/1000 Mbps Ethernet network speeds
- PD Charging port supports power input up to 20V 3A
- BC 1.2-compliant USB-A port provides up to 1.5A of fast-charging power
- Plug-and-play operation with no software or drivers required

Applications

- Establish a connection with a Gigabit Ethernet network via the RJ45 port
- Charge the host computer with up to 20V/3A (60W) of power
- Connect a USB peripheral or charge a connected device via the USB-A port
- Connect to a DVI monitor via the USB-C port on your computer, laptop or tablet

System Requirements

- Source device with USB-C or Thunderbolt 3 port that supports USB DisplayPort Alternate Mode
- Display device with DVI input (DVI port)

Package Includes

- U444-06N-DGU-C USB 3.1 Gen 1 USB-C to DVI Adapter
- Owner's manual

OVERVIEW	
UPC Code	037332193919
Product Type	USB-C to DVI Adapter
Technology	Cat5/5e; Cat6; DVI
Host Connector	USB C (MALE)
VIDEO	
Video Input	USB C (MALE)
Video Output	DVI-I DUAL LINK (FEMALE)
Number of Monitors Supported	1
Video Ports	DVI-I DUAL LINK (FEMALE)
Video Ports Details	HDCP 1.3
Resolutions Supported	1080P @ 60Hz (1920 x 1200)
Supported Resolutions	1920x1080 (1080p)
Max Supported Video Resolution	DVI: 1920 X 1080 (1080P) @ 60HZ
Extended Mode	No
Mirror Mode	No
3D Video Supported	No
AUDIO	
Audio Specification	Pass-through audio
DATA	
Data Ports	USB A (FEMALE)
Data Ports Details	USB-A - USB 3.2 Gen 1 (5 Gbps)
NETWORK	
Network Ports	RJ45 (FEMALE)
INPUT	
Built-In Cable Length (ft.)	0.36
Built-In Cable Length (m)	11.0
Built-In Cable Length (in.)	4.33
Bus Powered	Yes
Product Length (in.)	6
Product Length (cm.)	15.24

Product Length (ft.)	0.5
Product Length (m.)	0.15
BATTERY	
Battery Charging (5V/1.5A Port)	Yes
POWER	
Power Consumption (Watts)	2.40
USB Power Delivery (PD) Charging Support	Yes
USB Power Delivery (PD) Charging Specification	2.0
USER INTERFACE, ALERTS & CONTROLS	
LED Indicators	Green = Connected, Orange = Activity
CHARGING	
Total Charging Watts	60
Charging Ports Details	Charge the host PC with up to 20V/3A (60W) of power
Charging Ports	USB-C: 60W (20V 3A) Power Delivery (PD 2.0); USB-A: 5V 1.5A (7.5W)
Charging Ports / Amps	1.5A; 3A
PHYSICAL	
Color	White
Material of Construction	PVC, ABS
Cable Jacket Rating	VW-1
Shipping Dimensions (hwd / in.)	0.91 x 3.99 x 5.51
Shipping Dimensions (hwd / cm)	2.31 x 10.13 x 14.00
Shipping Weight (lbs.)	0.11
Shipping Weight (kg)	0.05
Unit Dimensions (hwd / in.)	0.650 x 3.800 x 1.600
Unit Packaging Type	Box
Unit Weight (lbs.)	0.09
Unit Weight (kg)	0.04
ENVIRONMENTAL	
Operating Temperature Range	32 to 113 F (0 to 45 C)
Storage Temperature Range	14 to 158 F (-10 to 70 C)
BTUs	8.3 BTU/Hr

Operating Humidity Range	10% to 85% RH, Non-Condensing
Storage Humidity Range	5% to 90% RH, Non-Condensing
Power Provided to Connected Device(s)	5V 1.5A (7.5W) Output (USB-A), Up to 20V 3A (60W) Input (USB-C)
CONNECTIONS	
Number of Ports	4
Side A - Connector 1	USB C (MALE)
Side B - Connector 1	DVI-I DUAL LINK (FEMALE)
Side B - Connector 2	USB 3.0 A (FEMALE)
Side B - Connector 3	RJ45 (FEMALE)
Side B - Connector 4	USB C (FEMALE)
Connector Plating	Nickel
FEATURES & SPECIFICATIONS	
HDCP Specification	1.3
USB Specification	USB 3.0 (up to 5 Gbps); USB 3.1 Gen 1 (up to 5 Gbps)
Driver Required	No
UASP Support	No
Auto MDIX Support	No
Full Duplex Support	No
Suspend Mode Support	No
Remote Wakeup Support	No
STANDARDS & COMPLIANCE	
Product Compliance	RoHS; CE (Europe); REACH; FCC (USA)
WARRANTY & SUPPORT	
Product Warranty Period (Worldwide)	3-year limited warranty