

TLE202x-Q1, TLE202xA-Q1  
EXCALIBUR HIGH-SPEED LOW-POWER PRECISION  
OPERATIONAL AMPLIFIERS

SGLS199B – JANUARY 2004 – REVISED APRIL 2008

- Qualified for Automotive Applications
- ESD Protection Exceeds 1000 V Per MIL-STD-883, Method 3015; Exceeds 200 V Using Machine Model (C = 200 pF, R = 0)
- Supply Current . . . 300  $\mu$ A Max
- High Unity-Gain Bandwidth . . . 2 MHz Typ
- High Slew Rate . . . 0.45 V/ $\mu$ s Min
- Supply-Current Change Over Full Temp Range . . . 10  $\mu$ A Typ at  $V_{CC} \pm = \pm 15$  V
- Specified for Both 5-V Single-Supply and  $\pm 15$ -V Operation
- Phase-Reversal Protection
- High Open-Loop Gain . . . 6.5 V/ $\mu$ V (136 dB) Typ
- Low Offset Voltage . . . 100  $\mu$ V Max
- Offset Voltage Drift With Time 0.005  $\mu$ V/mo Typ
- Low Input Bias Current . . . 50 nA Max
- Low Noise Voltage . . . 19 nV/ $\sqrt{\text{Hz}}$  Typ

### description

The TLE202x and TLE202xA devices are precision, high-speed, low-power operational amplifiers using a new Texas Instruments Excalibur process. These devices combine the best features of the OP21 with highly improved slew rate and unity-gain bandwidth.

The complementary bipolar Excalibur process utilizes isolated vertical pnp transistors that yield dramatic improvement in unity-gain bandwidth and slew rate over similar devices.

The addition of a bias circuit in conjunction with this process results in extremely stable parameters with both time and temperature. This means that a precision device remains a precision device even with changes in temperature and over years of use.

This combination of excellent dc performance with a common-mode input voltage range that includes the negative rail makes these devices the ideal choice for low-level signal conditioning applications in either single-supply or split-supply configurations. In addition, these devices offer phase-reversal protection circuitry that eliminates an unexpected change in output states when one of the inputs goes below the negative supply rail.

A variety of available options includes small-outline versions for high-density systems applications.

The Q-suffix devices are characterized for operation over the full automotive temperature range of  $-40^{\circ}\text{C}$  to  $125^{\circ}\text{C}$ .



Please be aware that an important notice concerning availability, standard warranty, and use in critical applications of Texas Instruments semiconductor products and disclaimers thereto appears at the end of this data sheet.

PRODUCTION DATA information is current as of publication date. Products conform to specifications per the terms of Texas Instruments standard warranty. Production processing does not necessarily include testing of all parameters.

Copyright © 2008, Texas Instruments Incorporated



POST OFFICE BOX 655303 • DALLAS, TEXAS 75265

**TLE202x-Q1, TLE202xA-Q1  
EXCALIBUR HIGH-SPEED LOW-POWER PRECISION  
OPERATIONAL AMPLIFIERS**

SGLS199B – JANUARY 2004 – REVISED APRIL 2008




**ORDERING INFORMATION<sup>†</sup>**

T <sub>A</sub>	V <sub>IOMAX</sub> AT 25°C	PACKAGE <sup>‡</sup>		ORDERABLE PART NUMBER	TOP-SIDE MARKING
–40°C to 125°C	200 µV	SOIC (D)	Tape and reel	TLE2021AQDRQ1	2021AQ
		TSSOP (PW)	Tape and reel	TLE2021AQPWRQ1§	2021AQ
	500 µV	SOIC (D)	Tape and reel	TLE2021QDRQ1	2021Q1
		TSSOP (PW)	Tape and reel	TLE2021QPWRQ1§	2021Q1
–40°C to 125°C	300 µV	SOIC (D)	Tape and reel	TLE2022AQDRQ1	2021AQ
		TSSOP (PW)	Tape and reel	TLE2022AQPWRQ1§	2022AQ1
	500 µV	SOIC (D)	Tape and reel	TLE2022QDRQ1	2022Q1
		TSSOP (PW)	Tape and reel	TLE2022QPWRQ1§	2022Q1
–40°C to 125°C	750 µV	SOP (DW)	Tape and reel	TLE2024AQDWRQ1	2024AQ1
	1000 µV	SOP (DW)	Tape and reel	TLE2024QDWRQ1	2024Q1

<sup>†</sup> For the most current package and ordering information, see the Package Option Addendum at the end of this document, or see the TI web site at <http://www.ti.com>.

<sup>‡</sup> Package drawings, thermal data, and symbolization are available at <http://www.ti.com/packaging>.

§ Product preview




NC – No internal connection

TLE202x-Q1, TLE202xA-Q1  
**EXCALIBUR HIGH-SPEED LOW-POWER PRECISION  
 OPERATIONAL AMPLIFIERS**

SGLS199B – JANUARY 2004 – REVISED APRIL 2008

**equivalent schematic (each amplifier)**



ACTUAL DEVICE COMPONENT COUNT			
COMPONENT	TLE2021	TLE2022	TLE2024
Transistors	40	80	160
Resistors	7	14	28
Diodes	4	8	16
Capacitors	4	8	16

**TLE202x-Q1, TLE202xA-Q1  
EXCALIBUR HIGH-SPEED LOW-POWER PRECISION  
OPERATIONAL AMPLIFIERS**

SGLS199B – JANUARY 2004 – REVISED APRIL 2008

**absolute maximum ratings over operating free-air temperature range (unless otherwise noted)<sup>†</sup>**

Supply voltage, $V_{CC+}$ (see Note 1) .....	20 V
Supply voltage, $V_{CC-}$ (see Note 1) .....	-20 V
Differential input voltage, $V_{ID}$ (see Note 2) .....	$\pm 0.6$ V
Input voltage range, $V_I$ (any input, see Note 1) .....	$\pm V_{CC}$
Input current, $I_I$ (each input) .....	$\pm 1$ mA
Output current, $I_O$ (each output): TLE2021 .....	$\pm 20$ mA
TLE2022 .....	$\pm 30$ mA
TLE2024 .....	$\pm 40$ mA
Total current into $V_{CC+}$ .....	80 mA
Total current out of $V_{CC-}$ .....	80 mA
Duration of short-circuit current at (or below) 25°C (see Note 3) .....	unlimited
Operating free-air temperature range, $T_A$ : Q suffix .....	-40°C to 125°C
Operating virtual junction temperature, $T_J$ .....	150°C
Packaging thermal impedance, $R_{\theta JA}$ (see Notes 4 and 5): D (8 pin) .....	97°C/W
DW (16 pin) .....	57°C/W
PW (8 pin) .....	149°C/W
PW (14 pin) .....	113°C/W
Storage temperature range, $T_{stg}$ .....	-65°C to 150°C
Lead temperature 1.6 mm (1/16 inch) from case for 3 seconds: D or PW package .....	300°C

<sup>†</sup> Stresses beyond those listed under "absolute maximum ratings" may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated under "recommended operating conditions" is not implied. Exposure to absolute-maximum-rated conditions for extended periods may affect device reliability.

- NOTES:
1. All voltage values, except differential voltages, are with respect to the midpoint between  $V_{CC+}$ , and  $V_{CC-}$ .
  2. Differential voltages are at IN+ with respect to IN-. Excessive current flows if a differential input voltage in excess of approximately  $\pm 600$  mV is applied between the inputs unless some limiting resistance is used.
  3. The output may be shorted to either supply. Temperature and/or supply voltages must be limited to ensure that the maximum dissipation rating is not exceeded.
  4. Maximum power dissipation is a function of  $T_J(\text{max})$ ,  $\theta_{JA}$ , and  $T_A$ . The maximum allowable power dissipation at any allowable ambient temperature is  $P_D = (T_J(\text{max}) - T_A)/\theta_{JA}$ . Selecting the maximum of 150°C can affect reliability.
  5. The package thermal impedance is calculated in accordance with JESD 51-7.

**recommended operating conditions**

	MIN	MAX	UNIT
Supply voltage, $V_{CC}$	$\pm 2$	$\pm 20$	V
Common-mode input voltage, $V_{IC}$	$V_{CC} = \pm 5$ V	0	V
	$V_{CC\pm} = \pm 15$ V	-15	
Operating free-air temperature, $T_A$	-40	125	°C

**TLE202x-Q1, TLE202xA-Q1**  
**EXCALIBUR HIGH-SPEED LOW-POWER PRECISION**  
**OPERATIONAL AMPLIFIERS**

SGLS199B – JANUARY 2004 – REVISED APRIL 2008

**TLE2021 electrical characteristics at specified free-air temperature,  $V_{CC} = 5$  V (unless otherwise noted)**

PARAMETER	TEST CONDITIONS	$T_A^\dagger$	TLE2021-Q1			TLE2021A-Q1			UNIT
			MIN	TYP	MAX	MIN	TYP	MAX	
$V_{IO}$	$V_{IC} = 0$ , $R_S = 50\ \Omega$	25°C	120	600	600	100	400	400	$\mu$ V
		Full range		800			550		
		Full range		2			2		$\mu$ V/°C
		25°C		0.005			0.005		$\mu$ V/mo
		25°C	0.2	6	6	0.2	6	6	nA
		Full range		10			10		
$I_{IO}$		25°C	25	70	70	25	70	70	nA
		Full range		90			90		
$V_{ICR}$	$R_S = 50\ \Omega$	25°C	0 to 3.5	-0.3 to 4	0 to 3.5	-0.3 to 4	0 to 3.5	-0.3 to 4	V
		Full range	0 to 3.2		0 to 3.2	0 to 3.2	0 to 3.2		
		25°C	4	4.3	4	4.3	4	4.3	V
		Full range	3.8		3.8		3.8		
$V_{OL}$	$R_L = 10\ k\Omega$	25°C	0.7	0.8	0.8	0.7	0.8	0.8	V
		Full range		0.95			0.95		
$A_{VD}$	$V_O = 1.4\ V$ to $4\ V$ , $R_L = 10\ k\Omega$	25°C	0.3	1.5	1.5	0.3	1.5	1.5	V/ $\mu$ V
		Full range	0.1			0.1			
CMRR	$V_{IC} = V_{ICR\min}$ , $R_S = 50\ \Omega$	25°C	85	110	110	85	110	110	dB
		Full range	80			80			
$k_{SVR}$	$V_{CC} = 5\ V$ to $30\ V$	25°C	105	120	120	105	120	120	dB
		Full range	100			100			
$I_{CC}$	$V_O = 2.5\ V$ , No load	25°C	170	300	300	170	300	300	$\mu$ A
		Full range		300			300		
$\Delta I_{CC}$		Full range		9			9		$\mu$ A

<sup>†</sup> Full range is -40°C to 125°C.

NOTE 4: Typical values are based on the input offset voltage shift observed through 168 hours of operating life test at  $T_A = 150^\circ\text{C}$  extrapolated to  $T_A = 25^\circ\text{C}$  using the Arrhenius equation and assuming an activation energy of 0.96 eV.

**TLE202x-Q1, TLE202xA-Q1  
EXCALIBUR HIGH-SPEED LOW-POWER PRECISION  
OPERATIONAL AMPLIFIERS**

SGLS199B – JANUARY 2004 – REVISED APRIL 2008

**TLE2021 electrical characteristics at specified free-air temperature,  $V_{CC} = \pm 15$  V (unless otherwise noted)**

PARAMETER	TEST CONDITIONS	$T_A^\dagger$	TLE2021-Q1			TLE2021A-Q1			UNIT
			MIN	TYP	MAX	MIN	TYP	MAX	
$V_{IO}$ Input offset voltage	$V_{IC} = 0$ , $R_S = 50\Omega$	25°C	120	500		80	300		$\mu V$
		Full range		700			450		
		Full range		2		2			$\mu V/^\circ C$
		25°C	0.006			0.006			$\mu V/mo$
		25°C	0.2	6		0.2	6		$nA$
		Full range		10			10		
		25°C	25	70		25	70		$nA$
		Full range		90			90		
		25°C	-15 to 13.5	-15.3 to 14		-15 to 13.5	-15.3 to 14		$V$
		Full range	-15 to 13.2		-15 to 13.2				
$V_{OM+}$ Maximum positive peak output voltage swing	$R_L = 10 k\Omega$	25°C	14	14.3		14	14.3		$V$
		Full range	13.8			13.8			
		25°C	-13.7	-14.1		-13.7	-14.1		$V$
		Full range	-13.6			-13.6			
$A_{VD}$ Large-signal differential voltage amplification	$V_O = \pm 10 V$ , $R_L = 10 k\Omega$	25°C	1	6.5		1	6.5		$V/\mu V$
		Full range	0.5			0.5			
$CMRR$ Common-mode rejection ratio	$V_{IC} = V_{ICRmin}$ , $R_S = 50\Omega$	25°C	100	115		100	115		$dB$
		Full range	96			96			
$k_{SVR}$ Supply-voltage rejection ratio ( $\Delta V_{CC\pm}/\Delta V_{IO}$ )	$V_{CC\pm} = \pm 2.5 V$ to $\pm 15 V$	25°C	105	120		105	120		$dB$
		Full range	100			100			
$I_{CC}$ Supply current	$V_O = 0$ ,	25°C	200	350		200	350		$\mu A$
		Full range		350			350		
$\Delta I_{CC}$ Supply current change over operating temperature range	No load	Full range		10			10		$\mu A$

<sup>†</sup> Full range is  $-40^\circ C$  to  $125^\circ C$ .

NOTE 4: Typical values are based on the input offset voltage shift observed through 168 hours of operating life test at  $T_A = 150^\circ C$  extrapolated to  $T_A = 25^\circ C$  using the Arrhenius equation and assuming an activation energy of 0.96 eV.

**TLE202x-Q1, TLE202xA-Q1**  
**EXCALIBUR HIGH-SPEED LOW-POWER PRECISION**  
**OPERATIONAL AMPLIFIERS**

SGS199B – JANUARY 2004 – REVISED APRIL 2008

**TLE2022 electrical characteristics at specified free-air temperature,  $V_{CC} = 5\text{ V}$  (unless otherwise noted)**

PARAMETER	TEST CONDITIONS	$T_A^\dagger$	TLE2022-Q1			TLE2022A-Q1			UNIT
			MIN	TYP	MAX	MIN	TYP	MAX	
$V_{IO}$	$V_{IC} = 0, R_S = 50\Omega$	25°C	600		400				$\mu\text{V}$
		Full range	800		550				
		Full range	2		2				$\mu\text{V}/^\circ\text{C}$
		25°C	0.005		0.005				$\mu\text{V}/\text{mo}$
		25°C	0.5	6		0.4	6		$\text{nA}$
		Full range		10			10		
		25°C	35	70		33	70		$\text{nA}$
		Full range		90			90		
$V_{ICR}$	$R_S = 50\Omega$	25°C	0 to 3.5	-0.3 to 4		0 to 3.5	-0.3 to 4		$\text{V}$
		Full range	0 to 3.2		0 to 3.2				
		25°C	4	4.3		4	4.3		$\text{V}$
		Full range	3.8		3.8				
$V_{OL}$	$R_L = 10\text{ k}\Omega$	25°C	0.7	0.8		0.7	0.8		$\text{V}$
		Full range		0.95			0.95		
$A_{VD}$	$V_O = 1.4\text{ V to }4\text{ V}, R_L = 10\text{ k}\Omega$	25°C	0.3	1.5		0.4	1.5		$\text{V}/\mu\text{V}$
		Full range	0.1		0.1				
CMRR	$V_{IC} = V_{ICR\min}, R_S = 50\Omega$	25°C	85	100		87	102		$\text{dB}$
		Full range	80		82				
$k_{SVR}$	$V_{CC} = 5\text{ V to }30\text{ V}$	25°C	100	115		103	118		$\text{dB}$
		Full range	95		98				
$I_{CC}$	$V_O = 2.5\text{ V}, \text{No load}$	25°C	450	600		450	600		$\mu\text{A}$
		Full range		600			600		
$\Delta I_{CC}$		Full range		37			37		$\mu\text{A}$

<sup>†</sup> Full range is  $-40^\circ\text{C}$  to  $125^\circ\text{C}$ .

NOTE 4: Typical values are based on the input offset voltage shift observed through 168 hours of operating life test at  $T_A = 150^\circ\text{C}$  extrapolated to  $T_A = 25^\circ\text{C}$  using the Arrhenius equation and assuming an activation energy of 0.96 eV.

**TLE202x-Q1, TLE202xA-Q1  
EXCALIBUR HIGH-SPEED LOW-POWER PRECISION  
OPERATIONAL AMPLIFIERS**

SGLS199B – JANUARY 2004 – REVISED APRIL 2008

**TLE2022 electrical characteristics at specified free-air temperature,  $V_{CC} = \pm 15$  V (unless otherwise noted)**

PARAMETER	TEST CONDITIONS	$T_A^\dagger$	TLE2022-Q1			TLE2022A-Q1			UNIT	
			MIN	TYP	MAX	MIN	TYP	MAX		
$V_{IO}$ Input offset voltage	$V_{IC} = 0$ , $R_S = 50\Omega$	25°C	150	500		120	300		$\mu V$	
		Full range		700			450			
		Full range		2			2		$\mu V/^\circ C$	
		25°C	0.006			0.006			$\mu V/mo$	
		25°C	0.5	6		0.4	6		$nA$	
		Full range		10			10			
$I_{IO}$ Input offset current	$R_S = 50\Omega$	25°C	35	70		33	70		$nA$	
		Full range		90			90			
$V_{ICR}$ Common-mode input voltage range		25°C	-15 to 13.5	-15.3 to 14		-15 to 13.5	-15.3 to 14		$V$	
		Full range	-15 to 13.2			-15 to 13.2				
$R_L = 10\text{ k}\Omega$	25°C	14	14.3		14	14.3		$V$		
	Full range	13.8			13.8					
	25°C	-13.7	-14.1		-13.7	-14.1		$V$		
	Full range	-13.6			-13.6					
$A_{VD}$ Large-signal differential voltage amplification	$V_O = \pm 10\text{ V}$ , $R_L = 10\text{ k}\Omega$	25°C	0.8	4		1	7		$V/\mu V$	
		Full range	0.8			1				
$CMRR$ Common-mode rejection ratio	$V_{IC} = V_{ICR\min}$ , $R_S = 50\Omega$	25°C	95	106		97	109		$dB$	
		Full range	91			93				
$k_{SVR}$ Supply-voltage rejection ratio ( $\Delta V_{CC\pm}/\Delta V_{IO}$ )	$V_{CC\pm} = \pm 2.5\text{ V to } \pm 15\text{ V}$	25°C	100	115		103	118		$dB$	
		Full range	95			98				
$I_{CC}$ Supply current	$V_O = 0$ , No load	25°C	550	700		550	700		$\mu A$	
		Full range		700			700			
$\Delta I_{CC}$ Supply current change over operating temperature range		Full range		60			60		$\mu A$	

<sup>†</sup> Full range is -40°C to 125°C.

NOTE 4: Typical values are based on the input offset voltage shift observed through 168 hours of operating life test at  $T_A = 150^\circ C$  extrapolated to  $T_A = 25^\circ C$  using the Arrhenius equation and assuming an activation energy of 0.96 eV.

**TLE202x-Q1, TLE202xA-Q1**  
**EXCALIBUR HIGH-SPEED LOW-POWER PRECISION**  
**OPERATIONAL AMPLIFIERS**

SGS199B – JANUARY 2004 – REVISED APRIL 2008

**TLE2024 electrical characteristics at specified free-air temperature,  $V_{CC} = 5$  V (unless otherwise noted)**

PARAMETER	TEST CONDITIONS	$T_A^\dagger$	TLE2024-Q1			TLE2024A-Q1			UNIT
			MIN	TYP	MAX	MIN	TYP	MAX	
$V_{IO}$ Input offset voltage	$V_{IC} = 0$ , $R_S = 50\ \Omega$	25°C	1100			850			$\mu\text{V}$
		Full range	1300			1050			
		Full range	2			2			$\mu\text{V}/^\circ\text{C}$
		25°C	0.005			0.005			$\mu\text{V}/\text{mo}$
$I_{IO}$ Input offset current	$R_L = 10\ \text{k}\Omega$	25°C	0.6	6		0.5	6		$\text{nA}$
		Full range	10			10			
		25°C	45	70		40	70		$\text{nA}$
		Full range	90			90			
$V_{ICR}$ Common-mode input voltage range	$R_S = 50\ \Omega$	25°C	0	-0.3		0	-0.3		$\text{V}$
			to	to		to	to		
			3.5	4		3.5	4		
		Full range	0			0			
$V_{OH}$ High-level output voltage	$V_O = 1.4\ \text{V to } 4\ \text{V},\ R_L = 10\ \text{k}\Omega$	25°C	3.9	4.2		3.9	4.2		$\text{V}$
		Full range	3.7			3.7			
		25°C	0.7	0.8		0.7	0.8		$\text{V}$
		Full range	0.95			0.95			
$A_{VD}$ Large-signal differential voltage amplification	$V_{IC} = V_{ICR\min},\ R_S = 50\ \Omega$	25°C	0.2	1.5		0.3	1.5		$\text{V}/\mu\text{V}$
		Full range	0.1			0.1			
CMRR Common-mode rejection ratio	$V_{CC\pm} = \pm 2.5\ \text{V to } \pm 15\ \text{V}$	25°C	80	90		82	92		$\text{dB}$
		Full range	80			82			
$k_{SVR}$ Supply-voltage rejection ratio ( $\Delta V_{CC\pm}/\Delta V_{IO}$ )	$V_O = 0$ , No load	25°C	98	112		100	115		$\text{dB}$
		Full range	93			95			
$I_{CC}$ Supply current	$V_O = 0$ , No load	25°C	800	1200		800	1200		$\mu\text{A}$
		Full range	1200			1200			
		Full range	50			50			$\mu\text{A}$

<sup>†</sup> Full range is -40°C to 125°C.

NOTE 4: Typical values are based on the input offset voltage shift observed through 168 hours of operating life test at  $T_A = 150^\circ\text{C}$  extrapolated to  $T_A = 25^\circ\text{C}$  using the Arrhenius equation and assuming an activation energy of 0.96 eV.

**TLE202x-Q1, TLE202xA-Q1  
EXCALIBUR HIGH-SPEED LOW-POWER PRECISION  
OPERATIONAL AMPLIFIERS**

SGLS199B – JANUARY 2004 – REVISED APRIL 2008

**TLE2024 electrical characteristics at specified free-air temperature,  $V_{CC} = \pm 15$  V (unless otherwise noted)**

PARAMETER	TEST CONDITIONS	$T_A^\dagger$	TLE2024-Q1			TLE2024A-Q1			UNIT
			MIN	TYP	MAX	MIN	TYP	MAX	
$V_{IO}$	$V_{IC} = 0$ , $R_S = 50\Omega$	25°C	1000			750			$\mu V$
$\alpha V_{IO}$		Full range		1200			950		
		Full range		2		2			
Input offset voltage long-term drift (see Note 4)		25°C	0.006			0.006			$\mu V/\text{mo}$
$I_{IO}$		25°C	0.6	6		0.2	6		$nA$
		Full range		10			10		
$I_{IB}$	$V_{IC} = V_{ICR\min}$ , $R_S = 50\Omega$	25°C	50	70		45	70		$nA$
		Full range		90			90		
$V_{ICR}$		25°C	-15	-15.3		-15	-15.3		$V$
Common-mode input voltage range			to	to		to	to		
			13.5	14		13.5	14		
		Full range	-15			-15			
			to			to			
			13.2			13.2			
$V_{OM+}$	$R_L = 10\text{ k}\Omega$	25°C	13.8	14.1		13.8	14.2		$V$
Maximum positive peak output voltage swing		Full range	13.7			13.7			
$V_{OM-}$		25°C	-13.7	-14.1		-13.7	-14.1		$V$
Maximum negative peak output voltage swing		Full range	-13.6			-13.6			
$A_{VD}$	$V_O = \pm 10\text{ V}$ , $R_L = 10\text{ k}\Omega$	25°C	0.4	2		0.8	4		$V/\mu V$
Large-signal differential voltage amplification		Full range	0.4			0.8			
$CMRR$	$V_{IC} = V_{ICR\min}$ , $R_S = 50\Omega$	25°C	92	102		94	105		$\text{dB}$
Common-mode rejection ratio		Full range	88			90			
$k_{SVR}$	$V_{CC\pm} = \pm 2.5\text{ V}$ to $\pm 15\text{ V}$	25°C	98	112		100	115		$\text{dB}$
Supply-voltage rejection ratio ( $\Delta V_{CC\pm}/\Delta V_{IO}$ )		Full range	93			95			
$I_{CC}$	$V_O = 0$ , No load	25°C	1050	1400		1050	1400		$\mu A$
Supply current		Full range		1400			1400		
$\Delta I_{CC}$		Full range		85		85			$\mu A$

<sup>†</sup> Full range is -40°C to 125°C.

NOTE 4: Typical values are based on the input offset voltage shift observed through 168 hours of operating life test at  $T_A = 150^\circ\text{C}$  extrapolated to  $T_A = 25^\circ\text{C}$  using the Arrhenius equation and assuming an activation energy of 0.96 eV.



POST OFFICE BOX 655303 • DALLAS, TEXAS 75265

**TLE202x-Q1, TLE202xA-Q1**  
**EXCALIBUR HIGH-SPEED LOW-POWER PRECISION**  
**OPERATIONAL AMPLIFIERS**

SGS199B – JANUARY 2004 – REVISED APRIL 2008

**TLE2021 operating characteristics,  $V_{CC} = 5 \text{ V}$ ,  $T_A = 25^\circ\text{C}$**

PARAMETER	TEST CONDITIONS	$T_A$	MIN	TYP	MAX	UNIT
SR Slew rate at unity gain	$V_O = 1 \text{ V}$ to $3 \text{ V}$ , See Figure 1	$25^\circ\text{C}$		0.5		$\text{V}/\mu\text{s}$
$V_n$ Equivalent input noise voltage (see Figure 2)	$f = 10 \text{ Hz}$	$25^\circ\text{C}$		21		$\text{nV}/\text{Hz}$
	$f = 1 \text{ kHz}$	$25^\circ\text{C}$		17		
$V_{N(PP)}$ Peak-to-peak equivalent input noise voltage	$f = 0.1$ to $1 \text{ Hz}$	$25^\circ\text{C}$		0.16		$\mu\text{V}$
	$f = 0.1$ to $10 \text{ Hz}$	$25^\circ\text{C}$		0.47		
$I_n$ Equivalent input noise current		$25^\circ\text{C}$		0.9		$\text{pA}/\text{Hz}$
$B_1$ Unity-gain bandwidth	See Figure 3	$25^\circ\text{C}$		1.2		MHz
$\phi_m$ Phase margin at unity gain	See Figure 3	$25^\circ\text{C}$		42°		

**TLE2021 operating characteristics at specified free-air temperature,  $V_{CC} = \pm 15 \text{ V}$**

PARAMETER	TEST CONDITIONS	$T_A^\dagger$	MIN	TYP	MAX	UNIT
SR Slew rate at unity gain	$V_O = \pm 10 \text{ V}$ , See Figure 1	$25^\circ\text{C}$	0.45	0.65		$\text{V}/\mu\text{s}$
		Full range		0.4		
$V_n$ Equivalent input noise voltage (see Figure 2)	$f = 10 \text{ Hz}$	$25^\circ\text{C}$		19		$\text{nV}/\text{Hz}$
	$f = 1 \text{ kHz}$	$25^\circ\text{C}$		15		
$V_{N(PP)}$ Peak-to-peak equivalent input noise voltage	$f = 0.1$ to $1 \text{ Hz}$	$25^\circ\text{C}$		0.16		$\mu\text{V}$
	$f = 0.1$ to $10 \text{ Hz}$	$25^\circ\text{C}$		0.47		
$I_n$ Equivalent input noise current		$25^\circ\text{C}$		0.09		$\text{pA}/\text{Hz}$
$B_1$ Unity-gain bandwidth	See Figure 3	$25^\circ\text{C}$		2		MHz
$\phi_m$ Phase margin at unity gain	See Figure 3	$25^\circ\text{C}$		46°		

† Full range is  $-40^\circ\text{C}$  to  $125^\circ\text{C}$  for the Q-suffix devices.

**TLE2022 operating characteristics,  $V_{CC} = 5 \text{ V}$ ,  $T_A = 25^\circ\text{C}$**

PARAMETER	TEST CONDITIONS	MIN	TYP	MAX	UNIT
SR Slew rate at unity gain	$V_O = 1 \text{ V}$ to $3 \text{ V}$ , See Figure 1		0.5		$\text{V}/\mu\text{s}$
$V_n$ Equivalent input noise voltage (see Figure 2)	$f = 10 \text{ Hz}$		21		$\text{nV}/\text{Hz}$
	$f = 1 \text{ kHz}$		17		
$V_{N(PP)}$ Peak-to-peak equivalent input noise voltage	$f = 0.1$ to $1 \text{ Hz}$		0.16		$\mu\text{V}$
	$f = 0.1$ to $10 \text{ Hz}$		0.47		
$I_n$ Equivalent input noise current			0.1		$\text{pA}/\sqrt{\text{Hz}}$
$B_1$ Unity-gain bandwidth	See Figure 3		1.7		MHz
$\phi_m$ Phase margin at unity gain	See Figure 3		47°		

**TLE202x-Q1, TLE202xA-Q1  
EXCALIBUR HIGH-SPEED LOW-POWER PRECISION  
OPERATIONAL AMPLIFIERS**

SGLS199B – JANUARY 2004 – REVISED APRIL 2008

**TLE2022 operating characteristics at specified free-air temperature,  $V_{CC} = \pm 15$  V**

PARAMETER	TEST CONDITIONS	$T_A^\dagger$	MIN	TYP	MAX	UNIT
SR Slew rate at unity gain	$V_O = \pm 10$ V, See Figure 1	25°C	0.45	0.65		V/ $\mu$ s
		Full range	0.4			
$V_n$ Equivalent input noise voltage (see Figure 2)	f = 10 Hz	25°C	19			nV/ $\sqrt{\text{Hz}}$
	f = 1 kHz	25°C	15			
$V_{N(PP)}$ Peak-to-peak equivalent input noise voltage	f = 0.1 to 1 Hz	25°C	0.16			$\mu$ V
	f = 0.1 to 10 Hz	25°C	0.47			
$I_n$ Equivalent input noise current		25°C	0.1			pA/ $\sqrt{\text{Hz}}$
$B_1$ Unity-gain bandwidth	See Figure 3	25°C	2.8			MHz
$\phi_m$ Phase margin at unity gain	See Figure 3	25°C	52°			

† Full range is -40°C to 125°C.

**TLE2024 operating characteristics,  $V_{CC} = 5$  V,  $T_A = 25$  °C**


PARAMETER	TEST CONDITIONS	MIN	TYP	MAX	UNIT
SR Slew rate at unity gain	$V_O = 1$ V to 3 V, See Figure 1	0.5			V/ $\mu$ s
$V_n$ Equivalent input noise voltage (see Figure 2)	f = 10 Hz	21			nV/ $\sqrt{\text{Hz}}$
	f = 1 kHz	17			
$V_{N(PP)}$ Peak-to-peak equivalent input noise voltage	f = 0.1 to 1 Hz	0.16			$\mu$ V
	f = 0.1 to 10 Hz	0.47			
$I_n$ Equivalent input noise current		0.1			pA/ $\sqrt{\text{Hz}}$
$B_1$ Unity-gain bandwidth	See Figure 3	1.7			MHz
$\phi_m$ Phase margin at unity gain	See Figure 3	47°			

**TLE2024 operating characteristics at specified free-air temperature,  $V_{CC} = \pm 15$  V (unless otherwise noted)**


PARAMETER	TEST CONDITIONS	$T_A^\dagger$	MIN	TYP	MAX	UNIT
SR Slew rate at unity gain	$V_O = \pm 10$ V, See Figure 1	25°C	0.45	0.7		V/ $\mu$ s
		Full range	0.4			
$V_n$ Equivalent input noise voltage (see Figure 2)	f = 10 Hz	25°C	19			nV/ $\sqrt{\text{Hz}}$
	f = 1 kHz	25°C	15			
$V_{N(PP)}$ Peak-to-peak equivalent input noise voltage	f = 0.1 to 1 Hz	25°C	0.16			$\mu$ V
	f = 0.1 to 10 Hz	25°C	0.47			
$I_n$ Equivalent input noise current		25°C	0.1			pA/ $\sqrt{\text{Hz}}$
$B_1$ Unity-gain bandwidth	See Figure 3	25°C	2.8			MHz
$\phi_m$ Phase margin at unity gain	See Figure 3	25°C	52°			

† Full range is -40°C to 125°C.

## PARAMETER MEASUREMENT INFORMATION




(a) SINGLE SUPPLY




(b) SPLIT SUPPLY

NOTE A:  $C_L$  includes fixture capacitance.

**Figure 1. Slew-Rate Test Circuit**




(a) SINGLE SUPPLY




(b) SPLIT SUPPLY

**Figure 2. Noise-Voltage Test Circuit**



(a) SINGLE SUPPLY



(b) SPLIT SUPPLY


NOTE A:  $C_L$  includes fixture capacitance.

**Figure 3. Unity-Gain Bandwidth and Phase-Margin Test Circuit**


**TLE202x-Q1, TLE202xA-Q1  
EXCALIBUR HIGH-SPEED LOW-POWER PRECISION  
OPERATIONAL AMPLIFIERS**

SGLS199B – JANUARY 2004 – REVISED APRIL 2008

**PARAMETER MEASUREMENT INFORMATION**



(a) SINGLE SUPPLY



(b) SPLIT SUPPLY

NOTE A:  $C_L$  includes fixture capacitance.

**Figure 4. Small-Signal Pulse-Response Test Circuit**

**typical values**

Typical values presented in this data sheet represent the median (50% point) of device parametric performance.

**TLE202x-Q1, TLE202xA-Q1**  
**EXCALIBUR HIGH-SPEED LOW-POWER PRECISION**  
**OPERATIONAL AMPLIFIERS**

SGLS199B – JANUARY 2004 – REVISED APRIL 2008

## TYPICAL CHARACTERISTICS





**Table of Graphs**

		<b>FIGURE</b>
$V_{IO}$	Input offset voltage	Distribution 5, 6, 7
$I_{IB}$	Input bias current	vs Common-mode input voltage 8, 9, 10 vs Free-air temperature 11, 12, 13
$I_I$	Input current	vs Differential input voltage 14
$V_{OM}$	Maximum peak output voltage	vs Output current 15, 16, 17 vs Free-air temperature 18
$V_{OH}$	High-level output voltage	vs High-level output current 19, 20 vs Free-air temperature 21
$V_{OL}$	Low-level output voltage	vs Low-level output current 22 vs Free-air temperature 23
$V_{O(PP)}$	Maximum peak-to-peak output voltage	vs Frequency 24, 25
$A_{VD}$	Large-signal differential voltage amplification	vs Frequency 26 vs Free-air temperature 27, 28, 29
$I_{OS}$	Short-circuit output current	vs Supply voltage 30 – 33 vs Free-air temperature 34 – 37
$I_{CC}$	Supply current	vs Supply voltage 38, 39, 40 vs Free-air temperature 41, 42, 43
CMRR	Common-mode rejection ratio	vs Frequency 44, 45, 46
SR	Slew rate	vs Free-air temperature 47, 48, 49
	Voltage-follower small-signal pulse response	50, 51
	Voltage-follower large-signal pulse response	52 – 57
$V_{N(PP)}$	Peak-to-peak equivalent input noise voltage	0.1 to 1 Hz 58 0.1 to 10 Hz 59
$V_n$	Equivalent input noise voltage	vs Frequency 60
$B_1$	Unity-gain bandwidth	vs Supply voltage 61, 62 vs Free-air temperature 63, 64
$\phi_m$	Phase margin	vs Supply voltage 65, 66 vs Load capacitance 67, 68 vs Free-air temperature 69, 70
	Phase shift	vs Frequency 26

**TLE202x-Q1, TLE202xA-Q1  
EXCALIBUR HIGH-SPEED LOW-POWER PRECISION  
OPERATIONAL AMPLIFIERS**

SGLS199B – JANUARY 2004 – REVISED APRIL 2008

**TYPICAL CHARACTERISTICS**



## TYPICAL CHARACTERISTICS




Figure 9




Figure 10




Figure 11




Figure 12

† Data at high and low temperatures are applicable only within the rated operating free-air temperature ranges of the various devices.

**TLE202x-Q1, TLE202xA-Q1  
EXCALIBUR HIGH-SPEED LOW-POWER PRECISION  
OPERATIONAL AMPLIFIERS**

SGLS199B – JANUARY 2004 – REVISED APRIL 2008

**TYPICAL CHARACTERISTICS**




Figure 13




Figure 14




Figure 15




Figure 16

<sup>†</sup> Data at high and low temperatures are applicable only within the rated operating free-air temperature ranges of the various devices.

## TYPICAL CHARACTERISTICS




Figure 17




Figure 18




Figure 19




Figure 20

<sup>†</sup> Data at high and low temperatures are applicable only within the rated operating free-air temperature ranges of the various devices.

**TLE202x-Q1, TLE202xA-Q1  
EXCALIBUR HIGH-SPEED LOW-POWER PRECISION  
OPERATIONAL AMPLIFIERS**

SGLS199B – JANUARY 2004 – REVISED APRIL 2008

**TYPICAL CHARACTERISTICS**




Figure 21




Figure 22




Figure 23





Figure 24

<sup>†</sup> Data at high and low temperatures are applicable only within the rated operating free-air temperature ranges of the various devices.


### TYPICAL CHARACTERISTICS

**MAXIMUM PEAK-TO-PEAK OUTPUT VOLTAGE  
 vs  
 FREQUENCY**



**Figure 25**

**LARGE-SIGNAL DIFFERENTIAL VOLTAGE  
 AMPLIFICATION AND PHASE SHIFT  
 vs  
 FREQUENCY**



**Figure 26**

**TLE202x-Q1, TLE202xA-Q1  
EXCALIBUR HIGH-SPEED LOW-POWER PRECISION  
OPERATIONAL AMPLIFIERS**

SGLS199B – JANUARY 2004 – REVISED APRIL 2008

**TYPICAL CHARACTERISTICS**




Figure 27




Figure 28




Figure 29




Figure 30

<sup>†</sup> Data at high and low temperatures are applicable only within the rated operating free-air temperature ranges of the various devices.

## TYPICAL CHARACTERISTICS




Figure 31




Figure 32




Figure 33




Figure 34

<sup>†</sup> Data at high and low temperatures are applicable only within the rated operating free-air temperature ranges of the various devices.

**TLE202x-Q1, TLE202xA-Q1  
EXCALIBUR HIGH-SPEED LOW-POWER PRECISION  
OPERATIONAL AMPLIFIERS**

SGLS199B – JANUARY 2004 – REVISED APRIL 2008

**TYPICAL CHARACTERISTICS**




Figure 35




Figure 36




Figure 37




Figure 38

<sup>†</sup> Data at high and low temperatures are applicable only within the rated operating free-air temperature ranges of the various devices.

## TYPICAL CHARACTERISTICS




Figure 39




Figure 40




Figure 41




Figure 42

<sup>†</sup> Data at high and low temperatures are applicable only within the rated operating free-air temperature ranges of the various devices.

**TLE202x-Q1, TLE202xA-Q1  
EXCALIBUR HIGH-SPEED LOW-POWER PRECISION  
OPERATIONAL AMPLIFIERS**

SGS199B – JANUARY 2004 – REVISED APRIL 2008

**TYPICAL CHARACTERISTICS**




Figure 43




Figure 44




Figure 45




Figure 46

<sup>†</sup> Data at high and low temperatures are applicable only within the rated operating free-air temperature ranges of the various devices.

### TYPICAL CHARACTERISTICS




Figure 47




Figure 48




Figure 49




Figure 50

<sup>†</sup> Data at high and low temperatures are applicable only within the rated operating free-air temperature ranges of the various devices.

**TLE202x-Q1, TLE202xA-Q1  
EXCALIBUR HIGH-SPEED LOW-POWER PRECISION  
OPERATIONAL AMPLIFIERS**

SGLS199B – JANUARY 2004 – REVISED APRIL 2008

**TYPICAL CHARACTERISTICS**




Figure 51




Figure 52




Figure 53




Figure 54

## TYPICAL CHARACTERISTICS




Figure 55




Figure 56




Figure 57




Figure 58

**TLE202x-Q1, TLE202xA-Q1  
EXCALIBUR HIGH-SPEED LOW-POWER PRECISION  
OPERATIONAL AMPLIFIERS**

SGLS199B – JANUARY 2004 – REVISED APRIL 2008

**TYPICAL CHARACTERISTICS**




Figure 59




Figure 60




Figure 61




Figure 62

## TYPICAL CHARACTERISTICS




Figure 63




Figure 64




Figure 65




Figure 66

† Data at high and low temperatures are applicable only within the rated operating free-air temperature ranges of the various devices.

**TLE202x-Q1, TLE202xA-Q1  
EXCALIBUR HIGH-SPEED LOW-POWER PRECISION  
OPERATIONAL AMPLIFIERS**

SGLS199B – JANUARY 2004 – REVISED APRIL 2008

**TYPICAL CHARACTERISTICS**




Figure 67




Figure 68




Figure 69





Figure 70

† Data at high and low temperatures are applicable only within the rated operating free-air temperature ranges of the various devices.

## APPLICATION INFORMATION

### voltage-follower applications


The TLE202x circuitry includes input-protection diodes to limit the voltage across the input transistors; however, no provision is made in the circuit to limit the current if these diodes are forward biased. This condition can occur when the device is operated in the voltage-follower configuration and driven with a fast, large-signal pulse. It is recommended that a feedback resistor be used to limit the current to a maximum of 1 mA to prevent degradation of the device. This feedback resistor forms a pole with the input capacitance of the device. For feedback resistor values greater than 10 k $\Omega$ , this pole degrades the amplifier phase margin. This problem can be alleviated by adding a capacitor (20 pF to 50 pF) in parallel with the feedback resistor (see Figure 71).



**Figure 71. Voltage Follower**

### Input offset voltage nulling

The TLE202x series offers external null pins that further reduce the input offset voltage. The circuit in Figure 72 can be connected as shown if this feature is desired. When external nulling is not needed, the null pins may be left disconnected.



**Figure 72. Input Offset Voltage Null Circuit**

# TLE202x-Q1, TLE202xA-Q1 EXCALIBUR HIGH-SPEED LOW-POWER PRECISION OPERATIONAL AMPLIFIERS

SGLS199B – JANUARY 2004 – REVISED APRIL 2008

## APPLICATION INFORMATION

### macromodel information

Macromodel information provided was derived using Microsim *Parts*™, the model generation software used with Microsim *PSpice*™. The Boyle macromodel (see Note 5) and subcircuit in Figure 73, Figure 74, and Figure 75 were generated using the TLE202x typical electrical and operating characteristics at 25°C. Using this information, output simulations of the following key parameters can be generated to a tolerance of 20% (in most cases):

- Maximum positive output voltage swing
- Maximum negative output voltage swing
- Slew rate
- Quiescent power dissipation
- Input bias current
- Open-loop voltage amplification
- Unity-gain frequency
- Common-mode rejection ratio
- Phase margin
- DC output resistance
- AC output resistance
- Short-circuit output current limit

NOTE 5: G. R. Boyle, B. M. Cohn, D. O. Pederson, and J. E. Solomon, "Macromodeling of Integrated Circuit Operational Amplifiers", *IEEE Journal of Solid-State Circuits*, SC-9, 353 (1974).




Figure 73. Boyle Subcircuit

*PSpice* and *Parts* are trademarks of MicroSim Corporation.

**TLE202x-Q1, TLE202xA-Q1**  
**EXCALIBUR HIGH-SPEED LOW-POWER PRECISION**  
**OPERATIONAL AMPLIFIERS**

SGLS199B – JANUARY 2004 – REVISED APRIL 2008

---

```
.SUBCKT TLE2021 1 2 3 4 5
*
c1 11 12 6.244E-12
c2 6 7 13.4E-12
c3 87 0 10.64E-9
cpsr 85 86 15.9E-9
dcm+ 81 82 dx
dcm- 83 81 dx
dc 5 53 dx
de 54 5 dx
dlp 90 91 dx
dln 92 90 dx
dp 4 3 dx
ecmr 84 99 (2 99) 1
egnd 99 0 poly(2) (3,0) (4,0) 0 .5 .5
epsr 85 0 poly(1) (3,4) -60E-6 2.0E-6
ense 89 2 poly(1) (88,0) 120E-6 1
fb 7 99 poly(6) vb vc ve vlp vln vpsr 0 547.3E6
+ -50E7 50E7 50E7 -50E7 547E6
ga 6 0 11 12 188.5E-6
gcm 0 6 10 99 335.2E-12
gpsr 85 86 (85,86) 100E-6
grc1 4 11 (4,11) 1.885E-4
grc2 4 12 (4,12) 1.885E-4
gre1 13 10 (13,10) 6.82E-4
gre2 14 10 (14,10) 6.82E-4
hlim 90 0 vlim 1k
```

```
hcmr 80 1 poly(2) vcm+ vcm- 0 1E2 1E2
irp 3 4 185E-6
iee 3 10 dc 15.67E-6
iio 2 0 2E-9
i1 88 0 1E-21
q1 11 89 13 qx
q2 12 80 14 qx
R2 6 9 100.0E3
rcm 84 81 1K
ree 10 99 14.76E6
rn1 87 0 2.55E8
rn2 87 88 11.67E3
ro1 8 5 62
ro2 7 99 63
vcm+ 82 99 13.3
vcm- 83 99 -14.6
vb 9 0 dc 0
vc 3 53 dc 1.300
ve 54 4 dc 1.500
vlim 7 8 dc 0
vlp 91 0 dc 3.600
vln 0 92 dc 3.600
vpsr 0 86 dc 0
.model dx d(is=800.0E-18)
.model qx pnp(is=800.0E-18 bf=270)
.ends
```

**Figure 74. Boyle Macromodel for the TLE2021**

---

```
.SUBCKT TLE2022 1 2 3 4 5
*
c1 11 12 6.814E-12
c2 6 7 20.00E-12
dc 5 53 dx
de 54 5 dx
dlp 90 91 dx
dln 92 90 dx
dp 4 3 dx
egnd 99 0 poly(2) (3,0) (4,0) 0 .5 .5
fb 7 99 poly(5) vb vc ve vlp vln 0
+ 45.47E6 -50E6 50E6 50E6 -50E6
ga 6 0 11 12 377.9E-6
gcm 0 6 10 99 7.84E-10
iee 3 10 DC 18.07E-6
hlim 90 0 vlim 1k
q1 11 2 13 qx
q2 12 1 14 qx
r2 6 9 100.0E3
```

```
rc1 4 11 2.842E3
rc2 4 12 2.842E3
gel 13 10 (10,13) 31.299E-3
ge2 14 10 (10,14) 31.299E-3
ree 10 99 11.07E6
rol 8 5 250
ro2 7 99 250
rp 3 4 137.2E3
vb 9 0 dc 0
vc 3 53 dc 1.300
ve 54 4 dc 1.500
vlim 7 8 dc 0
vlp 91 0 dc 3
vln 0 92 dc 3
.model dx d(is=800.0E-18)
.model qx pnp(is=800.0E-18 bf=257.1)
.ends
```

**Figure 75. Boyle Macromodel for the TLE2022**

**PACKAGING INFORMATION**

Orderable Device	Status (1)	Package Type	Package Drawing	Pins	Package Qty	Eco Plan (2)	Lead finish/ Ball material (6)	MSL Peak Temp (3)	Op Temp (°C)	Device Marking (4/5)	Samples
TLE2021AQDRG4Q1	ACTIVE	SOIC	D	8	2500	RoHS & Green	NIPDAU	Level-1-260C-UNLIM	-40 to 125	2021AQ	<span style="background-color: red; color: white;">Samples</span>
TLE2021AQDRQ1	ACTIVE	SOIC	D	8	2500	RoHS & Green	NIPDAU	Level-1-260C-UNLIM	-40 to 125	2021AQ	<span style="background-color: red; color: white;">Samples</span>
TLE2021QDRG4Q1	ACTIVE	SOIC	D	8	2500	RoHS & Green	NIPDAU	Level-1-260C-UNLIM	-40 to 125	2021Q1	<span style="background-color: red; color: white;">Samples</span>
TLE2021QDRQ1	ACTIVE	SOIC	D	8	2500	RoHS & Green	NIPDAU	Level-1-260C-UNLIM	-40 to 125	2021Q1	<span style="background-color: red; color: white;">Samples</span>
TLE2022AQDRG4Q1	ACTIVE	SOIC	D	8	2500	RoHS & Green	NIPDAU	Level-1-260C-UNLIM	-40 to 125	2022AQ	<span style="background-color: red; color: white;">Samples</span>
TLE2022QDRG4Q1	ACTIVE	SOIC	D	8	2500	RoHS & Green	NIPDAU	Level-1-260C-UNLIM	-40 to 125	2022Q1	<span style="background-color: red; color: white;">Samples</span>
TLE2022QDRQ1	ACTIVE	SOIC	D	8	2500	RoHS & Green	NIPDAU	Level-1-260C-UNLIM	-40 to 125	2022Q1	<span style="background-color: red; color: white;">Samples</span>
TLE2024QDWRG4Q1	ACTIVE	SOIC	DW	16	2000	RoHS & Green	NIPDAU	Level-1-260C-UNLIM	-40 to 125	2024Q1	<span style="background-color: red; color: white;">Samples</span>

(1) The marketing status values are defined as follows:

**ACTIVE:** Product device recommended for new designs.

**LIFEBUY:** TI has announced that the device will be discontinued, and a lifetime-buy period is in effect.

**NRND:** Not recommended for new designs. Device is in production to support existing customers, but TI does not recommend using this part in a new design.

**PREVIEW:** Device has been announced but is not in production. Samples may or may not be available.

**OBSOLETE:** TI has discontinued the production of the device.

(2) **RoHS:** TI defines "RoHS" to mean semiconductor products that are compliant with the current EU RoHS requirements for all 10 RoHS substances, including the requirement that RoHS substance do not exceed 0.1% by weight in homogeneous materials. Where designed to be soldered at high temperatures, "RoHS" products are suitable for use in specified lead-free processes. TI may reference these types of products as "Pb-Free".

**RoHS Exempt:** TI defines "RoHS Exempt" to mean products that contain lead but are compliant with EU RoHS pursuant to a specific EU RoHS exemption.

**Green:** TI defines "Green" to mean the content of Chlorine (Cl) and Bromine (Br) based flame retardants meet JS709B low halogen requirements of <=1000ppm threshold. Antimony trioxide based flame retardants must also meet the <=1000ppm threshold requirement.

(3) MSL, Peak Temp. - The Moisture Sensitivity Level rating according to the JEDEC industry standard classifications, and peak solder temperature.

(4) There may be additional marking, which relates to the logo, the lot trace code information, or the environmental category on the device.

(5) Multiple Device Markings will be inside parentheses. Only one Device Marking contained in parentheses and separated by a "~" will appear on a device. If a line is indented then it is a continuation of the previous line and the two combined represent the entire Device Marking for that device.

(6) Lead finish/Ball material - Orderable Devices may have multiple material finish options. Finish options are separated by a vertical ruled line. Lead finish/Ball material values may wrap to two lines if the finish value exceeds the maximum column width.

**Important Information and Disclaimer:** The information provided on this page represents TI's knowledge and belief as of the date that it is provided. TI bases its knowledge and belief on information provided by third parties, and makes no representation or warranty as to the accuracy of such information. Efforts are underway to better integrate information from third parties. TI has taken and continues to take reasonable steps to provide representative and accurate information but may not have conducted destructive testing or chemical analysis on incoming materials and chemicals. TI and TI suppliers consider certain information to be proprietary, and thus CAS numbers and other limited information may not be available for release.

In no event shall TI's liability arising out of such information exceed the total purchase price of the TI part(s) at issue in this document sold by TI to Customer on an annual basis.

**OTHER QUALIFIED VERSIONS OF TLE2021-Q1, TLE2021A-Q1, TLE2022-Q1, TLE2022A-Q1, TLE2024-Q1 :**

- Catalog : [TLE2021](#), [TLE2021A](#), [TLE2022](#), [TLE2022A](#), [TLE2024](#)
- Enhanced Product : [TLE2021-EP](#), [TLE2021A-EP](#), [TLE2022-EP](#), [TLE2022A-EP](#), [TLE2024-EP](#)
- Military : [TLE2021M](#), [TLE2021AM](#), [TLE2022M](#), [TLE2022AM](#), [TLE2024M](#)

**NOTE: Qualified Version Definitions:**

- Catalog - TI's standard catalog product
- Enhanced Product - Supports Defense, Aerospace and Medical Applications
- Military - QML certified for Military and Defense Applications

# GENERIC PACKAGE VIEW


DW 16

SOIC - 2.65 mm max height

7.5 x 10.3, 1.27 mm pitch


SMALL OUTLINE INTEGRATED CIRCUIT

This image is a representation of the package family, actual package may vary.  
Refer to the product data sheet for package details.



4224780/A


# DW0016A



## PACKAGE OUTLINE

SOIC - 2.65 mm max height

SOIC



4220721/A 07/2016

### NOTES:


- All linear dimensions are in millimeters. Dimensions in parenthesis are for reference only. Dimensioning and tolerancing per ASME Y14.5M.
- This drawing is subject to change without notice.
- This dimension does not include mold flash, protrusions, or gate burrs. Mold flash, protrusions, or gate burrs shall not exceed 0.15 mm, per side.
- This dimension does not include interlead flash. Interlead flash shall not exceed 0.25 mm, per side.
- Reference JEDEC registration MS-013.

# EXAMPLE BOARD LAYOUT


DW0016A

SOIC - 2.65 mm max height

SOIC



LAND PATTERN EXAMPLE  
SCALE:7X



4220721/A 07/2016

NOTES: (continued)

6. Publication IPC-7351 may have alternate designs.


7. Solder mask tolerances between and around signal pads can vary based on board fabrication site.

# EXAMPLE STENCIL DESIGN

DW0016A

SOIC - 2.65 mm max height

SOIC




SOLDER PASTE EXAMPLE  
BASED ON 0.125 mm THICK STENCIL  
SCALE:7X

4220721/A 07/2016

NOTES: (continued)

8. Laser cutting apertures with trapezoidal walls and rounded corners may offer better paste release. IPC-7525 may have alternate design recommendations.
9. Board assembly site may have different recommendations for stencil design.


D0008A



# PACKAGE OUTLINE

## SOIC - 1.75 mm max height

SMALL OUTLINE INTEGRATED CIRCUIT



4214825/C 02/2019

### NOTES:


- Linear dimensions are in inches [millimeters]. Dimensions in parenthesis are for reference only. Controlling dimensions are in inches. Dimensioning and tolerancing per ASME Y14.5M.
- This drawing is subject to change without notice.
- This dimension does not include mold flash, protrusions, or gate burrs. Mold flash, protrusions, or gate burrs shall not exceed .006 [0.15] per side.
- This dimension does not include interlead flash.
- Reference JEDEC registration MS-012, variation AA.

# EXAMPLE BOARD LAYOUT


D0008A

SOIC - 1.75 mm max height

SMALL OUTLINE INTEGRATED CIRCUIT



LAND PATTERN EXAMPLE  
EXPOSED METAL SHOWN  
SCALE:8X



SOLDER MASK DETAILS

4214825/C 02/2019

NOTES: (continued)

6. Publication IPC-7351 may have alternate designs.


7. Solder mask tolerances between and around signal pads can vary based on board fabrication site.

# EXAMPLE STENCIL DESIGN

D0008A

SOIC - 1.75 mm max height

SMALL OUTLINE INTEGRATED CIRCUIT



SOLDER PASTE EXAMPLE  
BASED ON .005 INCH [0.125 MM] THICK STENCIL  
SCALE:8X

4214825/C 02/2019

NOTES: (continued)

8. Laser cutting apertures with trapezoidal walls and rounded corners may offer better paste release. IPC-7525 may have alternate design recommendations.
9. Board assembly site may have different recommendations for stencil design.

## **IMPORTANT NOTICE AND DISCLAIMER**

TI PROVIDES TECHNICAL AND RELIABILITY DATA (INCLUDING DATA SHEETS), DESIGN RESOURCES (INCLUDING REFERENCE DESIGNS), APPLICATION OR OTHER DESIGN ADVICE, WEB TOOLS, SAFETY INFORMATION, AND OTHER RESOURCES "AS IS" AND WITH ALL FAULTS, AND DISCLAIMS ALL WARRANTIES, EXPRESS AND IMPLIED, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR NON-INFRINGEMENT OF THIRD PARTY INTELLECTUAL PROPERTY RIGHTS.

These resources are intended for skilled developers designing with TI products. You are solely responsible for (1) selecting the appropriate TI products for your application, (2) designing, validating and testing your application, and (3) ensuring your application meets applicable standards, and any other safety, security, regulatory or other requirements.

These resources are subject to change without notice. TI grants you permission to use these resources only for development of an application that uses the TI products described in the resource. Other reproduction and display of these resources is prohibited. No license is granted to any other TI intellectual property right or to any third party intellectual property right. TI disclaims responsibility for, and you will fully indemnify TI and its representatives against, any claims, damages, costs, losses, and liabilities arising out of your use of these resources.

TI's products are provided subject to [TI's Terms of Sale](#) or other applicable terms available either on [ti.com](#) or provided in conjunction with such TI products. TI's provision of these resources does not expand or otherwise alter TI's applicable warranties or warranty disclaimers for TI products.

TI objects to and rejects any additional or different terms you may have proposed.

Mailing Address: Texas Instruments, Post Office Box 655303, Dallas, Texas 75265  
Copyright © 2022, Texas Instruments Incorporated