



Dimensions: [mm]




Product Marking:

Pin 1 Anode	•
Marking	817D (Series 817, Binning D)
Marking - Date Code	YWW

Recommended Land Pattern: [mm]



Schematic:



General Properties:

Type	Optocoupler Phototransistor
Input	DC
Package	DIP 4, S-Type
Plastic Housing Color	White

Certification:

RoHS Approval	Compliant [2011/65/EU&2015/863]
REACH Approval	Conform or declared [EC1907/2006]
Halogen Free	Conform [JEDEC JS709B]
Halogen Free	Conform [IEC 61249-2-21]
VDE Approval	40051484 [DIN EN 60747-5-5 (VDE0884-5); EN 60747-5-5:2011; A1:2015]
UL Approval	E513104 [UL 1577]
CQC Approval	CQC20001274582 [GB4943.1-2001; GB8898-2011]

General Information:

Operating Temperature	-55 up to +110 °C
Storage Conditions (for single parts)	-55 up to +125 °C
Storage Conditions (in original packaging)	< 40 °C ; < 75 % RH
Moisture Sensitivity Level (MSL)	1

RoHS COMPLIANT	REACH COMPLIANT	HALOGEN FREE	DKE	UL	cac	CHECKED SaVo	REVISION 001.003	DATE (YYYY-MM-DD) 2030-01-01	GENERAL TOLERANCE DIN ISO 2768-1m	PROJECTION METHOD
DESCRIPTION										
WL-OCPT Optocoupler Phototransistor									ORDER CODE	
140817142400									STATUS	
DIP 4									PAGE	
eIPal									1/14	

This electronic component has been designed and developed for usage in general electronic equipment only. This product is not authorized for use in equipment where a higher safety standard and reliability standard is especially required or where a failure of the product is reasonably expected to cause severe personal injury or death, unless the parties have executed an agreement specifically governing such use. Moreover Würth Elektronik eiSos GmbH & Co KG products are neither designed nor intended for use in areas such as military, aerospace, aviation, nuclear control, submarine, transportation (automotive control, train control, ship control), transportation signal, disaster prevention, medical, public information network etc.. Würth Elektronik eiSos GmbH & Co KG must be informed about the intent of such usage before the design-in stage. In addition, sufficient reliability evaluation checks for safety must be performed on every electronic component which is used in electrical circuits that require high safety and reliability functions or performance.



**WURTH
ELEKTRONIK**
MORE THAN
YOU EXPECT

Würth Elektronik eiSos GmbH & Co. KG
EMC & Inductive Solutions
Max-Eyth-Str. 1
74638 Waldenburg
Germany
Tel. +49 (0) 79 42 945 - 0
www.we-online.com
eiSos@we-online.com

Absolute Maximum Ratings Input Properties (Ambient Temperature 25 °C unless otherwise specified):

Properties		Test conditions	Value	Unit
Forward Current	I_F max.		60	mA
Peak Forward Current	I_F Peak	duty/ 100 @ 100 Hz	1	A
Reverse Voltage	V_{REV}		6	V
Input Power Dissipation	P_I		100	mW

Absolute Maximum Ratings Output Properties:

Properties		Value	Unit
Collector Emitter Voltage	V_{CE}	35	V
Emitter Collector Voltage	V_{EC}	7	V
Collector Current	$I_{CE,P}$	50	mA
Output Power Dissipation	P_O	150	mW

Absolute Maximum Ratings Common Properties:

Properties		Value	Unit
Power Dissipation ¹⁾	P_{Diss}	200	mW
Isolation Voltage	V_{ISO}	5000	V (RMS)

¹⁾ Total power dissipation of the whole component

Electrical & Optical Input Properties:

Properties		Test conditions	Value		Unit
			typ.	max.	
Forward Voltage	V_F	$I_F = 10 \text{ mA}$	1.24	1.4	V
Reverse Current	I_{REV}	$V_{REV} = 6 \text{ V}$		10	μA
Input Capacitance	C_{in}	$V = 0 \text{ V}$ $f = 1 \text{ kHz}$	10		pF

Electrical & Optical Output Properties:

Properties		Test conditions	Value		Unit
			min.	max.	
Collector-Emitter Dark Current	$I_{CEO,Dark}$	$V_{CE} = 20 \text{ V}$ $I_F = 0$		100	nA
Collector-Emitter Breakdown Voltage	$V_{(BR)CE}$	$I_C = 100 \mu\text{A}$ $I_F = 0$	35		V
Emitter-Collector Breakdown Voltage	$V_{(BR)EC}$	$I_E = 100 \mu\text{A}$ $I_F = 0$	7		V

Electrical & Optical Transfer Properties:


Properties		Test conditions	Value			Unit
			min.	typ.	max.	
Current Transfer Ratio	CTR	$I_F = 5 \text{ mA}$ $V_{CE} = 5 \text{ V}$	300		600	%
Collector-Emitter Saturation Voltage	V_{CEsat}	$I_F = 20 \text{ mA}$ $I_C = 1 \text{ mA}$		0.06	0.2	V
Rise Time	t_r	$V_{CE} = 2 \text{ V}$ $I_C = 2 \text{ mA}$ $R_L = 100 \Omega$		3	18	μs
Fall Time	t_f	$V_{CE} = 2 \text{ V}$ $I_C = 2 \text{ mA}$ $R_L = 100 \Omega$		4	18	μs
Cut-Off Frequency	f_c	$V_{CE} = 2 \text{ V}$ $I_C = 2 \text{ mA}$ $R_L = 100 \Omega$		80		kHz
Floating Capacitance	C_{IO}	$V = 0 \text{ V}$ $f = 1 \text{ MHz}$		0.4		pF
Isolation Resistance	R_{ISO}	DC = 500 V 40~60 % R.H.	1	100		TΩ




**WURTH
ELEKTRONIK**
MORE THAN
YOU EXPECT

Würth Elektronik eiSos GmbH & Co. KG EMC & Inductive Solutions Max-Eyth-Str. 1 74638 Waldenburg Germany Tel. +49 (0) 79 42 945 - 0 www.we-online.com eiSos@we-online.com	CHECKED SaVo	REVISION 001.003	DATE (YYYY-MM-DD) 2030-01-01	GENERAL TOLERANCE DIN ISO 2768-1m	PROJECTION METHOD -
WL-OCPT Optocoupler Phototransistor					ORDER CODE 140817142400
SIZE/TYP DIP 4		BUSINESS UNIT eiPal	STATUS Valid		
			PAGE 2/14		

Total Power Dissipation vs. Ambient Temperature:




Collector Dark Current vs. Ambient Temperature:



Note: measured with Bin B


RoHS COMPLIANT REACH COMPLIANT HALOGEN FREE DKE UL cqc	CHECKED SaVo REVISION 001.003 DATE (YYYY-MM-DD) 2030-01-01 GENERAL TOLERANCE DIN ISO 2768-1m	PROJECTION METHOD
DESCRIPTION WL-OCPT Optocoupler Phototransistor		ORDER CODE 140817142400
SIZE/TYPE DIP 4		BUSINESS UNIT eIPal
STATUS Valid	PAGE 3/14	

Absolute CTR vs. Ambient Temperature



Testcondition: $I_F=5mA$, $T_A=25^\circ C$, Bin B


Relative CTR vs. Ambient Temperature:



Testcondition: $I_F=5mA$, Normalized to $T_A=25^\circ C$, Bin B


						WL-OCPT Optocoupler Phototransistor				
WURTH ELEKTRONIK	MORE THAN YOU EXPECT				Würth Elektronik eiSos GmbH & Co. KG EMC & Inductive Solutions Max-Eyth-Str. 1 74638 Waldenburg Germany Tel. +49 (0) 79 42 945 - 0 www.we-online.com eiSos@we-online.com				ORDER CODE 140817142400	
checked SaVo	revision 001.003	date (yyyy-mm-dd) 2030-01-01	general tolerance DIN ISO 2768-1m	projection method					status Valid	page 4/14
size/type DIP 4	business unit eIPal									

Collector-Emitter Saturation Voltage vs. Ambient Temperature:



Note: Bin B


Forward Current vs. Forward Voltage:



Note: Bin B


WURTH ELEKTRONIK MORE THAN YOU EXPECT					Würth Elektronik eiSos GmbH & Co. KG EMC & Inductive Solutions Max-Eyth-Str. 1 74638 Waldenburg Germany Tel. +49 (0) 79 42 945 - 0 www.we-online.com eiSos@we-online.com				
WL-OCPT Optocoupler Phototransistor									
CHECKED SaVo			REVISION 001.003	DATE (YYYY-MM-DD) 2030-01-01	GENERAL TOLERANCE DIN ISO 2768-1m	PROJECTION METHOD			
DESCRIPTION WL-OCPT Optocoupler Phototransistor						ORDER CODE 140817142400			
SIZE/TYPE DIP 4			BUSINESS UNIT eIPal	STATUS Valid	PAGE 5/14				

Collector Current vs. Collector-Emitter Voltage:



Testcondition $T_A=25^\circ\text{C}$, Bin B

Collector Current vs. Collector-Emitter Voltage, saturated




Testcondition $T_A=25^\circ\text{C}$, Bin B

RoHS COMPLIANT	REACH COMPLIANT	HALOGEN FREE	DKE	UL	cac	DESCRIPTION	GENERAL TOLERANCE	PROJECTION METHOD				
						WL-OCPT Optocoupler Phototransistor	DIN ISO 2768-1m					
	WURTH ELEKTRONIK MORE THAN YOU EXPECT		Würth Elektronik eiSos GmbH & Co. KG EMC & Inductive Solutions Max-Eyth-Str. 1 74638 Waldenburg Germany Tel. +49 (0) 79 42 945 - 0 www.we-online.com eiSos@we-online.com		CHECKED SaVo		REVISION 001.003	DATE (YYYY-MM-DD) 2030-01-01				
DESCRIPTION						GENERAL TOLERANCE						
WL-OCPT Optocoupler Phototransistor						DIN ISO 2768-1m						
SIZE/TYP				BUSINESS UNIT		ORDER CODE	140817142400					
DIP 4				eIPal		STATUS	Valid					
						PAGE	6/14					


This electronic component has been designed and developed for usage in general electronic equipment only. This product is not authorized for use in equipment where a higher safety standard and reliability standard is especially required or where a failure of the product is reasonably expected to cause severe personal injury or death, unless the parties have executed an agreement specifically governing such use. Moreover Würth Elektronik eiSos GmbH & Co KG products are neither designed nor intended for use in areas such as military, aerospace, aviation, nuclear control, submarine, transportation (automotive control, train control, ship control), transportation signal, disaster prevention, medical, public information network etc.. Würth Elektronik eiSos GmbH & Co KG must be informed about the intent of such usage before the design-in stage. In addition, sufficient reliability evaluation checks for safety must be performed on every electronic component which is used in electrical circuits that require high safety and reliability functions or performance.

Absolute CTR vs. Forward Current (at $V_{CE}=5\text{ V}$)



Testcondition $T_A=25^\circ\text{C}$


Relative CTR vs. Forward Current (at $V_{CE}=5\text{ V}$)



Testcondition $T_A=25^\circ\text{C}$


 WURTH ELEKTRONIK MORE THAN YOU EXPECT									
DESCRIPTION		GENERAL TOLERANCE			PROJECTION METHOD				
WL-OCPT Optocoupler Phototransistor		DIN ISO 2768-1m			METHOD				
SIZE/TYP		GENERAL TOLERANCE			PROJECTION METHOD				
DIP 4		DIN ISO 2768-1m			METHOD				
SIZE/TYP		GENERAL TOLERANCE			PROJECTION METHOD				
DIP 4		DIN ISO 2768-1m			METHOD				
DIP 4		DIN ISO 2768-1m			METHOD				
DIP 4		DIN ISO 2768-1m			METHOD				
DIP 4		DIN ISO 2768-1m			METHOD				
DIP 4		DIN ISO 2768-1m			METHOD				
DIP 4		DIN ISO 2768-1m			METHOD				
DIP 4		DIN ISO 2768-1m			METHOD				
DIP 4		DIN ISO 2768-1m			METHOD				
DIP 4		DIN ISO 2768-1m			METHOD				
DIP 4		DIN ISO 2768-1m			METHOD				
DIP 4		DIN ISO 2768-1m			METHOD				
DIP 4		DIN ISO 2768-1m			METHOD				
DIP 4		DIN ISO 2768-1m			METHOD				
DIP 4		DIN ISO 2768-1m			METHOD				
DIP 4		DIN ISO 2768-1m			METHOD				
DIP 4		DIN ISO 2768-1m			METHOD				
DIP 4		DIN ISO 2768-1m			METHOD				
DIP 4		DIN ISO 2768-1m			METHOD				
DIP 4		DIN ISO 2768-1m			METHOD				
DIP 4		DIN ISO 2768-1m			METHOD				
DIP 4		DIN ISO 2768-1m			METHOD				
DIP 4		DIN ISO 2768-1m			METHOD				
DIP 4		DIN ISO 2768-1m			METHOD				
DIP 4		DIN ISO 2768-1m			METHOD				
DIP 4		DIN ISO 2768-1m			METHOD				
DIP 4		DIN ISO 2768-1m			METHOD				
DIP 4		DIN ISO 2768-1m			METHOD				
DIP 4		DIN ISO 2768-1m			METHOD				
DIP 4		DIN ISO 2768-1m			METHOD				
DIP 4		DIN ISO 2768-1m			METHOD				
DIP 4		DIN ISO 2768-1m			METHOD				
DIP 4		DIN ISO 2768-1m			METHOD				
DIP 4		DIN ISO 2768-1m			METHOD				
DIP 4		DIN ISO 2768-1m			METHOD				
DIP 4		DIN ISO 2768-1m			METHOD				
DIP 4		DIN ISO 2768-1m			METHOD				
DIP 4		DIN ISO 2768-1m			METHOD				
DIP 4		DIN ISO 2768-1m			METHOD				
DIP 4		DIN ISO 2768-1m			METHOD				
DIP 4		DIN ISO 2768-1m			METHOD				
DIP 4		DIN ISO 2768-1m			METHOD				
DIP 4		DIN ISO 2768-1m			METHOD				
DIP 4		DIN ISO 2768-1m			METHOD				
DIP 4		DIN ISO 2768-1m			METHOD				
DIP 4		DIN ISO 2768-1m			METHOD				
DIP 4		DIN ISO 2768-1m			METHOD				
DIP 4		DIN ISO 2768-1m			METHOD				
DIP 4		DIN ISO 2768-1m			METHOD				
DIP 4		DIN ISO 2768-1m			METHOD				
DIP 4		DIN ISO 2768-1m			METHOD				
DIP 4		DIN ISO 2768-1m			METHOD				
DIP 4		DIN ISO 2768-1m			METHOD				
DIP 4		DIN ISO 2768-1m			METHOD				
DIP 4		DIN ISO 2768-1m			METHOD				
DIP 4		DIN ISO 2768-1m			METHOD				
DIP 4		DIN ISO 2768-1m			METHOD				
DIP 4		DIN ISO 2768-1m			METHOD				
DIP 4		DIN ISO 2768-1m			METHOD				
DIP 4		DIN ISO 2768-1m			METHOD				
DIP 4		DIN ISO 2768-1m			METHOD				
DIP 4		DIN ISO 2768-1m			METHOD				
DIP 4		DIN ISO 2768-1m			METHOD				
DIP 4		DIN ISO 2768-1m			METHOD				
DIP 4		DIN ISO 2768-1m			METHOD				
DIP 4		DIN ISO 2768-1m			METHOD				
DIP 4		DIN ISO 2768-1m			METHOD				
DIP 4		DIN ISO 2768-1m			METHOD				
DIP 4		DIN ISO 2768-1m			METHOD				
DIP 4		DIN ISO 2768-1m			METHOD				

Absolute CTR vs. Forward Current (at $V_{CE}=0,4$ V)



Testcondition $T_A=25^\circ\text{C}$

Relative CTR vs. Forward Current (at $V_{CE}=0,4$ V)




Testcondition $T_A=25^\circ\text{C}$

RoHS COMPLIANT	REACH COMPLIANT	HALOGEN FREE	DKE	UL	cac	DESCRIPTION	GENERAL TOLERANCE	PROJECTION METHOD	
						WL-OCPT Optocoupler Phototransistor	DIN ISO 2768-1m		
	WÜRTH ELEKTRONIK MORE THAN YOU EXPECT		Würth Elektronik eiSos GmbH & Co. KG EMC & Inductive Solutions Max-Eyth-Str. 1 74638 Waldenburg Germany Tel. +49 (0) 79 42 945 - 0 www.we-online.com eiSos@we-online.com		CHECKED SaVo	REVISION 001.003	DATE (YYYY-MM-DD) 2030-01-01	SIZE/TYPE DIP 4	
		DESCRIPTION WL-OCPT Optocoupler Phototransistor		GENERAL TOLERANCE DIN ISO 2768-1m		GENERAL TOLERANCE DIN ISO 2768-1m	PROJECTION METHOD DIP 4	ORDER CODE 140817142400	
						BUSINESS UNIT eIPal	STATUS Valid	PAGE 8/14	


This electronic component has been designed and developed for usage in general electronic equipment only. This product is not authorized for use in equipment where a higher safety standard and reliability standard is especially required or where a failure of the product is reasonably expected to cause severe personal injury or death, unless the parties have executed an agreement specifically governing such use. Moreover Würth Elektronik eiSos GmbH & Co KG products are neither designed nor intended for use in areas such as military, aerospace, aviation, nuclear control, submarine, transportation (automotive control, train control, ship control), transportation signal, disaster prevention, medical, public information network etc.. Würth Elektronik eiSos GmbH & Co KG must be informed about the intent of such usage before the design-in stage. In addition, sufficient reliability evaluation checks for safety must be performed on every electronic component which is used in electrical circuits that require high safety and reliability functions or performance.

Switching time vs. Load Resistance:



Testcondition $I_C=2\text{mA}$, $V_{CE}=2\text{V}$, $T_A=25^\circ\text{C}$, Bin B

Frequency Response




Testcondition $I_C=2\text{mA}$, $V_{CE}=2\text{V}$, $T_A=25^\circ\text{C}$, Bin B

						Würth Elektronik eiSos GmbH & Co. KG EMC & Industrial Solutions Max-Eyth-Str. 1 74638 Waldenburg Germany Tel. +49 (0) 79 42 945 - 0 www.we-online.com eiSos@we-online.com				
WL-OCPT Optocoupler Phototransistor										ORDER CODE 140817142400
SIZE/TYPE DIP 4						BUSINESS UNIT eIPal	STATUS Valid	PAGE 9/14		


This electronic component has been designed and developed for usage in general electronic equipment only. This product is not authorized for use in equipment where a higher safety standard and reliability standard is especially required or where a failure of the product is reasonably expected to cause severe personal injury or death, unless the parties have executed an agreement specifically governing such use. Moreover Würth Elektronik eiSos GmbH & Co KG products are neither designed nor intended for use in areas such as military, aerospace, aviation, nuclear control, submarine, transportation (automotive control, train control, ship control), transportation signal, disaster prevention, medical, public information network etc.. Würth Elektronik eiSos GmbH & Co KG must be informed about the intent of such usage before the design-in stage. In addition, sufficient reliability evaluation checks for safety must be performed on every electronic component which is used in electrical circuits that require high safety and reliability functions or performance.

Packaging Specification - Tape: [mm]




Packaging is referred to the international standard IEC 60286-3:2019


	Tape Type	A0 (mm)	B0 (mm)	W (mm)	T (mm)	T1 (mm)	T2 (mm)	K0 (mm)	P0 (mm)	P1 (mm)	P2 (mm)	D0 (mm)	D1 (mm)	E1 (mm)	E2 (mm)	F (mm)	Material	Qty. (pcs.)
Tolerance		typ.	typ.	+0,3/-0,1	ref.	ref.	typ.	typ.	typ.	±0,1	±0,1	±0,1/-0,0	min.	±0,1	min.	±0,1		
Value	2a	5,00	10,75	16,00	0,40	0,10	5,20	4,80	4,00	8,00	2,00	1,50	1,50	1,75	14,25	7,50	Polystyrene	1500




Packaging Specification - Reel: [mm]



	A (mm)	B (mm)	C (mm)	D (mm)	N (mm)	W1 (mm)	W2 (mm)	W3 (mm)	W3 (mm)	Material
Tolerance	± 2,0	typ.	typ.	typ.	typ.	typ.	typ.	min.	max.	
Value	330,00	2,20	13,00	20,90	97,20	16,70	20,70	15,90	19,40	Polystyrene



Classification Reflow Profile for SMT components:



Classification Reflow Soldering Profile:


Profile Feature	Value
Preheat Temperature Min	$T_s \text{ min}$ 150 °C
Preheat Temperature Max	$T_s \text{ max}$ 200 °C
Preheat Time t_s from $T_s \text{ min}$ to $T_s \text{ max}$	t_s max. 60 - 120 seconds
Ramp-up Rate (T_L to T_p)	3 °C/ second max.
Liquidous Temperature	T_L 217 °C
Time t_L maintained above T_L	t_L max. 60 seconds
Peak package body temperature	T_p $T_p \leq T_c$, see Table below
Time within 5°C of actual peak temperature	t_p max. 10 seconds
Ramp-down Rate (T_p to T_L)	6 °C/ second max.
Time 25°C to peak temperature	max. 220 seconds

refer to IPC/ JEDEC J-STD-020E

Package Classification Reflow Temperature (T_c):

Properties	Volume mm ³ <350	Volume mm ³ 350-2000	Volume mm ³ >2000
PB-Free Assembly Package Thickness < 1.6 mm	260 °C	260 °C	260 °C
PB-Free Assembly Package Thickness 1.6 mm - 2.5 mm	260 °C	250 °C	245 °C
PB-Free Assembly Package Thickness > 2.5 mm	250 °C	245 °C	245 °C
Applied cycles	2 cycles max.		

refer to IPC/ JEDEC J-STD-020E

     	CHECKED SaVo REVISION 001.003 DATE (YYYY-MM-DD) 2030-01-01 GENERAL TOLERANCE DIN ISO 2768-1m PROJECTION METHOD 
DESCRIPTION WL-OCPT Optocoupler Phototransistor	
ORDER CODE 140817142400	
SIZE/TYPE DIP 4	BUSINESS UNIT eiPal
STATUS Valid	
PAGE 11/14	

Cautions and Warnings:

The following conditions apply to all goods within the product series of Optoelectronic Components of Würth Elektronik eisSos GmbH & Co. KG:

General:

- This optoelectronic component is designed and manufactured for use in general electronic equipment.
- Würth Elektronik must be asked for written approval (following the PPAP procedure) before incorporating the components into any equipment in fields such as military, aerospace, aviation, nuclear control, submarine, transportation (automotive control, train control, ship control), transportation signal, disaster prevention, medical, public information network, etc. where higher safety and reliability are especially required and/or if there is the possibility of direct damage or human injury.
- Optoelectronic components that will be used in safety-critical or high-reliability applications, should be pre-evaluated by the customer.
- The optoelectronic component is designed and manufactured to be used within the datasheet specified values. If the usage and operation conditions specified in the datasheet are not met, the wire insulation may be damaged or dissolved.
- Do not drop or impact the components, the component may be damaged
- Würth Elektronik products are qualified according to international standards, which are listed in each product reliability report. Würth Elektronik does not warrant any customer qualified product characteristics beyond Würth Elektroniks' specifications, for its validity and sustainability over time.
- The responsibility for the applicability of the customer specific products and use in a particular customer design is always within the authority of the customer. All technical specifications for standard products also apply to customer specific products.
- Unless Würth Elektroik has given its express consent, the customer is under no circumstances entitled to reverse engineer, disassemble or otherwise attempt to extract knowledge or design information from the optoelectronic component.

Product specific:

Soldering:

- The solder profile must comply with the technical product specifications. All other profiles will void the warranty.
- All other soldering methods are at the customers' own risk
- The soldering pad pattern shown above is a general recommendation for the easy assembly of optoelectronic components. If a high degree of precision is required for the selected application (i.e. high density assembly), the customer must ensure that the soldering pad pattern is optimized accordingly.

Cleaning and Washing:

- Washing agents used during the production to clean the customer application might damage or change the characteristics of the optoelectronic component body, marking or plating. Washing agents may have a negative effect on the long-term functionality of the product.

- Using a brush during the cleaning process may break the optoelectronic component body. Therefore, we do not recommend using a brush during the PCB cleaning process.

Potting:

- If the product is potted in the customer application, the potting material might shrink or expand during and after hardening. Shrinking could lead to an incomplete seal, allowing contaminants into the optoelectronic component body, pins or termination. Expansion could damage the components. We recommend a manual inspection after potting to avoid these effects.

Storage Conditions:

- A storage of Würth Elektronik products for longer than 12 months is not recommended. Within other effects, the terminals may suffer degradation, resulting in bad solderability. Therefore, all products shall be used within the period of 12 months based on the day of shipment.
- Do not expose the optoelectronic component to direct sunlight.
- The storage conditions in the original packaging are defined according to DIN EN 61760-2.
- For a moisture sensitive component, the storage condition in the original packaging is defined according to IPC/JEDEC-J-STD-033. It is also recommended to return the optoelectronic component to the original moisture proof bag and reseal the moisture proof bag again.
- The storage conditions stated in the original packaging apply to the storage time and not to the transportation time of the components.

Packaging:

- The packaging specifications apply only to purchase orders comprising whole packaging units. If the ordered quantity exceeds or is lower than the specified packaging unit, packaging in accordance with the packaging specifications cannot be ensured.

Handling:

- Violation of the technical product specifications such as exceeding the nominal rated current, will void the warranty.
- The product design may influence the automatic optical inspection.
- Certain optoelectronic component surfaces consist of soft material. Pressure on the top surface has to be handled carefully to prevent negative influence to the function and reliability of the optoelectronic components.
- ESD prevention methods need to be applied for manual handling and processing by machinery.
- Resistors for protection are obligatory.
- In addition to optoelectronic components testing, products incorporating these devices have to comply with the safety precautions given in IEC 60825-1, IEC 62471 and IEC 62778.

Technical specification:


- The typical and/or calculated values and graphics of technical parameters can only reflect statistical figures. The actual parameters of each single product, may differ from the typical and/or calculated values or the typical characteristic line.

 RoHS COMPLIANT	 REACH COMPLIANT	 HALOGEN FREE		 UL	
 WURTH ELEKTRONIK MORE THAN YOU EXPECT	<p>Würth Elektronik eisSos GmbH & Co. KG EMC & Inductive Solutions Max-Eyth-Str. 1 74638 Waldenburg Germany Tel. +49 (0) 79 42 945 - 0 www.we-online.com eisSos@we-online.com</p>				
WL-OCPT Optocoupler Phototransistor					ORDER CODE 140817142400
SIZE/TYP		BUSINESS UNIT		STATUS	PAGE
DIP 4		eIPal		Valid	12/14

- In the characteristics curves, all values given in dotted lines may show a higher deviation than the parameters mentioned above.
- On each reel, only one bin is sorted and taped. The bin is defined on the current transfer ratio.
- In order to ensure highest availability, the reel binning of standard deliveries can vary. A single bin cannot be ordered. Please contact us in advance, if you need a particular bin sorting before placing your order.
- These cautions and warnings comply with the state of the scientific and technical knowledge and are believed to be accurate and reliable. However, no responsibility is assumed for inaccuracies or incompleteness.

The customer has the sole responsibility to ensure that he uses the latest version of this datasheet, which is available on Würth Elektronik's homepage. Unless otherwise agreed in writing (i.e. customer specific specification), changes to the content of this datasheet may occur without notice, provided that the changes do not have a significant effect on the usability of the optoelectronic components.

DRAFT

     	<small>CHECKED SaVo</small> <small>REVISION 001.003</small> <small>DATE (YYYY-MM-DD) 2030-01-01</small> <small>GENERAL TOLERANCE DIN ISO 2768-1m</small> <small>PROJECTION METHOD</small> 
WL-OCPT Optocoupler Phototransistor	<small>ORDER CODE</small> 140817142400
<small>SIZE/TYPE</small> DIP 4	<small>BUSINESS UNIT</small> eIPal
<small>STATUS</small> Valid	<small>PAGE</small> 13/14

This electronic component has been designed and developed for usage in general electronic equipment only. This product is not authorized for use in equipment where a higher safety standard and reliability standard is especially required or where a failure of the product is reasonably expected to cause severe personal injury or death, unless the parties have executed an agreement specifically governing such use. Moreover Würth Elektronik eiSos GmbH & Co KG products are neither designed nor intended for use in areas such as military, aerospace, aviation, nuclear control, submarine, transportation (automotive control, train control, ship control), transportation signal, disaster prevention, medical, public information network etc.. Würth Elektronik eiSos GmbH & Co KG must be informed about the intent of such usage before the design-in stage. In addition, sufficient reliability evaluation checks for safety must be performed on every electronic component which is used in electrical circuits that require high safety and reliability functions or performance.

Important Notes

The following conditions apply to all goods within the product range of Würth Elektronik eiSos GmbH & Co. KG:

1. General Customer Responsibility

Some goods within the product range of Würth Elektronik eiSos GmbH & Co. KG contain statements regarding general suitability for certain application areas. These statements about suitability are based on our knowledge and experience of typical requirements concerning the areas, serve as general guidance and cannot be estimated as binding statements about the suitability for a customer application. The responsibility for the applicability and use in a particular customer design is always solely within the authority of the customer. Due to this fact it is up to the customer to evaluate, where appropriate to investigate and decide whether the device with the specific product characteristics described in the product specification is valid and suitable for the respective customer application or not.

2. Customer Responsibility related to Specific, in particular Safety-Relevant Applications

It has to be clearly pointed out that the possibility of a malfunction of electronic components or failure before the end of the usual lifetime cannot be completely eliminated in the current state of the art, even if the products are operated within the range of the specifications. In certain customer applications requiring a very high level of safety and especially in customer applications in which the malfunction or failure of an electronic component could endanger human life or health it must be ensured by most advanced technological aid of suitable design of the customer application that no injury or damage is caused to third parties in the event of malfunction or failure of an electronic component. Therefore, customer is cautioned to verify that data sheets are current before placing orders. The current data sheets can be downloaded at www.we-online.com.

3. Best Care and Attention

Any product-specific notes, cautions and warnings must be strictly observed. Any disregard will result in the loss of warranty.

4. Customer Support for Product Specifications

Some products within the product range may contain substances which are subject to restrictions in certain jurisdictions in order to serve specific technical requirements. Necessary information is available on request. In this case the field sales engineer or the internal sales person in charge should be contacted who will be happy to support in this matter.

5. Product R&D

Due to constant product improvement product specifications may change from time to time. As a standard reporting procedure of the Product Change Notification (PCN) according to the JEDEC-Standard inform about minor and major changes. In case of further queries regarding the PCN, the field sales engineer or the internal sales person in charge should be contacted. The basic responsibility of the customer as per Section 1 and 2 remains unaffected.

6. Product Life Cycle

Due to technical progress and economical evaluation we also reserve the right to discontinue production and delivery of products. As a standard reporting procedure of the Product Termination Notification (PTN) according to the JEDEC-Standard we will inform at an early stage about inevitable product discontinuance. According to this we cannot guarantee that all products within our product range will always be available. Therefore it needs to be verified with the field sales engineer or the internal sales person in charge about the current product availability expectancy before or when the product for application design-in disposal is considered. The approach named above does not apply in the case of individual agreements deviating from the foregoing for customer-specific products.

7. Property Rights

All the rights for contractual products produced by Würth Elektronik eiSos GmbH & Co. KG on the basis of ideas, development contracts as well as models or templates that are subject to copyright, patent or commercial protection supplied to the customer will remain with Würth Elektronik eiSos GmbH & Co. KG. Würth Elektronik eiSos GmbH & Co. KG does not warrant or represent that any license, either expressed or implied, is granted under any patent right, copyright, mask work right, or other intellectual property right relating to any combination, application, or process in which Würth Elektronik eiSos GmbH & Co. KG components or services are used.

8. General Terms and Conditions

Unless otherwise agreed in individual contracts, all orders are subject to the current version of the "General Terms and Conditions of Würth Elektronik eiSos Group", last version available at www.we-online.com.

 RoHS COMPLIANT	 REACH COMPLIANT	 HALOGEN FREE				CHECKED SaVo	REVISION 001.003	DATE (YYYY-MM-DD) 2030-01-01	GENERAL TOLERANCE DIN ISO 2768-1m	PROJECTION METHOD
DESCRIPTION WL-OCPT Optocoupler Phototransistor									ORDER CODE 140817142400	
SIZE/TYPE DIP 4			BUSINESS UNIT eIPal			STATUS Valid	PAGE 14/14			
Würth Elektronik eiSos GmbH & Co. KG EMC & Inductive Solutions Max-Eyth-Str. 1 74638 Waldenburg Germany Tel. +49 (0) 79 42 945 - 0 www.we-online.com eiSos@we-online.com										