



NOTE:  
 Rating: DC 12V 50mA  
 Operating Force: 200±100gf  
 Lifetime: 10,000 Cycles

PAPT NO	L
SS-3268S-L1	2.0
SS-3268S-L2	3.0
SS-3268S-L3	4.0
SS-3268S-L4	5.0

ITEM	PAPT NAME	TER,NO	QTY	MATERIAL	FINISHING	REMARK
5	Terminal	12	Brass (0.30t)	ag Plated		
4	Contact spring	1	Phosphor bronze	ag Plated		
3	Base	1	Lcp	Black		
2	Cover	1	Sus	Natural		
1	Keystake	1	Pa46	Black		

广东星坤科技股份有限公司

ΔX		日期
ΔX		日期
ΔX		日期
MARK		DESCRIPTION

文件工程章

REVISIONS	DATE	REVISED	APPROVED	UNSPECIFIED TOLERANCES
				ANGULAR ±5°
				L ≤ 4 ±0.2
				4 < L ≤ 16 ±0.3
				16 < L ≤ 63 ±0.4
				L > 63 ±0.5

www.helloxkb.com www.helloxkb.cn www.xk-dg.cn

DSND	SCALE: N/A	MODEL TYPE: SLIDE SWITCH
DWN	VIEW:	PART NO.: SS-3268S-X
CHKD	UNIT: mm/in	DWG NO.:
APPD	SIZE: A4	

WEIGHT	SHEET	REVISION
	1/1	A0

**XKLB INDUSTRIAL PRECISION CO., LIMITED**