

SCSI/Fibre Channel - 10-ft. SCSI Cable HD50M to HD50M Double Shielded

MODEL NUMBER: \$366-010



Highlights

- Premium double-shielded cable
- 25 twisted-pair conductors

System Requirements

 Any external SCSI II device or controller card requiring HD50 interface

Package Includes

 10-ft. SCSI cable HD50M to HD50M double shielded

Description

Multi-platform SCSI II external peripheral cable HD50M/M. This 10ft cable is designed to connect two SCSI II (fast SCSI) devices together. Manufactured using double shielded 25 twisted pair high impedance cable. Constructed with low-capacitance, impedance matched, 28 AWG, stranded, tinned copper cable with insulated in polypropylene. Tripp Lite warrants this product to be free from defects in materials and workmanship for life.

Features

- Backwards compatibility with previous SCSI generations
- Double shielded (foil and braid)
- 25 twisted pair conductors
- Low-capacitance impedance matched 28 AWG stranded tinned copper insulated in polypropylene
- All Tripp Lite SCSI products, regardless of the SCSI generation, meet the latest specifications of ANSI
- Tripp Lite offers a complete line of internal and external solutions for SCSI/RAID and fibre channel ranging from the very latest Ultra 320 to legacy SCSI-1 and every combination in between
- Tripp Lite warrants this product to be free from defects in materials and workmanship for life

Specifications

OVERVIEW		
UPC Code	037332014092	
PHYSICAL		
Color	Beige	
Cable Length (ft.)	10	
Cable Length (m)	3.05	



Shipping Dimensions (hwd / in.)	12.50 x 10.00 x 1.25	
Shipping Dimensions (hwd / cm)	31.75 x 25.40 x 3.18	
Shipping Weight (lbs.)	1.13	
Shipping Weight (kg)	0.51	
CONNECTIONS		
Side A - Connector 1	HD50 (MALE)	
Side B - Connector 1	HD50 (MALE)	
WARRANTY & SUPPORT		
Product Warranty Period (Worldwide)	Lifetime limited warranty	



© 2022 Eaton. All Rights Reserved. Eaton is a registered trademark. All other trademarks are the property of their respective owners.