# TRIPP-LITE

1000 Eaton Boulevard Cleveland, OH 44122 United States

In some applications, a signal booster (Model Number: B120-000) should be used with this cable to ensure a signal strong enough for your display. An alternate solution is to use a Tripp Lite DVI over Cat5 Extender (Model Number: B140-101X) in place of a 50 ft. DVI cable and signal booster. Note that Tripp Lite's DVI over Cat5 Extender products support DVI Single Link resolutions only.

## DVI Dual Link Cable, Digital TMDS Monitor Cable (DVI-D M/M), 50 ft. (15.24 m)

## MODEL NUMBER: P560-050



## Description

Tripp Lite's 50-ft. (15.24 m) DVI Dual Link TMDS cable delivers the high performance, high bandwidth needed for today's digital video displays. Gold plated contacts ensure excellent conductivity, while double shielding (foil and braid) provides maximum EMI/RFI protection. Use in conjunction with DVI video cards that are specified as Dual or Single Link. Both DVI connectors are molded, have integral strain relief for long life reliability, and ferrite collars to drain off extraneous electrical interference. In most applications, a signal booster (B120-000) will need to be used with this cable to ensure a signal strong enough for your display.

## Features

- For use with Dual or Single Link TMDS specified equipment
- Compatible with Flat Panel Displays, Digital CRT Displays and Projectors
- Provides bandwidth for resolutions up to 2560 x 1600
- High Speed Digital Transmission to 9.9Gbps
- Superior molded cables with foil/braid shielding for maximum EMI/RFI protection
- In most applications, a signal booster (B120-000) will need to be used with this cable to ensure a signal strong enough for your display

## **Specifications**

OVERVIEW	
UPC Code	037332131058
Product Type	Passive Cable

## Highlights

- For use with Dual or Single Link TMDS specified equipment
- Compatible with Flat Panel Displays, Digital CRT Displays and Projectors
- Provides bandwidth for resolutions up to 2560 x 1600
- High Speed Digital Transmission to 9.9Gbps
- Superior molded cables with foil/braid shielding for maximum EMI/RFI protection

### System Requirements

- DVI monitor
- CPU with DVI Dual Link capabilities

### **Package Includes**

 50-ft. (15.24 m) DVI Dual Link TMDS Cable (DVI-D M/M)

## TRIPP-LITE

Technology	DVI	
Cable Type	Passive	
PHYSICAL		
Color	Black	
Cable Jacket Color	Black	
Cable Length (ft.)	50	
Cable Length (m)	15.24	
Cable Length (in.)	600	
Shipping Dimensions (hwd / in.)	17.00 x 14.00 x 1.00	
Shipping Dimensions (hwd / cm)	43.18 x 35.56 x 2.54	
Shipping Weight (lbs.)	4.70	
Shipping Weight (kg)	2.13	
Unit Dimensions (hwd / in.)	0.000 × 0.000 × 0.000	
CONNECTIONS		
Side A - Connector 1	DVI-D DUAL LINK (MALE)	
Side B - Connector 1	DVI-D DUAL LINK (MALE)	
Latching or Gripping Connector	No	
FEATURES & SPECIFICATIONS		
IP68 Rated	No	
IP20 Rated	No	
STANDARDS & COMPLIANCE		
Product Compliance	RoHS	
WARRANTY & SUPPORT		
Product Warranty Period (Worldwide)	Lifetime limited warranty	



© 2023 Eaton. All Rights Reserved. Eaton is a registered trademark. All other trademarks are the property of their respective owners.