

产品概览

FAN54161: Battery Charger IC for 98% Efficient 6A Direct Charging with Regulation and Protection

欲看完整文档，请参阅数据表。

The FAN54161UCX is a low loss direct charger which charges the battery safely at 6 A and provides active protection, regulation and monitoring features.

Integrated Protection and Regulation features control a pair of MOSFETs to ensure that the FAN54161UCX output voltage and current stay within a safe programmed operating range. Configurable hardware based safety features turn off the MOSFET in the event of a fault and notify the system.

An integrated 10-bit Analog-to-Digital Converter (ADC) provides real-time monitoring of input, output voltage, currents and temperature so that the system host or microcontroller can effectively use this information to optimize adapter and charger configuration.

特性

- Integrated Back-to-Back Common Source N-channel MOSFETs with Combined RON = 11 mΩ
- Maximum Input Voltage Tolerance of +22 V
- Reverse Input Voltage Tolerance of -2 V
- External N-channel MOSFET Drive Capability with Tolerance up to +32 V
- Regulation Modes (Charge Current, Input Current, Output Voltage, Battery Cell Voltage)
- Hardware-based Safety Protections (Input Over-Voltage, Input Under-Voltage, Output Over-Voltage, Input Over-Current, Die Over-Temperature, Internal Switch Short)


应用

- Mobile Devices
- Tablets

器件电气规格

产品	Compliance	Status	Type	Number of Cells Charged	V _{CC} Min (V)	V _{CC} Max (V)	I _D Max (μA)	Package Type
FAN54161UCX	Pb-free Halide free	Active	Li-Ion/Polymer	1	3	22	5.5	WLCSP-42

应用框图



欲了解更多信息，请联系您当地的销售支援 www.onsemi.cn。

创建于：11/27/2017