

## 产品概览

### 1N5234B: Zener 6.2V 0.5W 5%

欲看完整文档，请参阅数据表。

General Data Applicable to all series in this group.  
500 Milliwatt  
Hermetically Sealed  
Glass Silicon Zener Diodes

### 特性

- Complete Voltage Range - 1.8 to 200 Volts
- DO-204AH Package - Smaller than Conventional DO-204AA Package
- Double Slug Type Construction
- Metallurgically Bonded Construction

Mechanical Characteristics:

- CASE: Double slug type, hermetically sealed glass
- MAXIMUM LEAD TEMPERATURE FOR SOLDERING PURPOSES: 230°C, 1/16", from case for 10 seconds
- FINISH: All external surfaces are corrosion resistant with readily solderable leads
- POLARITY: Cathode indicated by color band. When operated in zener mode, cathode will be positive with respect to anode
- MOUNTING POSITION: Any
- WAFER FAB LOCATION: Phoenix, Arizona

For more features, see the data sheet

### 器件电气规格

产品	Compliance	Status	V <sub>Z</sub> Typ (V)	P Max (W)	Package Type
1N5234B	Pb-free	Active	6.2	0.5	Axial Lead
	Halide free				
1N5234BTR	Pb-free Halide free	Active			Axial Lead

欲了解更多信息，请联系您当地的销售支援 [www.onsemi.cn](http://www.onsemi.cn)。

创建于：11/27/2017