

外壳尺寸	类型	WV DC	电容	公差	标称尺寸 T (mm)	Digi-Key 零件编号	剪切带价格			Digi-Key 零件编号	带卷		YAGEO 零件编号
							10	100	500		数量	价格	
0805	NPO	50	27pF	±5%	0.6	311-1104-1-ND	.57	3.38	9.75	311-1104-2-ND	4,000	9.36/M	CC0805JRNPO9BN270
	NPO	50	33pF	±5%	0.6	311-1105-1-ND	.58	3.43	9.90	311-1105-2-ND	4,000	9.51/M	CC0805JRNPO9BN330
	NPO	50	39pF	±5%	0.6	311-1106-1-ND	.59	3.48	10.05	311-1106-2-ND	4,000	9.65/M	CC0805JRNPO9BN390
	NPO	50	47pF	±5%	0.6	311-1107-1-ND	.60	3.53	10.18	311-1107-2-ND	4,000	9.78/M	CC0805JRNPO9BN470
	NPO	50	56pF	±5%	0.6	311-1108-1-ND	.62	3.68	10.61	311-1108-2-ND	4,000	10.19/M	CC0805JRNPO9BN560
	NPO	50	68pF	±5%	0.6	311-1109-1-ND	.63	3.73	10.76	311-1109-2-ND	4,000	10.34/M	CC0805JRNPO9BN680
	NPO	50	82pF	±5%	0.6	311-1110-1-ND	.64	3.78	10.89	311-1110-2-ND	4,000	10.46/M	CC0805JRNPO9BN820
	NPO	50	100pF	±5%	0.6	311-1111-1-ND	.64	3.78	10.89	311-1111-2-ND	4,000	10.46/M	CC0805JRNPO9BN101
	NPO	50	120pF	±5%	0.6	311-1112-1-ND	.70	4.13	11.91	311-1112-2-ND	4,000	11.43/M	CC0805JRNPO9BN121
	NPO	50	150pF	±5%	0.6	311-1113-1-ND	.70	4.13	11.91	311-1113-2-ND	4,000	11.43/M	CC0805JRNPO9BN151
	NPO	50	180pF	±5%	0.6	311-1114-1-ND	.70	4.13	11.91	311-1114-2-ND	4,000	11.43/M	CC0805JRNPO9BN181
	NPO	50	220pF	±5%	0.6	311-1115-1-ND	.76	4.48	12.92	311-1115-2-ND	4,000	12.41/M	CC0805JRNPO9BN221
	NPO	50	270pF	±5%	0.6	311-1116-1-ND	.91	5.37	15.49	311-1116-2-ND	4,000	12.39/M	CC0805JRNPO9BN271
	NPO	50	330pF	±5%	0.6	311-1117-1-ND	.77	4.58	13.20	311-1117-2-ND	4,000	12.68/M	CC0805JRNPO9BN331
	NPO	50	390pF	±5%	0.6	311-1118-1-ND	.84	4.97	14.34	311-1118-2-ND	4,000	13.77/M	CC0805JRNPO9BN391
	NPO	50	470pF	±5%	0.6	311-1119-1-ND	.93	5.47	15.79	311-1119-2-ND	4,000	15.16/M	CC0805JRNPO9BN471
	NPO	50	560pF	±5%	0.6	311-1120-1-ND	1.01	5.97	17.21	311-1120-2-ND	4,000	16.53/M	CC0805JRNPO9BN561
	NPO	50	680pF	±5%	0.6	311-1121-1-ND	1.11	6.57	18.94	311-1121-2-ND	4,000	18.18/M	CC0805JRNPO9BN681
	NPO	50	1000pF	±5%	0.6	311-1122-1-ND	1.40	8.29	23.91	311-1122-2-ND	4,000	22.95/M	CC0805JRNPO9BN102
	X7R	50	220pF	±10%	0.6	311-1123-1-ND	.46	2.74	7.89	311-1123-2-ND	4,000	7.58/M	CC0805KRX7R9BB221
	X7R	50	270pF	±10%	0.6	311-1191-1-ND	.58	3.43	9.88	311-1191-2-ND	4,000	9.49/M	CC0805KRX7R9BB271
	X7R	50	330pF	±10%	0.6	311-1192-1-ND	.58	3.43	9.88	311-1192-2-ND	4,000	9.49/M	CC0805KRX7R9BB331
	X7R	50	390pF	±10%	0.6	311-1193-1-ND	.58	3.43	9.88	311-1193-2-ND	4,000	9.49/M	CC0805KRX7R9BB391
	X7R	50	470pF	±10%	0.6	311-1124-1-ND	.48	2.81	8.10	311-1124-2-ND	4,000	7.78/M	CC0805KRX7R9BB471
	X7R	50	560pF	±10%	0.6	311-1125-1-ND	.48	2.81	8.10	311-1125-2-ND	4,000	7.78/M	CC0805KRX7R9BB561
	X7R	50	680pF	±10%	0.6	311-1126-1-ND	.48	2.81	8.10	311-1126-2-ND	4,000	7.78/M	CC0805KRX7R9BB681
	X7R	50	820pF	±10%	0.6	311-1194-1-ND	.58	3.43	9.88	311-1194-2-ND	4,000	9.49/M	CC0805KRX7R9BB821
	X7R	50	1000pF	±10%	0.6	311-1127-1-ND	.49	2.89	8.33	311-1127-2-ND	4,000	8.00/M	CC0805KRX7R9BB102
	X7R	50	1500pF	±10%	0.6	311-1128-1-ND	.49	2.89	8.33	311-1128-2-ND	4,000	8.00/M	CC0805KRX7R9BB152
	X7R	50	2200pF	±10%	0.6	311-1129-1-ND	.46	2.74	7.89	311-1129-2-ND	4,000	7.58/M	CC0805KRX7R9BB222
	X7R	50	2700pF	±10%	0.6	311-1130-1-ND	.46	2.74	7.89	311-1130-2-ND	4,000	7.58/M	CC0805KRX7R9BB272
	X7R	50	3300pF	±10%	0.6	311-1131-1-ND	.49	2.89	8.33	311-1131-2-ND	4,000	8.00/M	CC0805KRX7R9BB332
	X7R	50	3900pF	±10%	0.6	311-1132-1-ND	.49	2.89	8.33	311-1132-2-ND	4,000	8.00/M	CC0805KRX7R9BB392
	X7R	50	4700pF	±10%	0.6	311-1133-1-ND	.48	2.81	8.10	311-1133-2-ND	4,000	7.78/M	CC0805KRX7R9BB472
	X7R	50	5600pF	±10%	0.6	311-1134-1-ND	.48	2.81	8.10	311-1134-2-ND	4,000	7.78/M	CC0805KRX7R9BB562
	X7R	50	6800pF	±10%	0.6	311-1135-1-ND	.48	2.81	8.10	311-1135-2-ND	4,000	7.78/M	CC0805KRX7R9BB682
	X7R	50	10000pF	±10%	0.6	311-1136-1-ND	.48	2.81	8.10	311-1136-2-ND	4,000	7.78/M	CC0805KRX7R9BB103
	X7R	50	15000pF	±10%	0.6	311-1143-1-ND	.50	2.98	8.61	311-1143-2-ND	4,000	8.27/M	CC0805KRX7R9BB153
	X7R	50	18000pF	±10%	0.6	311-1137-1-ND	.50	2.98	8.61	311-1137-2-ND	4,000	8.27/M	CC0805KRX7R9BB183
	X7R	50	22000pF	±10%	0.6	311-1138-1-ND	.59	3.48	10.05	311-1138-2-ND	4,000	9.65/M	CC0805KRX7R9BB223
	X7R	50	27000pF	±10%	0.85	311-1139-1-ND	.63	3.73	10.76	311-1139-2-ND	4,000	10.34/M	CC0805KRX7R9BB273
	X7R	50	33000pF	±10%	0.85	311-1374-1-ND	.64	3.76	10.84	311-1374-2-ND	4,000	10.41/M	CC0805KRX7R9BB333
	X7R	50	.10μF	±10%	0.85	311-1140-1-ND	.46	2.72	7.86	311-1140-2-ND	4,000	7.55/M	CC0805KRX7R9BB104
	X7R	25	.10μF	±10%	0.85	311-1141-1-ND	.92	5.44	15.69	311-1141-2-ND	4,000	15.07/M	CC0805KRX7R9BB104
	X7R	25	.47μF	±10%	1.25	311-1364-1-ND	.91	5.40	15.56	311-1364-2-ND	3,000	14.94/M	CC0805KXX7R8BB474
	X7R	16	.10μF	±10%	0.85	311-1142-1-ND	.92	5.44	15.69	311-1142-2-ND	4,000	15.07/M	CC0805KRX7R7BB104
	X7R	16	1.0μF	±10%	1.25	311-1365-1-ND	.69	4.08	11.78	311-1365-2-ND	3,000	11.31/M	CC0805KXX7R7BB105
	X7R	10	2.2μF	±10%	1.25	311-1368-1-ND	1.87	11.02	31.80	311-1368-2-ND	3,000	30.53/M	CC0805KXX7R6BB225
	Y5V	50	.10μF	-20%+80%	0.6	311-1361-1-ND	.28	1.66	4.80	311-1361-2-ND	4,000	4.61/M	CC0805ZRY5V9BB104
	Y5V	25	1.0μF	-20%+80%	0.85	311-1358-1-ND	.39	2.29	6.62	311-1358-2-ND	4,000	6.36/M	CC0805ZRY5V8BB105
	Y5V	10	3.3μF	-20%+80%	1.25	311-1190-1-ND	1.40	8.25	23.79	311-1190-2-ND	3,000	22.85/M	CC0805ZKY5V6BB335
	Y5V	10	4.7μF	-20%+80%	0.85	311-1371-1-ND	.78	4.60	13.26	311-1371-2-ND	4,000	12.73/M	CC0805ZRY5V6BB475
	Y5V	10	10μF	-20%+80%	1.25	311-1355-1-ND	1.19	7.02	20.25	311-1355-2-ND	3,000	19.44/M	CC0805ZKY5V6BB106
1206	NPO	50	.5pF	±0.25pF	0.6	311-1145-1-ND	1.18	6.96	20.08	311-1145-2-ND	4,000	19.28/M	CC1206CRNPO9BNR50
	NPO	50	1pF	±0.25pF	0.6	311-1212-1-ND	1.25	7.37	21.26	311-1212-2-ND	4,000	20.42/M	CC1206CRNPO9BN1R0
	NPO	50	1.5pF	±0.25pF	0.6	311-1214-1-ND	1.40	8.29	23.93	311-1214-2-ND	4,000	22.97/M	CC1206CRNPO9BN1R5
	NPO	50	1.8pF	±0.25pF	0.6	311-1215-1-ND	1.40	8.29	23.93	311-1215-2-ND	4,000	22.97/M	CC1206CRNPO9BN1R8
	NPO	50	2.2pF	±0.25pF	0.6	311-1146-1-ND	1.14	6.76	19.50	311-1146-2-ND	4,000	18.72/M	CC1206CRNPO9BN2R2
	NPO	50	2.7pF	±0.25pF	0.6	311-1216-1-ND	1.40	8.29	23.93	311-1216-2-ND	4,000	22.97/M	CC1206CRNPO9BN2R7
	NPO	50	3.3pF	±0.25pF	0.6	311-1147-1-ND	1.14	6.71	19.37	311-1147-2-ND	4,000	18.60/M	CC1206CRNPO9BN3R3
	NPO	50	3.9pF	±0.25pF	0.6	311-1217-1-ND	1.40	8.29	23.93	311-1217-2-ND	4,000	22.97/M	CC1206CRNPO9BN3R9
	NPO	50	4.7pF	±0.25pF	0.6	311-1218-1-ND	1.41	8.34	24.06	311-1218-2-ND	4,000	23.10/M	CC1206CRNPO9BN4R7
	NPO	50	5.6pF	±0.25pF	0.6	311-1149-1-ND	1.24	7.31	21.09	311-1149-2-ND	4,000	20.25/M	CC1206CRNPO9BN5R6
	NPO	50	6.8pF	±0.5pF	0.6	311-1220-1-ND	1.40	8.29	23.93	311-1220-2-ND	4,000	22.97/M	CC1206DRNPO9BN6R8
	NPO	50	7.5pF	±0.5pF	0.6	311-1221-1-ND	2.48	14.63	42.19	—	—	—	CC1206DRNPO9BN7R9
	NPO	50	8.2pF	±0.5pF	0.6	311-1222-1-ND	1.40	8.29	23.93	311-1222-2-ND	4,000	22.97/M	CC1206DRNPO9BN8R2
	NPO	50	10pF	±5%	0.6	311-1150-1-ND	1.09	6.42	18.51	311-1150-2-ND	4,000	17.77/M	CC1206JRNPO9BN100
	NPO	50	12pF	±5%	0.6	311-1213-1-ND	1.34	7.90	22.78	311-1213-2-ND	4,000	21.87/M	CC1206JRNPO9BN120
	NPO	50	15pF	±5%	0.6	311-1151-1-ND	1.20	7.11	20.51	311-1151-2-ND	4,000	19.70/M	CC1206JRNPO9BN150
	NPO	50	18pF	±5%	0.6	311-1152-1-ND	1.20	7.11	20.51	311-1152-2-ND	4,000	19.70/M	CC1206JRNPO9BN180
	NPO	50	20pF	±5%	0.6	311-1153-1-ND	1.14	6.71	19.37	311-1153-2-ND	4,000	18.60/M	CC1206JRNPO9BN200
	NPO	50	22pF	±5%	0.6	311-1154-1-ND	1.20	7.11	20.51	311-1154-2-ND	4,000	19.70/M	CC1206JRNPO9BN220
	NPO	50	27pF	±5%	0.6	311-1155-1-ND	1.20	7.11	20.51	311-1155-2-ND	4,000	19.70/M	CC1206JRNPO9BN270
	NPO	50	33pF	±5%	0.6	311-1156-1-ND	1.20	7.11	20.51	311-1156-2-ND	4,000	19.70/M	CC1206JRNPO9BN330
	NPO	50	39pF	±5%	0.6	311-1157-1-ND	1.34	7.90	22.78	311-1157-2-ND	4,000	21.87/M	CC1206JRNPO9BN390
	NPO	50	47pF	±5%	0.6	311-1158-1-ND	1.18	6.96	20.08	311-1158-2-ND	4,000	16.07/M	CC1206JRNPO9BN470
	NPO	50	51pF	±5%	0.6	311-12							