Cooling Solutions

for the lighting industry.

ebmpapst

The engineer's choice







About ebm-papst North America







Headquarters - Farmington, CT

- 250,000 square feet
- 275 employees
- Contract manufacturing
- Acoustic testing chamber
- Complete air testing lab on site
- ISO 9001 and ISO 14001 certifications
- Distribution centers in Farmington, CT and Toronto, Canada

ebm-papst is an innovator and market leader in fans, blowers, and motors with core competencies in motor technology, aerodynamics, and electronics. With over 15,000 products, we provide solutions to a wide range of markets including Air-conditioning and Ventilation, Appliance, Commercial Refrigeration, Heating, Industrial, Lighting, IT / Telecom, Medical, Transportation and more.

Support when and where you need it

Knowledgeable field sales professionals are close by for face-to-face meetings. Dedicated inside sales associates fulfill all of your ordering needs. To assist you with order management, our Customer Relations department provides automated services such as shipment notifications, reorder notifications, and invoicing.

Design and manufacturing

Beginning with the initial product concept, our application engineers work in tandem with customers to select the best air moving solution to suit specific goals and requirements. Once the prototype has been established, it can then be tested in our state-of-the-art airflow testing chambers to optimize performance. Each chamber has been designed to meet AMCA 210 and ISO 5801 requirements. In addition to our airflow testing capabilities, ebm-papst can conduct comparative sound, temperature, and velocity tests. The electrical engineering team can design everything from simple fan controllers for monitoring fan speed to complex controllers and power supplies, filtering, and specific communication protocols.

Logistics and inventory management programs

Our facilities feature over 90,000 square feet of climate-controlled warehousing, and utilize bar coding for real-time inventory management. Supply chain management programs such as Kanban, demand/pull, safety stock, consignment, and local warehousing can be customized to your needs.

Cooling solutions for the lighting industry

Sustainability is the center of our GreenTech philosophy Market overview Lifetime Computational fluid dynamics Active cooling for LED modules & CoBs Bridgelux technical data Cree technical data Philips technical data Xicato technical data



Table of Contents

Sustainability is the center of our GreenTech philosophy

Eco-friendliness and sustainability have always been at the core of our thoughts and actions. For decades, we have worked according to the simple but strict creed of our co-founder Gerhard Sturm: "Each new product we develop has to be better than the last one in terms of economy and ecology." GreenTech is the ultimate expression of our corporate philosophy.

The symbol of our commitment

Our company philosophy encompasses much more than designing new and more efficient fans and blowers; we put it into practice daily - in our offices and factories around the world! GreenTech symbolizes our continuous commitment, achievements, and passion to provide customers with the highest quality products using modern development and production methods, responsible business practices and initiatives that benefit the user as well as the environment.

GreenTech is eco-friendly production

Our GreenTech philosophy drives our product development, upholding the most stringent energy efficiency and environmental standards. Our production processes incorporate GreenTech practices including intelligent use of industrial waste heat and groundwater cooling, photovoltaics and our own cooling and ventilation technology. Our most modern plant consumes 91% less energy than required. From their origin to their recyclable packaging, our products contribute to the protection of the environment.

GreenTech is pro-active development

Even in the design phase, the materials and processes we use maximize the greatest possible eco-friendliness, energy balance and - wherever possible - recyclability. We work to continually improve the material components and performance of our products, as well as enhancing the air flow, decreasing noise characteristics and significantly reducing energy consumption.

Our customers profit from this every day

The heart of GreenTech is our EC technology. At the core of our energysaving motors and fans, EC technology provides up to 90% efficiency, significantly extends service life and makes our products maintenancefree. These values pay off for the environment as well as offer costsavings for the user! All ebm-papst products feature the greatest possible connection of economy and ecology.





The LED market

With high visible light, low radiant energy, and no infrared or ultraviolet light, LEDs are the most efficient light source in the lighting market today. While as much as 80% more energy efficient than traditional incandescent lighting, LED components still create a considerable amount of heat. High temperatures can cut the lifespan of an LED light in half. Temperatures over the maximum rated junction can quickly weaken the lumen output and the color rendering index of LEDs.

By dissipating the heat emitted by the LED light source, the efficiency and length of life of the light source can increase exponentially. Thermal management is a key factor in lumen output. For high-lumen output applications, passive cooling is not enough. In order to reach the desired lumen values in a small form factor, active cooling is the perfect solution to effectively disperse the heat

Market overview

produced by LED components. Active cooling solutions are a new contender in LED thermal management systems. Dissipating heat directly from the core of the modules allows for less thermal resistance, making the entire assembly more efficient. Active cooling technology offers thermal capabilities that are superior to passive heat sinks and can raise performance while significantly reducing the size of the lighting fixture. With industry-leading Germanengineered compact fans and American-designed assemblies, ebm-papst can provide the perfect cooling solution for your LED application. One of the most significant advantages that ebm-papst fans have on the life of the LED light is the reliability of our products. With active cooling solutions far surpassing the 50,000+ hour promise the industry is accustomed to, an ebm-papst fan is now the LED light's most efficient cooling source.

Lifetime

Computational fluid dynamics (CFD)

		Series	Dimensions	Temperature range	Lifetime	Lifetime	
Туре			mm	°C	hours	years	
Axials		400, 400F, 412F	40 x 10 / 20	-20 +85°C1	120,000 / 90,000 / 115,000	13.7 / 10.3 /13.1	
		500F	50 x 15	-20+85°C1	120,000	13.7	
		600F, 620	60 x 15 / 25	-20+85°C1	120,000 / 305,000	13.7 / 34.8	
		8200J, 8400N, 8450	80 x 38 / 25	-20+70°C ²	237,500 / 305,000 / 305,000	27.1 / 34.8 / 34.8	
		3200J, 3400N	92 x 38 / 25	-20+70°C ²	265,000 / 305,000	30.3 / 34.8	
		4100N, 4300, 4400F, 4400FGLLA	119 x 38 / 32 / 25	-20+75°C ³	305,000 / 322,500 / 285,000	34.8 / 36.8 / 32.5	
Radials	ø	RLF35	51 x 15	-20+70°C ³	227,500	26	
	0	RL48	76 x 27	-20+70°C ²	265,000	30.3	
	0	RL65	97 x 93.5 x 33	-20+70°C ²	227,500	26	
		Note: 1-4 to 185°F; 2-4 to 158°F; 3-4°F to 167°F. Lifetime L10 per IPC 9591 at 20°C ambient. Values are dependent on speed and application.					

Computational Fluid Dynamics (CFD)

- Flow simulations using Mentor Graphics FloEFD software
- Design service offered to customers
- Ability to optimize active cooling solutions in conjuction with lamp design
- Predictive analysis of thermal performance and LED junction temperature
- Validation of results using ebm-papst thermal resources
- Accelerates design process for custom applications







Active cooling for LED modules & CoBs

High lumen CoBs technical data

Enabling technology for the LED Market

"Today's high-performance LEDs, particularly the type known as "Chipon-Board" (CoB), are the fastest-growing package style for lighting. CoBs are arrays of small die placed together under a single phosphor pour. There are many LED cooling technologies; yet, few have truly addressed the unique requirements of LED systems. ebm-papst, one of the most innovative manufacturers of precision fans and blowers, has introduced their Active Cooling solutions - small, specialized fan/ heat sinks engineered expressly for high-power LED applications.

ebm-papst's fan mechanism offers a particularly reliable service life in the hundreds of thousands of hours (> 300K with certain models). Designed to be nearly silent, each fan is enclosed in an acoustic isolation ring, bringing the net acoustic noise to less than 7 dB. A very impressive noise reduction when compared to background noise in a quiet office usually about 40 dB. When used with a CoB device, the cooling fan effectively lowers the heat temperature to 90°F/36°C. Typically, CoB devices should be kept at less than 120°C. Using the ebm-papst cooling devices provides far lower temperatures than required parameters. In addition to significant noise and heat reduction, ebm-papst offers an impressive 5 year warranty on fans - far exceeding the life-span of most CoBs. Regardless of manufacturer, we think the ebm-papst active cooling solution is an excellent approach - almost a "platform" - for all CoB lighting systems." (Cary Eskow, Global Director of the Solid State Lighting & Advanced LED Business Unit Avnet Electronics Marketing)

Benefits of using ebm-papst cooling solutions

- German-engineered compact fans and motors, USA-designed assembly
- Reference designs include Bridgelux, Cree, Philips, Xicato light engines and CoBs
- Lifetime: in excess of 87,500 hours at ambient temperatures up to 40°C
- Industry leading reliability: 5 year warranty available (application dependent)
- 100% end of line testing
- Low noise: Custom acoustic isolation ring
- Solutions operate as low as 7 dB(A)
- A quiet office has a background noise of about 40 dB(A)
- High efficiency motor design
- Thermal protection: thermal isolation ring



Con M

PG1W-12-60-XXXX

 \odot Nominal Data CoB / LED OEM Туре VDC dB(A) W years hours hours rpm W years Bridgelux Vero 29 High Lumen PG1W-012-119-12 12 150 1200 582 1.1 176,000 20.0 97,500 11 16 Bridgelux Vero 29 PG1W-012-060-09 12 130 137,500 15.7 80,000 9 19 3000 672 0.42 Bridgelux Vero 10/13/18 PG1W-012-060-13 12 7 60 1800 197 0.18 197,500 22.5 87,500 10 **CREE LMH2 High Lumen** PG1W-012-119-10 12 16 150 1200 582 1.1 176 000 20.0 97.500 11 Cree CXA 20/25 12 10 PG1W-012-060-07 7 50 1800 227 0.18 197,500 22.5 87,500 Cree CXA PG1W-012-060-08 12 50 1800 627 0.18 197,500 22.5 87,500 10 7 Cree LMH2 PG1W-012-060-11 12 7 73 1800 191 0.18 197,500 22.5 87,500 10 Philips Fortimo SLM PG1W-012-060-06 12 7 50 1800 217 0.18 197,500 22.5 87,500 10 Xicato XSM, XIM, XTM PG1W-12-60-M3BN** 12 7 38 1800 147 0.18 10 197 500 22.5 87.500 12 Xicato XLM PG1W-12-60-L3BN** 7 53 1800 277 0 18 197 500 22.5 87 500 10

Note: Voltages are based on base fan models. Other voltages available upon request. Lifetime L₁₀ per IPC 9591. **Various mounting options available. Refer to data on pages 17-18 of this brochure. *Application dependant.







Bridgelux Vero 29 technical data

AIRFLOW

Bridgelux Vero 10/13/18 technical data









Dimensions shown in inches















High lumen CoBs technical data

PG1W-012-119-10

CREE LMH2









Dimensions shown in inches

PG1W-012-060-07







Cree 20/25 CXA technical data



Cree CXA technical data

PG1W-012-060-08





Dimensions shown in inches

PG1W-012-060-11







AIRFLOW



Cree LMH2 technical data



Philips SLM technical data

Xicato XSM, XIM, XTM technical data

709 -







Dimensions shown in inches

PG1W-12-60-M3BN









Xicato XLM technical data

PG1W-12-60-L3BN

ARLOT













ebm-papst Inc. North America

100 Hyde Road Farmington, CT 06034 Phone + 1 860-674-1515 Fax + 1 860-674-8536 sales@us.ebmpapst.com © ebm-papst Inc. 2016. ebm-papst Inc. reserves the right to change any specifications or data without notice.

ebmpapst

The engineer's choice