



# Selecting the Right Backshell for your Application!



#### Step #1

#### What Type of Material?

- Die Cast Nickel
- Die Cast Black
- Metalized Plastic
- Black Plastic
- Grey Plastic
- Plastic Assorted Colors
  - Available only on 972 Series





#### What Degree Cable Exit | Entry?

- 180° (Straight)
- 90°
- 60°
- 45°
- 40°
- 35°





#### What Type of Hardware?

#### **Standard:**

- #4-40 Mating Screws
- #4-40 Thumbscrews

#### Other (Sold Separate):

- M2.5
- M2.6
- M3
- Slide Locks
- Quick Lock Posts
- Grommets





#### What Type of Strain Relief?

- Mechanical
  - Requires a tool to assemble
- Compression
  - Does not Require any tools to assemble



#### NorComp Quick Reference Guide To Backshells

	Material					Cable Entry							Hardware		
	Die Cast	Die Cast	Metalized	Plastic								Stan	dard	Other Hardware	
Series	Nickel	Black	Plastic	(Std. Colors)								4-40 Mating	4-40 Thumb	Types	Strain
	(70 db)	Chromate	(60 db)		180°	90°	60°	45°	40°	35°	3-Way	Screws	Screws	Available	Relief Type
950			Χ	Black			X					X		M3	Mechanical
951			X	Black			X						X	M3	Mechanical
952	Х				Х								X	M2.5-M3-M2.6	Mechanical
953	Χ									Χ			Х	M2.5-M3-M2.6	Mechanical
954	Χ							X						Slide Lock	Compression
955	Χ		X	Black	Х			X						Quick Lock	Mechanical
956			Χ	Grey & Black	Χ							Х			Compression
957				Grey & Black								X			N/A
970	Χ	χ	Χ	Black	Χ								X	M2.5-M3-M2.6	
971	Х	χ	Χ	Black				Х					X	M2.5-M3-M2.6	
972				Multi-colors	Χ								X	M2.5-M3-M2.6	Mechanical
973			χ	Black	Χ						1		Χ		Mechanical
974			Χ	Black					Х				X		Mechanical
975			Χ	Black							Х	Х			Mechanical
976			Χ	Grey	Х							Х			Compression
977			X	Grey	Χ							Х			Mechanical
978			Χ	Grey	Χ							Х			Screw
979	Х		Χ	Grey	Χ							Х			Compression
981	Χ					X							Χ	Slide Lock	Compression
982			Χ	Grey	X	Χ						X			Mechanical
983			Χ	Grey & Black	Χ							Х			Mechanical
993			Χ	Grey				X					X		Mechanical
994	Х				Χ									Silde Lock	Mechanical
RJADK			X	Grey & Black									Х		N/A



#### NorComp Backshell Part Number Key:

	Put-up 1 = Kit
Series Positions Material RoHS Color	1 = Kit
950 9 010 = Plastic 01 = Black	
951 15 020 = Metalized Plastic 02 = White	2 = Bulk
952 25 030 = Nickel Die Cast 03 = Grey	
953 37 040 = Black Chromate Die Cast 04 = Green	
954 50 05 = Brown	
955 06 = Red	
956 07 = Blue	
957 08 = Yellow	
970 09 = Beige	
971 12 = Metal(ized)	
972	
973	
974	
975	
976	
977	

## NORCOMP

Passion for Excellence

950 - 957, RJADK Series BACKSHELLS







- Material: Metalized Plastic **Black Plastic**
- Cable Exit: 60°
- **Strain Relief Type:** Mechanical
- Available Positions: 9, 15, 25, 37
- **Supplied Hardware:** 
  - (2) #4-40 Mating Screws
  - Strain Relief Clamp w/ (2) Screws









- Ideal for Narrow Area Applications
- Easy Snap Together Design for Reducing Assembly Cost
- Hood is same Thickness as Standard D-Subs
- Includes #4-40 Mating Screws







- Material: Metalized Plastic

  Black Plastic
- Cable Exit: 60°
- Strain Relief Type: Mechanical
- Available Positions: 9, 15, 25, 37
- Supplied Hardware:
  - (2) #4-40 Thumbscrews
  - Strain Relief Clamp w/ (2) Screws





- Ideal for Narrow Area Applications
- Easy Snap Together Design for Reducing Assembly Cost
- Hood is same Thickness as Standard D-Subs
- Includes #4-40 Thumbscrews





- Material: Die Cast Nickel
- Cable Exit: 180° (Straight)
- Strain Relief Type: Mechanical & Compression
- Available Positions: 9, 15, 25, 37
- Supplied Hardware:
  - (2) #4-40 Thumbscrews
  - Strain Relief Clamps w/ (2) Screws
  - (2) Mounting Screws
  - 3 Sets of Metalized Plastic Inserts





- More Robust Design for Those Areas That Need It
- 360° Shielding with Mechanical Strain Relief
- Perimeter sealing dips for secure assembly





- Material: Die Cast Nickel
- Cable Exit: 35°
- Strain Relief Type: Mechanical & Compression
- **Available Positions:** 9, 15, 25, 37
- Supplied Hardware:
  - (2) #4-40 Thumbscrews
  - Strain Relief Clamps w/ (2) Screws
  - (2) Mounting Screws
  - 3 Sets of Metalized Plastic Inserts





- More Robust Design for Those Areas That Need It
- 360° Shielding with Mechanical Strain Relief
- Perimeter sealing dips for secure assembly
- Fully Tapped assembly holes for easy assembly






- Material: Die Cast Nickel
- Cable Exit: 45°
- Strain Relief Type: Compression
- Available Positions: 9, 15, 25, 37
- Supplied Hardware:
  - (2) Mounting Screws
  - 4 Sets of Black Plastic Inserts





- Die Cast for excellent shielding
- Easy Assembly reduces manufacturing costs
- Additional Hardware (Sold Separately)
  - Slide Locks & Posts





- Material: Die Cast
   Metalized Plastic
   Black Plastic
- Cable Exit: 45° / 180° (Straight)
- Strain Relief Type: Mechanical
- Available Positions: 9, 15, 25, 37
- Supplied Hardware:
  - (4) Mounting Screws
  - Strain Relief Clamp w/ (2) Screws
  - Cable Exit Block Plates





- Ideal for High Vibration Environments
  - Aviation, Testing Equipment, Etc...
- New Locking system allows for single hand removal / mating with secure latching
- Cable Exit Options:

Plastic/Metalized: (2-Way): 9, 15, 25 Positions

(3-Way): 37 Position

Die Cast: (2-Way): 9 Position

(3-Way): 15, 25, 37 Positions

- Additional Hardware:
  - Quick Lock Posts





- Material: Metalized Plastic
   Black Plastic
   Grey Plastic
- Cable Exit: 180° (Straight)
- Strain Relief Type: Compression
- Available Positions: 9, 15, 25
- Supplied Hardware:
  - (2) Jackscrews
  - Strain Relief (2-Parts)





- Snap Together Design Allows Low Cost Assembly
- Quick Assembly Strain Relief Allows Positive Retention
- Available in 3 Different Materials





- Material: Metalized Plastic
  Black Plastic
  Grey Plastic
- **Type:** Gender Changer
- Strain Relief Type: N/A
- Available Positions:
  - 9-to-9, 15-to-15, 25-to-25, 9-to-25
- Supplied Hardware:
  - (4) Jackscrews





- Snap Together Design Allows Low Cost Assembly
- Internal Cavity Designed for PCB's
- #4-40 Mating screws provide secure connection to your mating connector




#### RJADK SERIES



- Material: Metalized Plastic
  Black Plastic
  Grey Plastic
- **Type:** RJ45 to D-Sub Adapter
- Strain Relief Type: N/A
- Available Positions:
  - RJ-to-9, RJ-to-15, RJ-to-25
- Supplied Hardware:
  - Backshell w/ Thumbscrews
  - D-Sub Connector



#### RJADK SERIES



- Contacts Pre-Crimped onto
   Conductors (No Crimp tool Required)
- Snap Together Design Allows Low Cost Assembly
- #4-40 Thumbscrews Supplied Pre-Installed in Backshell
- Available in 3 Different Materials



#### 970 - 994 Series BACKSHELLS





- Material: Die Cast Nickel
   Die Cast Black
   Metalized Plastic
   Black Plastic
- Cable Exit: 180° (Straight)
- Strain Relief Type: Compression
- Available Positions: 9, 15, 25, 37
- Supplied Hardware:
  - (2) #4-40 Thumbscrews
  - (2) Mounting Screws
  - Strain Relief Spring
  - 2-Piece Grommet Set (Various I.D.)





- More robust design for those areas that need It
- Fully tapped holes for easy assembly (Die Cast Option)
- Perimeter sealing dips for secure assembly





Material: Die Cast - Nickel
Die Cast - Black
Metalized Plastic
Black Plastic

- Cable Exit: 45°
- Strain Relief Type: Compression
- Available Positions: 9, 15, 25, 37
- Supplied Hardware:
  - (2) #4-40 Thumbscrews
  - (2) Mounting Screws
  - Strain Relief Spring
  - 2-Piece Grommet Set (Various I.D.)





- More Robust Design for Those Areas That Need It
- Fully Tapped Holes for easy assembly (Die Cast Option)
- Perimeter sealing dips for secure assembly





- **Material:** Plastic (Various Colors)
- Cable Exit: 180° (Straight)
- Strain Relief Type: Mechanical
- Available Positions: 9, 15, 25, 37
- Supplied Hardware:
  - (2) #4-40 Thumbscrews
  - Strain Relief Clamp w/ Screws
  - Plastic Strain Relief





- Clam Shell Design aids assembly, reducing manufacturing cost
- Wide Range of Colors available for coding / brand identification
- Perimeter sealing dips for secure assembly
- Slim Line Design for critical space requirements





- Material: Metalized Plastic
   Black Plastic
- Cable Exit: 180° (Straight)
- Strain Relief Type: Mechanical
- **Available Positions:** 9, 15, 25, 37, 50
- Supplied Hardware:
  - (2) #4-40 Thumbscrews
  - (2) Mounting Screws
  - Strain Relief Clamp w/ Screws





- Perimeter sealing dips for secure assembly
- Metalized Plastic Provides up to a 60dB shield effectiveness rating
- Easy assembly reduces manufacturing cost






- Material: Metalized Plastic
   Black Plastic
- Cable Exit: 40° (Straight)
- Strain Relief Type: Mechanical
- **Available Positions:** 9, 15, 25, 37, 50
- Supplied Hardware:
  - (2) #4-40 Thumbscrews
  - (2) Mounting Screws
  - Strain Relief Clamp w/ Screws






- 40° Cable exit and low profile design allow for use in racking, where space is a premium
- Perimeter sealing dips for secure assembly
- Metalized Plastic Provides up to a 60dB shield effectiveness rating








- Material: Metalized Plastic
   Black Plastic
- Cable Exit: 3-Way
- Strain Relief Type: Mechanical
- Available Positions: 9, 15, 25, 37
- Supplied Hardware:
  - (2) #4-40 Thumbscrews
  - (2) Mounting Screws
  - Strain Relief Clamp w/ Screws
  - Block Off Plate(s)

**Consult Factory for Availability** 





45° 45°,

- Multiple Cable Exits allow for unique customization
- #4-40 Thumbscrews are pre-installed for easy assembly
- Metalized Plastic Provides up to a 60dB shield effectiveness rating
- 9 Position backshell only has 180° cable exit option

**Consult Factory for Availability** 



### 975T SERIES



45° 45°,


- Material: Metalized Plastic
   Black Plastic
- Cable Exit: 3-Way
- Strain Relief Type: Mechanical
- Available Positions: 9, 15, 25, 37
- Supplied Hardware:
  - (2) #4-40 Thumbscrews
  - (2) Mounting Screws
  - Strain Relief Clamp w/ Screws
  - Block Off Plate(s)



#### 975T SERIES



- Multiple Cable Exits allow for unique customization
- #4-40 Thumbscrews are pre-installed for easy assembly
- Metalized Plastic Provides up to a 60dB shield effectiveness rating







- Material: Metalized Plastic Grey Plastic
- Cable Exit: 180° (Straight)
- Strain Relief Type: Compression
- Available Positions: 9, 15, 25, 37
- Supplied Hardware:
  - (2) #4-40 Mating screws
  - (2) Mounting Screws w/ Nuts





- Works with most industry standard IDC ribbon D-Sub connectors
- Metalized Plastic Provides up to a 60dB shield effectiveness rating
- Perimeter sealing dips for secure assembly
- Internal Strain Relief built into backshell (No additional Parts)





- Material: Metalized Plastic Grey Plastic
- Cable Exit: 180° (Straight)
- Strain Relief Type: Mechanical
- **Available Positions:** 9, 15, 25, 37, 50
- Supplied Hardware:
  - (2) #4-40 Mating screws
  - (2) Mounting Screws w/ Nuts
  - Strain Relief Clamps w/ screws
  - (2) Saddle Washers





- Internal Strain Relief eliminates the need for grommets
- Metalized Plastic Provides up to a 60dB shield effectiveness rating
- Perimeter sealing dips for secure assembly
- Easy assembly reduces manufacturing cost





- Material: Metalized Plastic Grey Plastic
- Cable Exit: 180° (Straight)
- Strain Relief Type: Screw
- **Available Positions:** 9, 15, 25, 37, 50
- Supplied Hardware:
  - (2) #4-40 Mating screws
  - (2) Mounting Screws w/ Nuts
  - Screw Type Strain Relief
  - (2) Saddle Washers





- Strain Relief Design ensures secure fit no matter what cable diameter is used
- Metalized Plastic Provides up to a 60dB shield effectiveness rating
- Perimeter sealing dips for secure assembly
- Easy assembly reduces manufacturing cost





- Material: Die Cast Nickel Metalized Plastic Grey Plastic
- Cable Exit: 180° (Straight)
- Strain Relief Type: Compression
- **Available Positions:** 9, 15, 25, 37, 50
- Supplied Hardware:
  - (2) #4-40 Mating screws
  - (2) Mounting Screws w/ Nuts
  - 4-piece Grommet Set
  - (2) Saddle Washers





- Strain Relief Design ensures secure fit no matter what cable diameter is used
- Die Cast Nickel Provides up to a 70dB shield effectiveness rating
- Perimeter sealing dips for secure assembly
- Easy assembly reduces manufacturing cost





- Material: Die Cast Nickel
- Cable Exit: 90°
- Strain Relief Type: Compression
- Available Positions: 9, 15, 25
- Supplied Hardware:
  - (2) #4-40 Thumbscrews (Option -130R)
  - (3) Mounting Screws
  - 4-piece Grommet Set





- Fully tapped holes for easy assembly
- Die Cast Nickel Provides up to a 70dB Shield effectiveness rating
- Perimeter sealing dips for secure assembly





- Material: Metalized Plastic Grey Plastic
- Cable Exit: 90° / 180° (Straight)
- Strain Relief Type: Mechanical
- **Available Positions:** 9, 15, 25, 37, 50
- Supplied Hardware:
  - (2) #4-40 Mating screws
  - (2) Mounting Screws
  - Strain Relief w/ screws
  - Block off Plate(s)





- Strain Relief Design ensures secure fit no matter what cable diameter is used
- Metalized Plastic Provides up to a 60dB Shield effectiveness rating
- Perimeter sealing dips for secure assembly
- Easy assembly reduces manufacturing cost





- Material: Metalized Plastic
   Grey Plastic
   Black Plastic
- Cable Exit: 180° (Straight)
- Strain Relief Type: Mechanical
- **Available Positions:** 9, 15, 25, 37, 50
- Supplied Hardware:
  - (2) #4-40 Mating screws
  - Strain Relief w/ screws
  - (2) Saddle Washers





- Cable clamp with self tapping screws provide positive strain relief
- Metalized Plastic Provides up to a 60dB Shield effectiveness rating
- Perimeter sealing dips for secure assembly
- Can be used as a gender changer, pin-out changer, or standard D-sub Backshell





- Material: Metalized Plastic Grey Plastic
- Cable Exit: 45°
- Strain Relief Type: Mechanical
- Available Positions: 9, 25
- Supplied Hardware:
  - (2) #4-40 Thumbscrews
  - (2) Mounting Screws w/ nuts
  - Strain Relief w/ screws





45°

- Strain Relief Design ensures secure fit no matter what cable diameter is used
- Metalized Plastic Provides up to a 60dB Shield effectiveness rating
- Perimeter sealing dips for secure assembly
- Easy assembly reduces manufacturing costs





- Material: Die Cast Nickel
- Cable Exit: 180° (Straight)
- Strain Relief Type: Mechanical
- Available Positions: 9, 15, 25
- Supplied Hardware:
  - (2) Mounting Screws w/ nuts
  - Strain Relief w/ screws





- Slide Lock & Grommets can be purchased separately for this backshell series
- Die Cast Nickel Provides up to a 70dB Shield effectiveness rating
- Perimeter sealing dips for secure assembly
- Easy assembly reduces manufacturing costs





Physical Address: 3300 International Airport Drive

Suite #200

Charlotte, NC 28208

• Telephone Numbers: 800-849-4450 (Toll Free)

(704) 424-5448 (Local) (704) 424-5648 (Fax)

• E-Mail Addresses: <u>sales@norcomp.net</u>

info@norcomp.net eng@norcomp.net