



P. C. B. LAYOUT

SPECIFICATIONS:

Current Rating: LAMP

Insulator Resistance: 1000Megohms min

Voltage Rating: AC 300V

Operating Temperature: -40° ~+105°

Max Processing Temp: 260° for 3~5 seconds

Contact Material: Brass

Insulator Material: PA6T Black

Plating: Glod Flash Plated over Nickel

Contacts Per Row	Dimensions		Contacts Per Row		Dimensions	
	A	B	A	B	A	B
2*2P	0.00	0.00	2*26P	33.02	31.75	
2*2P	2.54	1.27	2*27P	34.29	33.02	
2*3P	3.81	2.54	2*28P	35.56	34.29	
2*4P	5.08	3.81	2*29P	36.83	35.56	
2*5P	6.35	5.08	2*30P	38.10	36.83	
2*6P	7.62	6.35	2*31P	39.37	38.10	
2*7P	8.89	7.62	2*32P	40.64	39.37	
2*8P	10.16	8.89	2*33P	41.91	40.64	
2*9P	11.43	10.16	2*34P	43.18	41.91	
2*10P	12.70	11.43	2*35P	44.45	43.18	
2*11P	13.97	12.70	2*36P	45.72	44.45	
2*12P	15.24	13.97	2*37P	46.99	45.72	
2*13P	16.51	15.24	2*38P	48.26	46.99	
2*14P	17.78	16.51	2*39P	49.53	48.26	
2*15P	19.05	17.78	2*40P	50.80	49.53	
2*16P	20.32	19.05	2*41P	52.07	50.80	
2*17P	21.59	20.32	2*42P	53.34	52.07	
2*18P	22.86	21.59	2*43P	54.61	53.34	
2*19P	24.13	22.86	2*44P	55.88	54.61	
2*20P	25.40	24.13	2*45P	57.15	55.88	
2*21P	26.67	25.40	2*46P	58.42	57.15	
2*22P	27.94	26.67	2*47P	59.69	58.42	
2*23P	29.21	27.94	2*48P	60.96	59.69	
2*24P	30.48	29.21	2*49P	62.23	60.96	
2*25P	31.75	30.48	2*50P	63.50	62.23	

toppt 深圳市鑫冠辉电子有限公司

一般公差 DIMENSIONS TOLERANCES	图号 DWG. NAME	料号 PART. NO.	品名 TITLE	排针1.27*1.0 2*50P 180度 L=6.3mm 6T	日期 DATE	2019-02-18	比例 SCALE	1:1
X. ±0.25	PH3-N250-SAB-G0						单位 UNIT	MM
XX ±0.20							版次 REV.	A.0
XXX ±0.15							页次 SHEET	01
X.XXX ±0.10							图幅 MANS	A4
ANGLE ±2°								

编号 DWG. NO.	标记 REV. LTR.	日期 DATE	变更内容 REVISION NOTES	签名 SIGN	版次 REV.
2					
3					
4					
5					
6					
7					