



P.C.B. LAYOUT

SPECIFICATIONS:

Current Rating: 2AMP
 Insulator Resistance: 1000Meg ohms min
 Withstand Voltage : AC 500V
 Operating Temperature: -40° ~+105°
 Max Processing Temp: 260° for 3~5 seconds
 Contact Material: Copper Alloy
 Insulator Material: PA6T Black
 Plating: G/F Plated Over Nickel

Contacts Per Row	A		B	
	28210in	4200	28210in	4000
2825in	4.00	2.00	28220in	44.00
2830in	6.00	4.00	28230in	46.00
2840in	8.00	6.00	28240in	48.00
2850in	10.00	8.00	28250in	50.00
2860in	12.00	10.00	28260in	52.00
2870in	14.00	12.00	28270in	54.00
2880in	16.00	14.00	28280in	56.00
2890in	18.00	16.00	28290in	58.00
2900in	20.00	18.00	28300in	60.00
2910in	22.00	20.00	28310in	62.00
2920in	24.00	22.00	28320in	64.00
2930in	26.00	24.00	28330in	66.00
2940in	28.00	26.00	28340in	68.00
2950in	30.00	28.00	28350in	70.00
2960in	32.00	30.00	28360in	72.00
2970in	34.00	32.00	28370in	74.00
2980in	36.00	34.00	28380in	76.00
2990in	38.00	36.00	28390in	78.00
28200in	40.00	38.00	28400in	80.00

topat 深圳市鑫冠辉电子有限公司

一般公差 COMMON TOLERANCES	图号 DWG. NAME	成品图	绘图 FLOT	LXW	比例 SCALE	1:1
X	±0.30	料号 PART NO.	PH2-F2XX-SAB-G0	审核 CHECKED	单位 UNIT	MM
X.X	±0.25	品名 TITLE	排针2.0 2*NP 180度 PC2.8 L=8.3	LYAN	版次 REV.	A.0
X.XXX	±0.20	THIRD ANGLE PROJECTION:		核 APPROVED	页次 SHEET	1/1
ANGLE	±0.15			日期 DATE	图幅 MANS	A4
				2019-02-18		

编号 DWG. NO.	XGH-DWG-A440	标记 REV. LTR.	日期 DATE	变更内容 REVISION NOTES	签名 SIGN