



P.C.B LAYOUT

编号 DWG NO.	XGH-DWG-A1708	标记 REV. LTR.	日期 DATE	变更内容 REVISION NOTES	签名 SIGN	版次 REV.
		Δ	15.12.30	增加电焊底层, 塑胶材质的更改为CP	LXW	A.2

- SPECIFICATIONS:
- Current Rating: 1AMP
 - Insulator Resistance: 1000Meg ohms min
 - Withstrand Voltage : AC 300V
 - Operating Temperature: -40° C~+105° C
 - Max Processing Temp: 260° C for 3~5 seconds
 - Contact Material: C5191
 - Insulator Material: LCP Black UL94V-0
 - Plating: G/F Plated over Nickel

Contacts Per Row	Dimensions			Contacts Per Row	Dimensions		
	A	B	C		A	B	C
0.00	0.00	0.00	0.00	2*26P	33.42	31.75	30.48
2*2P	2.94	1.27	0.00	2*27P	34.69	33.02	31.75
2*3P	4.21	2.54	1.27	2*28P	35.96	34.29	33.02
2*4P	5.48	3.81	2.54	2*29P	37.23	35.56	34.29
2*5P	6.75	5.08	3.81	2*30P	38.50	36.83	35.56
2*6P	8.02	6.35	5.08	2*31P	39.77	38.10	36.83
2*7P	9.29	7.62	6.35	2*32P	41.04	39.37	38.10
2*8P	10.56	8.89	7.62	2*33P	42.31	40.64	39.37
2*9P	11.83	10.16	8.89	2*34P	43.58	41.91	40.64
2*10P	13.10	11.43	10.16	2*35P	44.85	43.18	41.91
2*11P	14.37	12.70	11.43	2*36P	46.12	44.45	43.18
2*12P	15.64	13.97	12.70	2*37P	47.39	45.72	44.45
2*13P	16.91	15.24	13.97	2*38P	48.66	46.99	45.72
2*14P	18.18	16.51	15.24	2*39P	49.93	48.26	46.99
2*15P	19.45	17.78	16.51	2*40P	51.20	49.53	48.26
2*16P	20.72	19.05	17.78	2*41P	52.47	50.80	49.53
2*17P	21.99	20.32	19.05	2*42P	53.74	52.07	50.80
2*18P	23.26	21.59	20.32	2*43P	55.01	53.34	52.07
2*19P	24.53	22.86	21.59	2*44P	56.28	54.61	53.34
2*20P	25.80	24.13	22.86	2*45P	57.55	55.88	54.61
2*21P	27.07	25.40	24.13	2*46P	58.82	57.15	55.88
2*22P	28.34	26.67	25.40	2*47P	60.09	58.42	57.15
2*23P	29.61	27.94	26.67	2*48P	61.36	59.69	58.42
2*24P	30.88	29.21	27.94	2*49P	62.63	60.96	59.69
2*25P	32.15	30.48	29.21	2*50P	63.90	62.23	60.96

toppt 深圳市鑫冠辉电子有限公司

一般公差 COMMON TOLERANCES	图号 DRAWING NAME	成品图	绘图 FLOIT	LXW	比例 SCALE	1:1
±0.30	料号 PART NO.	PR3-C2XX-P-TLB-60-TU	审核 CHECKED	LYYAN	单位 UNIT	MM
±0.25	品名 TITLE	排母 1.27*4.3 2*NP SMT 带柱展开5.0 LCP	核准 APPROVED		版次 REV.	A.2
±0.20	THIRD ANGLE PROJECTION		日期 DATE	2019-02-18	页次 SHEET	01
±0.15	ANGLE		图幅 MMS			A4