



P.C.B. LAYOUT

SPECIFICATIONS:

Current Rating: 2AMP
 Insulator Resistance: 1000Meg ohms min
 Dielectric withstanding: AC 500V
 Operating Temperature: -40° C~+105° C
 Max Processing Temp: 260° for 3~5 seconds
 Contact Material: Alloy
 Insulator Material: PA6T
 Plating: G/F Plated Over Nickel

Contacts Per Row	Dimensions		Contacts Per Row	Dimensions	
	A	B		A	B
2*3P	13.30	4.00	2*19P	45.30	36.00
2*4P	15.30	6.00	2*20P	47.30	38.00
2*5P	17.30	8.00	2*21P	49.30	40.00
2*6P	19.30	10.00	2*22P	51.30	42.00
2*7P	21.30	12.00	2*23P	53.30	44.00
2*8P	23.30	14.00	2*24P	55.30	46.00
2*9P	25.30	16.00	2*25P	57.30	48.00
2*10P	27.30	18.00	2*26P	59.30	50.00
2*11P	29.30	20.00	2*27P	61.30	52.00
2*12P	31.30	22.00	2*28P	63.30	54.00
2*13P	33.30	24.00	2*29P	65.30	56.00
2*14P	35.30	26.00	2*30P	67.30	58.00
2*15P	37.30	28.00	2*31P	69.30	60.00
2*16P	39.30	30.00	2*32P	71.30	62.00
2*17P	41.30	32.00	2*33P	73.30	64.00
2*18P	43.30	34.00	2*34P	75.30	66.00

toppt 深圳市鑫冠辉电子有限公司

一般公差 TOLERANCES	图号 DWG. NAME	成品图	绘图 FLOT	LXW	比例 SCALE	1:1
X	料号 PART NO.	BH2-1205-SAB-G0-TR	审核 CHECKED	LYYAN	单位 UNIT	MM
X.X	品名 TITLE	筒牛2.0 2*5P 180度 L=8.3mm PC2.8mm	核准 APPROVED		版次 REV.	A.1
X.XXX	角度 ANGLE	±0.15	日期 DATE	2019-02-20	页次 SHEET	01
			THIRD ANGLE PROJECTION:		图幅 SIZES	A4

编号 DWG. NO.	XGH-DWG-A1909	标记 REV. LTR.	日期 DATE	变更内容 REVISION NOTES	签名 SIGN
----------------	---------------	-----------------	------------	------------------------	------------