



P.C.B. LAYOUT

SPECIFICATIONS:

Current Rating: 3AMP
 Insulator Resistance: 1000Meg ohms min
 Withstand Voltage: AC 500V
 Operating Temperature: -40° C~+105° C
 Max Processing Temp: 220° C for 3~5 seconds
 Contact Material: Brass
 Insulator Material: PBT Black
 Plating: G/F Plated Over Nickel

Contact S	Dimensions		
	A	B	C
Per Row			
2*3P	15.24	12.94	5.08
2*4P	17.78	15.48	7.62
2*5P	20.32	18.02	10.16
2*6P	22.86	20.56	12.70
2*7P	25.40	23.10	15.24
2*8P	27.94	25.64	17.78
2*9P	30.48	28.18	20.32
2*10P	33.02	30.72	22.86
2*11P	35.56	33.26	25.40
2*12P	38.10	35.80	27.94
2*13P	40.64	38.34	30.48
2*14P	43.18	40.88	33.02
2*15P	45.72	43.42	35.56
2*16P	48.26	45.96	38.10
2*17P	50.80	48.50	40.64
2*18P	53.34	51.04	43.18
2*19P	55.88	53.58	45.72
2*20P	58.42	56.12	48.26
2*25P	71.12	68.82	60.96

topot 深圳市鑫冠辉电子有限公司

一般公差 TOLERANCES		图号 DRAWING		绘图 DRAWING		比例 SCALE	
X	±0.30	料号 PART NO	BH1-128-SBB-G1-TR	审核 CHECKED	LYYAN	单位 UNIT	MM
X.X	±0.25	品名 TITLE	筒牛2.54*2*8P 180度方型	核准 APPROVED		版次 REV.	A.0
X.XXX	±0.20	THIRD ANGLE PROJECTION:	L=11.5 PC=3.0	日期 DATE	2019-02-20	页次 SHEET	01
X.XXX	±0.15	ANGLE	±2°	图幅 SIZE	A4		

编号 DWG NO	标记 REV. LTR	日期 DATE	变更内容 REVISION NOTES	签名 SIGN
XGH-DWG-A2182				