



P.C.B LAYOUT

SPECIFICATIONS:

Current Rating: 1AMP
 Insulator Resistance: 1000Megaohms min
 Voltage Rating: AC 300V
 Operating Temperature: -40° ~ +105°
 Max Processing Temp: 260° for 3~5 seconds
 Contact Material: C5191
 Insulator Material: LCP UL94V-0 Black
 Plating: Gild Flash Plated over Nickel

Contacts Per Row	Dimensions		Contacts Per Row	Dimensions	
	A	B		A	B
2*20pin	2.94	1.27	2*20pin	33.42	31.75
2*3pin	4.21	2.54	2*27pin	34.69	33.02
2*4pin	5.48	3.81	2*28pin	35.96	34.29
2*5pin	6.75	5.08	2*29pin	37.23	35.56
2*6pin	8.02	6.35	2*30pin	38.50	36.83
2*7pin	9.29	7.62	2*31pin	39.77	38.10
2*8pin	10.56	8.89	2*32pin	41.04	39.37
2*9pin	11.83	10.16	2*33pin	42.31	40.64
2*10pin	13.10	11.43	2*34pin	43.58	41.91
2*11pin	14.37	12.70	2*35pin	44.85	43.18
2*12pin	15.64	13.97	2*36pin	46.12	44.45
2*13pin	16.91	15.24	2*37pin	47.39	45.72
2*14pin	18.18	16.51	2*38pin	48.66	46.99
2*15pin	19.45	17.78	2*39pin	49.93	48.26
2*16pin	20.72	19.05	2*40pin	51.20	49.53
2*17pin	21.99	20.32	2*41pin	52.47	50.80
2*18pin	23.26	21.59	2*42pin	53.74	52.07
2*19pin	24.53	22.86	2*43pin	55.01	53.34
2*20pin	25.80	24.13	2*44pin	56.28	54.61
2*21pin	27.07	25.40	2*45pin	57.55	55.88
2*22pin	28.34	26.67	2*46pin	58.82	57.15
2*23pin	29.61	27.94	2*47pin	60.09	58.42
2*24pin	30.88	29.21	2*48pin	61.36	59.69
2*25pin	32.15	30.48	2*49pin	62.63	60.96
			2*50pin	63.90	62.23

toppt 深圳市鑫冠辉电子有限公司

图号 DWG NAME	XGH-DWG-A3584		绘图 FLDT	LXW		比例 SCALE	1:1	
料号 PART NO	PF3-C2XX-TLB-60-TU		审核 CHECKED	LYAN		单位 UNIT	MM	
品名 TITLE	排母1.27X4.3 2XNP SMT 展开50		核准 APPROVED			版次 REV.	A.0	
一般公差 TOLERANCES	±0.30		日期 DATE	2019-02-21		页次 SHEET	01	
X.X	±0.25		图幅 MMS	A4				
X.XX	±0.20							
X.XXX	±0.15							
ANGLE	±2°							

编号 DWG NO	标记 REV. LTR	日期 DATE	变更内容 REVISION NOTES	签名 SIGN	版次 REV.