



FRONT EDGE OF CONNECTOR
PCB LAYOUT (T=1.60mm)

MAPX	MODIFICATION	DATE
------	--------------	------

NOTES:
1. HOUSING: SEE NOTES, UL94V-0.
TERMINAL: SEE NOTES.
SHELL: SEE NOTES.
SPECIFICATION:

1. ELECTRICAL CHARACTERISTIC:
CONTACT RESISTANCE: 30MΩ MAX
DIELECTRIC WITHSTANDING VOLTAGE: 500V AC FOR 1MIN
INSULATION RESISTANCE: 1000MΩ MIN

2. MECHANICAL CHARACTERISTIC:
INSERTION FORCE: 35N(3.57KGf) MAX
EXTRACTION FORCE: 10~35N(1.02~3.57KGf) MIN
DURABILITY: 1500 CYCLES EXTRACTION FORCE: 10~35N
5000 CYCLES MIN

3. ENVIRONMENTAL:
OPERATING TEMPERATURE: -55 °C+85 °C

4. Contact finish:
01: Selective Gold Flash
02: Selective Gold 3U"
03: Selective Gold 5U"
04: Selective Gold 15U"
05: Selective Gold 30U"

深圳市精拓金电子有限公司

PRODUCT CHART DWG		公差一览表	
TOLERANCE	UNLESS OTHERWISE	公差	OTHERWISE
X	±0.25	X	±5°
X	±0.20	X	±2°
XX	±0.15	XX	±1°
XXX	±0.10	XXX	±0.5°

单位	MM	制图	Z-Y-B	制图料号	JTY-USB-10.6-002
比例	1:1	审核		产品名称	USB A/F 封闭式30度 2/3短路反向成品
日期	2013.10.24	核准		PRODUCT NO.	
DATE		APRD		角注	版本
				VIEW	VER
					AD

1 2 3 4 7 8 9 10

Autodesk 教育版产品制作