



FH series

Part number	FH151M100I200A	
Capacitance	150	μF
Voltage	100	VDC
Surge Voltage	115	VDC
Capacitance Tolerance (@ +20°C)	±20	%
Ripple current (max, @100kHz,+105°C)	1000	mA
Dissipation factor(tanδ @120Hz, +20°C)	8	%
Leakage Current (max, @ +20°C)*	150	μA
Impedance (max.@100kHz, +20°C)	0.11	Ω
Size	13x20	mm
Operating temperature	-40 to 105	°C
Endurance	10000	h



L.C.: After 2 min. with rated working voltage applied.

Test conditions	Endurance	Shelf Life
Duration time	10000h @ 105°C	1000h @ 105°C
Applied voltage	Rated DC working voltage, I _R	None
After test requirements (+20°C):		
Capacitance change	≤ ±25% of initial measured value	
Dissipation factor change	≤ 200% of the initial specified value	
Leakage current	≤ the initial specified value	
comment	Pre-treatment for measurements shall be conducted after application of DC working voltage for 30 min.	



D	13
L	20
F	5
dφ	0.6

Series	Cap	Tol.	Voltage	Case D	Case L	Type	Lead Treatm.	Special
1_2	3_4_5	6	7_8_9	10	11_12_13	14	15_16	17_18_19_20
FH	151	M	100	I	200	A	A	
	=150μF	=±20%	=100V	=13mm	=20mm	A=standard	no request	
	...							

Specification and description for the component(s) are subject to change without notice. For packaging, handling, precautions and warning information, please visit our website: www.capxongroup.com