



Temperature	-20~70 C
Rated Load	DC 30V 0.3A
Contact Resistance	<math>< 0.03\Omega</math>
Insulation Resistance	>100M Ω
Withstand Voltage	AC500V(50Hz)/min
Actuating Force	2.2~30N
Life	5000次

XKB

SWITCH CONNECTOR

Model No.	PJ-3582-	PJ-3583-
Schematic		
color	B:Black W:White	

	MATERIAL	PLATING
terminal 1	copper alloy	silver
terminal 2	copper alloy	silver
terminal 3	copper alloy	silver
terminal 4	copper alloy	silver
plastic	PBT	

MARK	DESCRIPTION	DATE	REVISED	APPROVED	UNSPECIFIED TOLERANCES	DSND	DATE	SCALE: N/A	MODEL TYPE: 3.5 PHONE JACK
Δ X					ANGLAR $\pm 5^\circ$	DWN	DATE	VIEW:	PART NO.:
Δ X					$L \leq 4$ ± 0.2	CHKD	DATE	UNIT: mm	DWG NO.:
Δ X					$4 < L \leq 16$ ± 0.3	APPD	DATE	SIZE: A4	PJ-358X-X
					$16 < L \leq 63$ ± 0.4				WEIGHT
					$L > 63$ ± 0.5				1.0g
									SHEET
									1/1
									REVISION
									A0