



**SPECIFICATION**

Contact Rating	50mA, 12V DC
Contact Resistance	100mΩ max.
Insulation Resistance	100MΩ min. 500V
Dielectric Strength	250V AC/1 min
Travel	0.25 mm
Operating Temp.	-25°C ~ +70°C
Storage Temp.	-30°C ~ +80°C

PAPT NO	TS-1105G-X-X-A
Operating force	A: 100gf B: 160gf C: 26
Height	H: 2.5
color	B: black BL: blue
Line	A: Normal; open B: Normal

P.C.B MOUNTING HOLES

PACKING REEL TYPE 3,000/1 REEL (EA)

5	Terminal	2	Brass
4	Contact	1	F
3	Base	1	P/
2	Cover	1	S/
1	Keystake	1	S

Δ X						units: mm	DSND		DATE	SCALE: NA	MC
Δ X						tolerance: X.X ±0.2mm	DWN		DATE	VIEW: 3/4	PA
Δ X						X.XX ±0.1mm	CHKD		DATE	UNIT: mm	DW
MARK	DESCRIPTION	REVISIONS	DATE	REVISED	APPROVED	X.XXX ±0.05mm	APPD		DATE	SIZE: A4	W
						UNSPECIFIED TOLERANCES	XKB INDUSTRIAL PRECISION CO., LIMITED				
						www.xk-dg.cn www.helloxkb.com www.helloxkb.cn					