


RoHS

SPECIFICATIONS

Rated Current:1.5AMP  
 Contact Resistance:20mΩ Max  
 Withstand Voltage:400V AC/DC  
 Insulation Resistance:800MΩ Min  
 Operation Temperature:-40°c to +105°c

Contact Material:Brass  
 Contact Plating:Au Over Ni  
 Insulator Material:Polyester(UL94V-0)  
 Standard: PA6T  
 Max.Processing Temp: 230°C for 30-60 seconds  
 (260°C for 10 seconds)

Recommended P.C.B Layout(Top Side)  
 (PCB BOARD TOLERANCE±0.05)



料号 : T.JC.01.Y020900002

深圳市连盛精密连接器有限公司

				OPERATION		DRAW		SCALE		FIT		PART NO. BH-00164	
				X.X	±0.30			UNIT	mm				
				X.XX	±0.20	CHECK		SIZE	A4			TITLE: 2.0BOX 90P H=5.65 W=7.0 DIP PC2.8 L=8.2 AU0.8U PA6T 黑色 带外大小柱 改模后 两端壁厚加0.65mm	
A0	2018.09.27	两端壁厚加厚0.65MM		X.XXX	±0.10	APPROVE		SHEET	1/1				
REV	DATE	MODIFICATION DESCRIPTION		CHANGE	DIM	TOL			PROJ.				