

RoHS

SPECIFICATIONS

Rated Current:3.0AMP
 Contact Resistance:20mΩ Max
 Withstand Voltage:1000V AC/DC
 Insulation Resistance:1000MΩ Min
 Operation Temperature:-40°C to +105°C

Contact Material:Brass
 Contact Plating:Au(0.8u") Over Ni(30~50u")
 Insulator Material:Polyester(UL94V-0)
 Standard: PA6T
 Max.Processing Temp: 230°C for 30-60 seconds
 (260°C for 10 seconds)

Ordering Information


1225 22 06 C W XX S 222 X 01

Insulator Material Option
 A=BK-PBT
 B=BK-PA66
 C=BK-PA6T
 D=BK-PA46
 F=BK-LCP




Contact Plating
 G0:Gold Flash
 G2:5U" Gold
 G3:10U" Gold
 G4:15U" Gold
 G5:30U" Gold
 S0:Gold Flash/Tin
 SN:Tin

Pin Length
 222=22.2mm

Packing
 0=PE Bag
 A=Tray
 T=Tube



Recommended P.C.B Layout(Top Side)
 (PCB BOARD TOLERANCE±0.05)



				OPERATION		DRAW		SCALE		FIT		深圳市连盛精密连接器有限公司	
				X.X	±0.30			UNIT	mm				
				X.XX	±0.20	CHECK		SIZE	A4	PART NO.		PH-00275	
A0	2015.03.10	NEW DRAWING		X.XXX	±0.10			SHEET	1/1	TITLE:		2.54x2.54PH 2x6P 双壁 180° 带一边柱 第3,4P高出0.5MM,L=22.7/22.2MM	
REV	DATE	MODIFICATION DESCRIPTION		CHANGE		APPROVE		PROJ.	◆				