


RoHS

SPECIFICATIONS

Rated Current:3.0AMP
 Contact Resistance:20mΩ Max
 Withstand Voltage:1000V AC/DC
 Insulation Resistance:1000MΩ Min
 Operation Temperature:-40°C to +105°C

Contact Material:Brass
 Contact Plating:Au Over Ni
 Insulator Material:Polyester(UL94V-0)
 Standard: PA6T
 Max.Processing Temp: 230°C for 30-60 seconds
 (260°C for 10 seconds)

Recommended P.C.B Layout(Top Side)
 (PCB BOARD TOLERANCE±0.05)



Dimension antitheses list				
ITEM	PC	PA	PB	L
Standard				
Alternate	3.00	3.00	8.40	14.40

				OPERATION		DRAW		SCALE		FIT		深圳市连盛精密连接器有限公司 PART NO. PH-00903 TITLE: 2.54PH 2H=2X2.5 2X16P 180° 胶芯反向	
				X.X	±0.30			UNIT	mm				
				X.XX	±0.20	CHECK		SIZE	A4				
				X.XXX	±0.10			SHEET	1/1				
A0	2012.04.18	NEW DRAWING		Angle	±3°	APPROVE		PROJ.					
REV	DATE	MODIFICATION DESCRIPTION		CHANGE	DIM	TOL							
1		2	3	4	5	6	7	8	9				