



RECOMMENDED P.C.B. LAYOUT
TOLERANCE UNSPECIFIED ±0.05mm

备注:

1. 材质:

- 1.1 胶芯: LCP+30%G.F UL94V-0
- 1.2 端子: 磷铜, T=0.12mm; 镍底, 镀金XU"
- 1.3 外壳: 不锈钢, T=0.30mm; 镀半金镍"
- 1.4 接地片: 不锈钢, T=0.10mm;
- 1.5 卡片: 不锈钢, T=0.15mm;

2. 主要特性:

- 2.1 额定电流: 3A
- 2.2 接触阻抗: 30mΩ MAX
- 2.3 绝缘阻抗: 100MΩ MIN 250V DC
- 2.4 耐压测试: 250V AC
- 2.5 沾锡性: 温度250±5℃, 时间5±0.5s
- 2.6 整体插入力: 3.57kgf MAX

耐久前整体拔出力: 0.8kgf MIN

耐久后整体拔出力: 0.60kgf MIN(匹配021专用母座)

2.7 使用寿命: 10000次

2.8 工作温度: -30℃~+80℃

MANUFACTURE DWG		东莞市讯普电子科技有限公司 DongGuan XunPu Electronics Co., Ltd			
UNLESS OTHERWISE SPECIFIED TOLERANCES			TITLE:USB 3.1TYPE-C/F 双槽贴片带柱母座		
			PAR	TYPEC-324G-BCP24	
			DWN	YAO	2017.06.18
			CHKD	APVD	
DECIMALS:	ANGLES:				
.X:±0.30	X°.±1'				
.XX:±0.20					
.XXX:±0.10					
		CUSTOMER COPY	SIZE:A4	SHEET:1F1	
				REV:A	