
KEMET Part Number: M3253505E1C102JZMB

(C1206K102J2EML)



SMD MIL COG PRF32535, Ceramic, 1000 pF, 5%, 200 VDC, COG, SMD, Low ESR, MIL-PRF-32535, N/A, 1206



Dimensions		
Chip Size	1206	
L	3.2mm +0.3/-0.25mm	
	(0.126 in +0.012/-0.01 in)	
W	1.6mm +0.3/-0.25mm	
	(0.063 in +0.012/-0.01 in)	
Т	1.8mm MAX (0.071 in MAX)	
В	0.51mm +/-0.36mm	
	(0.02 in +/-0.014 in)	

Packaging Specifications		
Packaging:	Waffle	
Packaging Quantity:	126	

General Information		
Series:	SMD MIL COG PRF32535	
Style:	SMD Chip	
Description:	SMD, Low ESR, MIL-PRF-32535	
RoHS:	No	
Prop 65:	WARNING: Cancer and reproductive harm - www.p65warnings.ca.gov.	
SCIP Number:	d66873f5-e54d-410c-a0cf- ebf6fcf635b5	
Termination:	Solder Plated	
Failure Rate:	N/A	
Qualifications:	MIL-PRF-32535 M-Level	
AEC-Q200:	No	
Shelf Life:	78 Weeks	
MSL:	1	

Specifications		
Capacitance:	1000 pF	
Capacitance Tolerance:	5%	
Voltage DC:	200 VDC	
Dielectric Withstanding Voltage:	500 VDC	
Temperature Range:	-55/+125°C	
Temperature Coefficient:	COG	
Dissipation Factor:	0.15% 1 MHz 25C	
Aging Rate:	0% Loss/Decade Hour	
Insulation Resistance:	100 GOhms	

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

