



SPECIFICATIONS

- 1、Current Rating: 1A AC, DC
- 2、Voltage Rating: 125V AC, DC
- 3、Temperatuer Range: $-25^{\circ}\text{C} \sim +85^{\circ}\text{C}$
- 4、Contact Resistance: $20\text{m}\Omega$ Max
- 5、Insulation Resistance: $100\text{M}\Omega$ Min
- 6、Withstanding Voltang: 500V AC/minute
- 7、Material: Wafer Nylon46, UL94V-0
PIN Brass Tin-plated

编 号	尺寸 (mm)	
	A	B
HC-1.25-2A	1.25	4.25
HC-1.25-3A	2.50	5.50
HC-1.25-4A	3.75	6.75
HC-1.25-5A	5.00	8.00
HC-1.25-6A	6.25	9.25
HC-1.25-7A	7.50	10.50
HC-1.25-8A	8.75	11.75
HC-1.25-9A	10.00	13.00
HC-1.25-10A	11.25	14.25
HC-1.25-11A	12.50	15.50
HC-1.25-12A	13.75	16.75
HC-1.25-13A	15.00	18.00
HC-1.25-14A	16.25	19.25
HC-1.25-15A	17.50	20.50
HC-1.25-16A	18.75	21.75

PCB LAYOUT

联系电话 18058866958

制 图 DRAWN	变 更 内 容 DESCRIPTION	日 期 DATE	GENERL TOLERANCE		制 图 DRAWING	钱岳生		料 号 PART NO.	HC-1.25-NA		版 本 REV.	A				
			X.±0.25	X.'±2'		2013、07、01	张 名		品 名 TITLE	1.25开口直针		页 次 SHEET	1/1			
			.X±0.20	.X'±1'						2013、07、03			张 名	客 户 料 号 CUTL NO.	WAFER DIP TYPE	
			.XX±0.15	.XX'±0.5'											2013、07、05	深 圳 市 华 灿 天 禄 电 子 有 限 公 司
.XXX±0.10	.XXX'±0.5'	单 位 UNITS	MM	比 例 SCALE	1:1											