



# DATA SHEET

## SS0520~SS0540

### SURFACE MOUNT SCHOTTKY BARRIER

**VOLTAGE** 20 to 40 Volts **CURRENT** 0.50 Ampers

**SOD-123**

Unit: inch (mm)

#### FEATURES

- Low turn-on voltage
- Fast switching
- PN Junction Guard Ring for Transient and ESD Protection.
- Pb free product are available : 99% Sn above can meet Rohs environment substance directive request


#### MECHANICAL DATA

Case: SOD-123, Plastic

Terminals: Solderable per MIL-STD-202G, Method 208

Polarity: See Diagram Below

Approx. Weight: 0.008 gram




#### MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS


Ratings at 25°C ambient temperature unless otherwise specified.

For capacitive load, derate current by 20%.


Parameter	Symbol	SS0520	SS0530	SS0540	Units
Marking Code		B 2	B 3	B 4	
Maximum Recurrent Peak Reverse Voltage	$V_{RRM}$	20	30	40	V
Maximum RMS Voltage	$V_{RMS}$	14	21	28	V
Maximum DC Blocking Voltage	$V_{DC}$	20	30	40	V
Maximum Average Forward Current at $T_a=75^\circ\text{C}$	$I_{AV}$	0.5			A
Peak Forward Surge Current, 8.3ms single half sine-wave superimposed on rated load (JEDEC method)	$I_{FSM}$	5.5			A
Maximum Instantaneous Forward Voltage	$V_F$	0.3@ 0.1A 0.385@ 0.5A	0.375@ 0.1A 0.430@ 0.5A	0.51@ 0.5A 0.62@ 1.0A	V
Maximum Reverse Current	$I_R$	75@ $V_R=10V$	20@ $V_R=15V$	10@ $V_R=20V$	$\mu\text{A}$
Typical junction capacitance at $V_R=0V$ DC	$C_J$	170			pF
Maximum Thermal Resistance	$R_{\theta JL}$ $R_{\theta JA}$	150 206			$^\circ\text{C} / \text{W}$
Operating Junction and Storage Temperature Range	$T_J, T_{STG}$	-55 TO +125			$^\circ\text{C}$




**Fig.1 FORWARD CURRENT DERATING**



**Fig.2 TYPICAL FORWARD VOLTAGE**




**Fig.3 TYPICAL REVERSE CURRENT**



**Fig.4 TYPICAL JUNCTION CAPACITANCE**



## MOUNTING PAD LAYOUT



## ORDER INFORMATION

- Packing information
  - T/R - 10K per 13" plastic Reel
  - T/R - 3.0K per 7" plastic Reel

## LEGAL STATEMENT

### IMPORTANT NOTICE

This information is intended to unambiguously characterize the product in order to facilitate the customer's evaluation of the device in the application. The information will help the customer's technical experts determine that the device is compatible and interchangeable with similar devices made by other vendors. The information in this data sheet is believed to be reliable and accurate. The specifications and information herein are subject to change without notice. New products and improvements in products and product characterization are constantly in process. Therefore, the factory should be consulted for the most recent information and for any special characteristics not described or specified.

### Copyright Pan Jit International Inc. 2003

All rights reserved. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner.

The information presented in this document does not form part of any quotation or contract. The information presented is believed to be accurate and reliable, and may change without notice in advance. No liability will be accepted by the publisher for any consequence of use. Publication thereof does not convey nor imply any license under patent or other industrial or intellectual property rights.