

# MOSFET - Power, Single N-Channel

## 40 V, 1.1 mΩ, 240 A

### FDBL9406L-F085

#### Features

- Small Footprint (TOLL) for Compact Design
- Low  $R_{DS(on)}$  to Minimize Conduction Losses
- Low  $Q_G$  and Capacitance to Minimize Driver Losses
- AEC-Q101 Qualified and PPAP Capable
- These Devices are Pb-Free, Halogen Free/BFR Free and are RoHS Compliant

**MAXIMUM RATINGS** ( $T_J = 25^\circ\text{C}$  unless otherwise noted)

Parameter	Symbol	Value	Unit
Drain-to-Source Voltage	$V_{DSS}$	40	V
Gate-to-Source Voltage	$V_{GS}$	$\pm 20$	V
Continuous Drain Current $R_{\theta JC}$ (Notes 1, 3)	$I_D$	240	A
Power Dissipation $R_{\theta JA}$ (Note 1)	$P_D$	300	W
		150	
Continuous Drain Current $R_{\theta JA}$ (Notes 1, 2, 3)	$I_D$	43	A
		31	
Power Dissipation $R_{\theta JA}$ (Notes 1, 2)	$P_D$	3.5	W
		1.7	
Pulsed Drain Current	$I_{DM}$	2755	A
Operating Junction and Storage Temperature Range	$T_J, T_{stg}$	-55 to +175	°C
Source Current (Body Diode)	$I_S$	100	A
Single Pulse Drain-to-Source Avalanche Energy ( $I_{L(pk)} = 85$ A; $L = 60$ $\mu\text{H}$ )	$E_{AS}$	217	mJ
Lead Temperature for Soldering Purposes (1/8" from case for 10 s)	$T_L$	260	°C

Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.

#### THERMAL RESISTANCE MAXIMUM RATINGS

Parameter	Symbol	Value	Unit
Junction-to-Case – Steady State	$R_{\theta JC}$	0.5	°C/W
Junction-to-Ambient – Steady State (Note 2)	$R_{\theta JA}$	43	


1. The entire application environment impacts the thermal resistance values shown, they are not constants and are only valid for the particular conditions noted. Current is limited by bondwire configuration.
2. Surface-mounted on FR4 board using a 650 mm<sup>2</sup>, 2 oz. Cu pad.
3. Maximum current for pulses as long as 1 second is higher but is dependent on pulse duration and duty cycle.




**ON Semiconductor®**

[www.onsemi.com](http://www.onsemi.com)

$V_{(BR)DSS}$	$R_{DS(ON)}$ MAX	$I_D$ MAX
40 V	1.1 mΩ @ 10 V 1.78 mΩ @ 4.5 V	80 A




N-CHANNEL MOSFET



MO-299A  
CASE 100CU

#### MARKING DIAGRAM



&Z = Assembly Plant Code  
&3 = Numeric Date Code  
&K = Lot Code  
FDBL9406L = Specific Device Code

#### ORDERING INFORMATION

See detailed ordering and shipping information on page 7 of this data sheet.

# FDBL9406L-F085

## ELECTRICAL CHARACTERISTICS (T<sub>J</sub> = 25°C unless otherwise noted)

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
-----------	--------	-----------------	-----	-----	-----	------

### OFF CHARACTERISTICS

Drain-to-Source Breakdown Voltage	V <sub>(BR)DSS</sub>	V <sub>GS</sub> = 0 V, I <sub>D</sub> = 250 μA	40	—	—	V
Drain-to-Source Breakdown Voltage Temperature Coefficient	V <sub>(BR)DSS/T<sub>J</sub></sub>		—	19.3	—	mV/°C
Zero Gate Voltage Drain Current	I <sub>DSS</sub>	V <sub>GS</sub> = 0 V, V <sub>DS</sub> = 40 V, T <sub>J</sub> = 25°C	—	—	1	μA
		V <sub>GS</sub> = 0 V, V <sub>DS</sub> = 40 V, T <sub>J</sub> = 175°C	—	—	1	mA
Zero Gate Voltage Drain Current	I <sub>GS</sub>	V <sub>DS</sub> = 0 V, V <sub>GS</sub> = ±20 V	—	—	±100	nA

### ON CHARACTERISTICS (Note 4)

Gate Threshold Voltage	V <sub>GS(th)</sub>	V <sub>GS</sub> = V <sub>DS</sub> , I <sub>D</sub> = 250 μA	1	1.9	3	V
Threshold Temperature Coefficient	V <sub>GS(th)/T<sub>J</sub></sub>		—	-6.5	—	mV/°C
Drain-to-Source On Resistance	R <sub>DS(on)</sub>	V <sub>GS</sub> = 10 V, I <sub>D</sub> = 80 A	—	0.9	1.1	mΩ
		V <sub>GS</sub> = 4.5 V, I <sub>D</sub> = 40 A	—	1.25	1.78	

### CHARGES, CAPACITANCES & GATE RESISTANCE

Input Capacitance	C <sub>iss</sub>	V <sub>GS</sub> = 0 V, f = 1 MHz, V <sub>DS</sub> = 20 V	—	8600	—	pF
Output Capacitance	C <sub>oss</sub>		—	2380	—	pF
Reverse Transfer Capacitance	C <sub>rss</sub>		—	106	—	pF
Gate Resistance	R <sub>g</sub>	V <sub>GS</sub> = 0.5 V, f = 1 MHz	—	2	—	Ω
Total Gate Charge	Q <sub>G(TOT)</sub>	V <sub>GS</sub> = 4.5 V, V <sub>DS</sub> = 32 V, I <sub>D</sub> = 80 A	—	58	—	nC
		V <sub>GS</sub> = 10 V, V <sub>DS</sub> = 32 V, I <sub>D</sub> = 80 A	—	121	—	
Threshold Gate Charge	Q <sub>g(th)</sub>	V <sub>GS</sub> = 0 to 1 V	—	7	—	
Gate-to-Source Gate Charge	Q <sub>gs</sub>	V <sub>DD</sub> = 32 V, I <sub>D</sub> = 80 A	—	26	—	
Gate-to-Drain "Miller" Charge	Q <sub>gd</sub>		—	19	—	
Plateau Voltage	V <sub>GP</sub>		—	3.2	—	V

### SWITCHING CHARACTERISTICS

Turn-On Delay Time	t <sub>d(on)</sub>	V <sub>DD</sub> = 20 V, I <sub>D</sub> = 80 A, V <sub>GS</sub> = 10 V, R <sub>GEN</sub> = 6 Ω	—	22	—	ns
Turn-On Rise Time	t <sub>r</sub>		—	22	—	ns
Turn-Off Delay Time	t <sub>d(off)</sub>		—	134	—	ns
Turn-Off Fall Time	t <sub>f</sub>		—	44	—	ns

### DRAIN-SOURCE DIODE CHARACTERISTICS

Source-to-Drain Diode Voltage	V <sub>SD</sub>	I <sub>SD</sub> = 80 A, V <sub>GS</sub> = 0 V	—	0.81	1.25	V
		I <sub>SD</sub> = 40 A, V <sub>GS</sub> = 0 V	—	0.77	1.2	V
Reverse Recovery Time	T <sub>RR</sub>	V <sub>GS</sub> = 0 V, dI <sub>SD</sub> /dt = 100 A/μs I <sub>S</sub> = 80 A	—	77	—	ns
Charge Time	t <sub>a</sub>		—	38	—	
Discharge Time	t <sub>b</sub>		—	39	—	
Reverse Recovery Charge	Q <sub>RR</sub>		—	95	—	nC

Product parametric performance is indicated in the Electrical Characteristics for the listed test conditions, unless otherwise noted. Product performance may not be indicated by the Electrical Characteristics if operated under different conditions.

4. Pulse Test: pulse width ≤ 300 μs, duty cycle ≤ 2%.

5. Switching characteristics are independent of operating junction temperatures.

TYPICAL CHARACTERISTICS




Figure 1. Normalized Power Dissipation vs. Case Temperature




Figure 2. Maximum Continuous Drain Current vs. Case Temperature




Figure 3. Normalized Maximum Transient Thermal Impedance




Figure 4. Peak Current Capability






Figure 5. Forward Bias Safe Operating Area


## TYPICAL CHARACTERISTICS




**Figure 6. Unclamped Inductive Switching Capability**




**Figure 7. Transfer Characteristics**




**Figure 8. Forward Diode Characteristics**



**Figure 9. Saturation Characteristics**








**Figure 10. Normalized R<sub>DS(on)</sub> vs. Drain Current**



**Figure 11. R<sub>DS(on)</sub> vs. Gate Voltage**

**TYPICAL CHARACTERISTICS**



## FDBL9406L-F085

### PACKAGE MARKING AND ORDERING INFORMATION

Part Number	Top Marking	Package	Reel Size	Tape Width	Quantity
FDBL9406L-F085	FDBL9406L	H-PSOF8L (Pb-Free / Halogen Free)	13"	24 mm	2000 Units

†For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specifications Brochure, [BRD8011/D](#).

# MECHANICAL CASE OUTLINE


## PACKAGE DIMENSIONS

ON Semiconductor®




**H-PSOF8L 11.68x9.80**  
CASE 100CU  
ISSUE A

DATE 06 JAN 2020



**GENERIC  
MARKING DIAGRAM\***



A = Assembly Location  
 Y = Year  
 WW = Work Week  
 ZZ = Assembly Lot Code  
 XXXX = Specific Device Code

\*This information is generic. Please refer to  
 device data sheet for actual part marking.  
 Pb-Free indicator, "G" or microdot "■", may  
 or may not be present. Some products may  
 not follow the Generic Marking.

DOCUMENT NUMBER:	98AON13813G	Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped "CONTROLLED COPY" in red.
DESCRIPTION:	H-PSOF8L 11.68x9.80	PAGE 1 OF 1

ON Semiconductor and **ON** are trademarks of Semiconductor Components Industries, LLC dba ON Semiconductor or its subsidiaries in the United States and/or other countries. ON Semiconductor reserves the right to make changes without further notice to any products herein. ON Semiconductor makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does ON Semiconductor assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. ON Semiconductor does not convey any license under its patent rights nor the rights of others.

**onsemi, ONSEMI, and other names, marks, and brands** are registered and/or common law trademarks of Semiconductor Components Industries, LLC dba "**onsemi**" or its affiliates and/or subsidiaries in the United States and/or other countries. **onsemi** owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of **onsemi**'s product/patent coverage may be accessed at [www.onsemi.com/site/pdf/Patent-Marking.pdf](http://www.onsemi.com/site/pdf/Patent-Marking.pdf). **onsemi** reserves the right to make changes at any time to any products or information herein, without notice. The information herein is provided "as-is" and **onsemi** makes no warranty, representation or guarantee regarding the accuracy of the information, product features, availability, functionality, or suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using **onsemi** products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by **onsemi**. "Typical" parameters which may be provided in **onsemi** data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. **onsemi** does not convey any license under any of its intellectual property rights nor the rights of others. **onsemi** products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use **onsemi** products for any such unintended or unauthorized application, Buyer shall indemnify and hold **onsemi** and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that **onsemi** was negligent regarding the design or manufacture of the part. **onsemi** is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

## PUBLICATION ORDERING INFORMATION

### LITERATURE FULFILLMENT:

Email Requests to: [orderlit@onsemi.com](mailto:orderlit@onsemi.com)

**onsemi** Website: [www.onsemi.com](http://www.onsemi.com)

### TECHNICAL SUPPORT

#### North American Technical Support:

Voice Mail: 1 800-282-9855 Toll Free USA/Canada

Phone: 011 421 33 790 2910

#### Europe, Middle East and Africa Technical Support:

Phone: 00421 33 790 2910

For additional information, please contact your local Sales Representative