




**Features**

- Tolerances down to  $\pm 10$  PPM
- Stabilities down to  $\pm 5$  PPM
- Operating Temperature Range to  $-55^{\circ}\text{C} \sim +125^{\circ}$

STANDARD SPECIFICATIONS	
PARAMETERS	MAX (Unless otherwise noted)
Frequency Range	6.000 ~ 50.000 MHz
Frequency Tolerance @ 25°C	(See options below)
Frequency Stability, ref 25°C	(See options below)
Temperature Range	
Operating ( $T_{OPR}$ )	(See options below)
Storage ( $T_{STG}$ )	55°C ~ +125°C
Shunt Capacitance ( $C_0$ )	5 pF
Load Capacitance ( $C_L$ )	(See options below)
Drive Level	
6.000 ~ 50.000 MHz	0.5 mW
Aging per year (@ 25°C)	$\pm 3$ PPM
Maximum Soldering Temp / Time	260°C / 10 Seconds x 2
Moisture Sensitivity Level (MSL) per J-STD-033	Not Applicable
Termination Finish	Au over Ni
Seal Method	Seam
Lead (Pb) Free	Yes
RoHS Compliant	Yes


Frequency Range (MHz)	Operating Mode	Max ESR $\Omega$
6.000 ~ 9.999999	Fundamental	80
10.000 ~ 15.999999	Fundamental	50
16.000 ~ 31.999999	Fundamental	40
32.000 ~ 39.999999	Fundamental	30
40.000 ~ 50.000000	Fundamental	20

DIMENSIONS / MECHANICAL SPECIFICATIONS	
	
	
	<b>Recommended Solder Pad Layout</b>
	<b>Dimensions in mm</b>
	<b>Pin Connections</b>
	#4 - Lid/Gnd #3 - Crystal
	#1 - Crystal #2 - Lid/Gnd
<p>Note: Dimensional drawing is for reference to critical specifications defined by size measurements. Certain non-critical visual attributes, such as side castellations, etc. may vary. Cut corner/rounded pad not shown.</p> <p>Crystal has no polarity and cannot be placed incorrectly; pin numbers are for reference only.</p>	


AVAILABLE OPERATING TEMPERATURES AND STABILITIES*								
Operating Temperature	±5 PPM	±10 PPM	±15 PPM	±20 PPM	±25 PPM	±30 PPM	±50 PPM	±100 PPM
-0°C ~ +70°C	X	O	O	O	O	O	O	N/A
-10°C ~ +60°C	O	O	O	O	O	O	O	N/A
-10°C ~ +70°C	X	O	O	O	O	O	O	N/A
-20°C ~ +70°C	X	O	O	O	O	O	O	N/A
-30°C ~ +85°C	X	X	O	O	O	O	O	N/A
-40°C ~ +85°C	X	X	O	O	O	O	O	N/A
-40°C ~ +105°C	X	X	X	X	X	X	O	O
-40°C ~ +125°C	X	X	X	X	X	X	O	O
-55°C ~ +155°C	X	X	X	X	X	X	O	O

Key: O = Available, X = Not Available, N/A = Not Applicable

TAPE SPECIFICATIONS (mm)						
A	B	C	D	E	F	REEL QTY
Ø1.55	4.0	8.0	7.5	16.0	1.7	-T1 = 1,000 -T2 = 2,000



REEL SPECIFICATIONS (mm)						
G	H	I	J	K	L	M
2.0	Ø13	Ø21	Ø80	Ø250	17.5	2.0



Available Options & Part Identification for Crystal Model C7BS<sup>1</sup>Sample PN: FC7BSBBMD25.0-T1

F	C7BS	B	B	M	D	25.0	-T1
<u>Fox</u>	<u>Model Number</u>	<u>Tolerance</u> B = <b>±50 PPM</b> C = <b>±30 PPM</b> D = <b>±25 PPM</b> E = <b>±20 PPM</b> F = <b>±15 PPM</b> H = <b>±10 PPM</b>	<u>Stability</u> <b>B = ±50 PPM</b> C = ±30 PPM D = ±25 PPM E = ±20 PPM F = ±15 PPM H = ±10 PPM L = ±5 PPM	<u>Load Capacitance<sup>2</sup></u> <b>M = 20pF</b> E = 10pF G = 12pF J = 15pF K = 16pF L = 18pF	<u>Operating Temperature</u> <b>D = -10 to +60°C</b> C = 0 to +70°C E = -10 to +70°C F = -20 to +70°C K = -30 to +85°C M = -40 to +85°C P = -40 to +105°C I = -40 to +125°C T = -55 to +125°C	<u>Frequency (MHz)</u>	<u>Values Added Options</u> Blank = Bulk T1 = 1,000 pcs T2 = 2,000 pcs

1 Not all frequency, tolerance, stability, load, and operating temperature combinations may be available.

2 Listed load capacitances represent the most commonly used. Other load capacitances are available. Contact us for assistance

## Reliability Test Conditions

Please contact Abracan Quality Assurance department