



PC Board Layout
Component Side Shown

NOTES:

MATERIAL :

- 1 HOUSING MATERIAL : GLASS FILLED POLYESTER UL94V-0
- 2 CONTACT MATERIAL : PHOSPHOR BRONZE φ0.46mm.
- 3 PLATING : GOLD PLATING OVER NICKEL.
- 4 SHIELD : 0.23mm THICKNESS COPPER ALLOY WITH NICKEL PLATED

ELECTRICAL:

- 1 VOLTAGE RATING : 125 VAC RMS.
- 2 CURRENT RATING : 1.5 AMP.
- 3 CONTACT RESISTANCE : 30 MILLIOHMS MAX.
- 4 INSULATION RESISTANCE : 500 MEGOHMS MIN @ 500V DC .
- 5 DIELECTRIC WITHSTANDING RESISTANCE : 1000V AC RMS 50Hz 1MIN.

MECHANICAL:

- 1 DURABILITY : 750 CYCLES MIN
- 2 PCB RETENTION PRE-SOLDER : 1 LB MIN.

ENVIRONMENTAL:

- 1 STORAGE : -40°~+85°
- 2 OPERATION : 0° C TO 70° C.

TOLERANCE TABLE

.0	±0.30
.00	±0.20
.000	±0.05

APPROVED:	DATE:	TITLE:
CHECKED:	DATE:	RJ45-8P/8C 弯插 带屏蔽 短体 (6JA-1X1-8P8C-S)
DRAWN:	DATE:	PART. NO. R-RJ45R08P-B000
Juli-Liu	2016-03-23	UNIT mm SCALE free
		FILE NO. Chantw-RJ45-0076 REV. A HY04

深圳市如科盟实业有限公司
CHANKLEMENT INDUSTRY CO., LTD