

ASS'	Y P/N		KEY STYLE	CONTACT QTY.		
W16982-5SG-P-5XX			A-KEY	5		
W16982-6SG-P-5XX			B-KEY	6		
W16982-7	7SG-P-5X	Х	A-KEY	7		
W16982- <u>X</u> SG-P-5 <u>XX</u>						
	-GROMMET SIZE					

-NUMBER OF CONTACTS

	MA	08-18-20	RELEASED PER PDR 18004-4						
	JGK	2/28/20	ADDED SHEET 2 FOR CABLE-END ASSEMBLY INSTRUCTIONS.						
	JGK	9/09/19	DRAWING CREATED FOR PDR #18004.						
	INIT.	DATE	DESCRIPTION						
INFORMATION ILLUSTRATED IS HE PROPERTY OF "CONXALL RPORATION." UNAUTHORIZED LICATION OR DISTRIBUTION OF IS DOCUMENT IS PROHIBITED.		OF "CONXALL UNAUTHORIZED DISTRIBUTION OF	ORIG. DRAWN BY: JGK CHECKED BY:	date: 9/09/19	Conxall				
ALL UNITS ARE IN FEET, CHES, FRACTION OF INCHES AND DECIMALS. NLESS OTHERWISE SPECIFIED TOLERANCES: 3 PLACE DECIMALS ±.005 ANGLES ±1°		ION OF INCHES CIMALS. WISE SPECIFIED ANCES: CIMALS ±.005 ES ±1°	APPROVED BY: SCALE SIZE SHEET NTS B 1 OF 1		601 E. WILDWOOD VILLA PARK, IL 60181 TITLE: CABLE-END ASSEMBLY (5-7) #26 SOCKET CONTACTS, SOLDER INSTA-CLICK™ MICRO-CON-X customer: STANDARD PRODUCT				
FRACTIONS ±1/16 = CRITICAL CHARACTERISTIC		CHARACTERISTIC	FILE: W16982-XSG-P-5X			EV A			