


RoHS


CAD GENERATED DRAWING. DON' T CHANGE BY HAND.

REV.	ECN. NO.	APPD.

T (terminal)	
A	Solder terminals
B	Straight PCB terminal
C	Others



Circuit Diagram



Printing :

— Date

— Month

— Year

e. g.: Oct

21, 2019— 191021

CHARACTERISTICS

Operating Force	150gf Max
Release Force	30gf Min
Free Position	7.90mm Max
Operation Position	7.10±0.25mm
Movement-Differential	0.30mm Max
Total Travel Position	5.30mm Max

ELECTRICAL DATA

CONTACT ARRANGEMENT	SWITCH SEALING
S. P. S. T-NO	IP67
Ratings	
12V DC	0.1A
5V DC	50 μ A

X.	± 0.50	X. °	$\pm 2^{\circ}$	UNITS mm
.X	± 0.30	.X °	$\pm 1^{\circ}$	
.XX	± 0.10	.XX °	$\pm 0.5^{\circ}$	MAT'L /
.XXX	± 0.05			
THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF YIYUAN TECHNOLOGY CO.,LTD AND SHALL NOT BE REPRODUCED, COPIED OR USED IN ANY MANNER WITHOUT THE PRIOR WRITTEN CONSENT OF YIYUAN TECHNOLOGY CO.,LTD				FINISH / Q' TY /

 YIYUAN		深圳市怡远科技有限公司 SHENZHEN YIYUAN TECHNOLOGY CO., LTD								
PART NO. YTD-309-11T		TITLE: DETECT SWITCH								
APPD: ROGER		DWG NO. : YTD-309-11T								
CHKD: ROC		 <table><tr><th>SCALE</th><th>SHEET</th><th>REV.</th></tr><tr><td>1/1</td><td>1/1</td><td>A</td></tr></table>			SCALE	SHEET	REV.	1/1	1/1	A
SCALE	SHEET				REV.					
1/1	1/1	A								
DR: BILLY WANG 2020/08/21										