

# Schottky Diode

$V_{RRM}$  = 200 V  
 $I_{FAV}$  = 2x 15 A  
 $V_F$  = 0.78 V


High Performance Schottky Diode

Low Loss and Soft Recovery


Common Cathode

Part number

**DSA30C200PB**



Backside: cathode



## Features / Advantages:

- Very low  $V_F$
- Extremely low switching losses
- Low  $I_{rm}$  values
- Improved thermal behaviour
- High reliability circuit operation
- Low voltage peaks for reduced protection circuits
- Low noise switching

## Applications:

- Rectifiers in switch mode power supplies (SMPS)
- Free wheeling diode in low voltage converters

## Package: TO-220

- Industry standard outline
- RoHS compliant
- Epoxy meets UL 94V-0

## Disclaimer Notice


Information furnished is believed to be accurate and reliable. However, users should independently evaluate the suitability of and test each product selected for their own applications. Littelfuse products are not designed for, and may not be used in, all applications. Read complete Disclaimer Notice at [www.littelfuse.com/disclaimer-electronics](http://www.littelfuse.com/disclaimer-electronics).

**Schottky**

| Symbol            | Definition   | Conditions   | Ratings   |      |                              |                |
|-------------------|--|--|---|------|------------------------------|----------------|
|                   |  |  | min.  | typ. | max.                         |                |
| $V_{RSM}$         | max. non-repetitive reverse blocking voltage                               | $T_{VJ} = 25^\circ C$  |   |      | 200                          | V              |
| $V_{RRM}$         | max. repetitive reverse blocking voltage                                   | $T_{VJ} = 25^\circ C$  |   |      | 200                          | V              |
| $I_R$             | reverse current, drain current   | $V_R = 200 V$<br>$V_R = 200 V$                               | $T_{VJ} = 25^\circ C$<br>$T_{VJ} = 125^\circ C$ |      | 250<br>2.5                   | $\mu A$<br>mA  |
| $V_F$             | forward voltage drop   | $I_F = 15 A$<br>$I_F = 30 A$<br>$I_F = 15 A$<br>$I_F = 30 A$ | $T_{VJ} = 25^\circ C$<br>$T_{VJ} = 125^\circ C$ |      | 0.94<br>1.10<br>0.78<br>0.95 | V<br>V         |
| $I_{FAV}$         | average forward current  | $T_C = 155^\circ C$<br>rectangular<br>$d = 0.5$              | $T_{VJ} = 175^\circ C$                          |      | 15                           | A              |
| $V_{F0}$<br>$r_F$ | threshold voltage<br>slope resistance }<br>for power loss calculation only |  | $T_{VJ} = 175^\circ C$                          |      | 0.53<br>10.8                 | V<br>$m\Omega$ |
| $R_{thJC}$        | thermal resistance junction to case  |  |   |      | 1.75                         | K/W            |
| $R_{thCH}$        | thermal resistance case to heatsink  |  |   | 0.50 |                              | K/W            |
| $P_{tot}$         | total power dissipation  |  | $T_C = 25^\circ C$                              |      | 85                           | W              |
| $I_{FSM}$         | max. forward surge current   | $t = 10 \text{ ms}; (50 \text{ Hz}), \text{sine}; V_R = 0 V$ | $T_{VJ} = 45^\circ C$                           |      | 320                          | A              |
| $C_J$             | junction capacitance   | $V_R = 48 V$ f = 1 MHz                                       | $T_{VJ} = 25^\circ C$                           | 47   |                              | pF             |

**Package TO-220**

| Symbol        | Definition                   | Conditions                 | min. | typ. | max. | Unit |
|---------------|------------------------------|----------------------------|------|------|------|------|
| $I_{RMS}$     | RMS current                  | per terminal <sup>1)</sup> |      |      | 35   | A    |
| $T_{VJ}$      | virtual junction temperature |                            | -55  |      | 175  | °C   |
| $T_{op}$      | operation temperature        |                            | -55  |      | 150  | °C   |
| $T_{stg}$     | storage temperature          |                            | -55  |      | 150  | °C   |
| <b>Weight</b> |                              |                            |      | 2    |      | g    |
| $M_d$         | mounting torque              |                            | 0.4  |      | 0.6  | Nm   |
| $F_c$         | mounting force with clip     |                            | 20   |      | 60   | N    |


**Product Marking**

**Part description**


D = Diode  
 S = Schottky Diode  
 A = low VF  
 30 = Current Rating [A]  
 C = Common Cathode  
 200 = Reverse Voltage [V]  
 PB = TO-220AB (3)

| Ordering | Ordering Number | Marking on Product | Delivery Mode | Quantity | Code No. |
|----------|-----------------|--------------------|---------------|----------|----------|
| Standard | DSA30C200PB     | DSA30C200PB        | Tube          | 50       | 507014   |


| Similar Part | Package              | Voltage class |
|--------------|----------------------|---------------|
| DSA30C200IB  | TO-262 (I2Pak) (3)   | 200           |
| DSA30C200PC  | TO-263AB (D2Pak) (2) | 200           |

**Equivalent Circuits for Simulation**
<sup>\*</sup>on die level

 $T_{VJ} = 175 \text{ }^{\circ}\text{C}$ 


**Outlines TO-220**


| Dim. | Millimeter |       | Inches |       |
|------|------------|-------|--------|-------|
|      | Min.       | Max.  | Min.   | Max.  |
| A    | 4.32       | 4.82  | 0.170  | 0.190 |
| A1   | 1.14       | 1.39  | 0.045  | 0.055 |
| A2   | 2.29       | 2.79  | 0.090  | 0.110 |
| b    | 0.64       | 1.01  | 0.025  | 0.040 |
| b2   | 1.15       | 1.65  | 0.045  | 0.065 |
| C    | 0.35       | 0.56  | 0.014  | 0.022 |
| D    | 14.73      | 16.00 | 0.580  | 0.630 |
| E    | 9.91       | 10.66 | 0.390  | 0.420 |
| e    | 2.54       | BSC   | 0.100  | BSC   |
| H1   | 5.85       | 6.85  | 0.230  | 0.270 |
| L    | 12.70      | 13.97 | 0.500  | 0.550 |
| L1   | 2.79       | 5.84  | 0.110  | 0.230 |
| ØP   | 3.54       | 4.08  | 0.139  | 0.161 |
| Q    | 2.54       | 3.18  | 0.100  | 0.125 |




**Schottky**


Fig. 1 Maximum forward voltage drop characteristics




Fig. 2 Typ. reverse current  $I_R$  vs. reverse voltage  $V_R$




Fig. 3 Typ. junction capacitance  $C_T$  vs. reverse voltage  $V_R$




Fig. 4 Average forward current  $I_{F(AV)}$  vs. case temperature  $T_c$




Fig. 5 Forward power loss characteristics




Fig. 6 Transient thermal impedance junction to case

Note: All curves are per diode