


Recommended P.C.B Layout



■ Specifications :

- Voltage rating: 250V AC / DC
- Current rating: 3A AC / DC
- Withstanding voltage: 800V AC/minute
- Temperature range: -25°C~+85°C
- Insulation resistance: $\geq 1000M \Omega$
- Contact resistance: $\leq 10m\Omega$
- After environmental testing : $\leq 20m\Omega$

X2000 W V S-XX- 9T SN

- ① Series No.
- ② Category : W-WAFER
- ③ Wedding Board Angle : V-Stright 180°
- ④ Welding Way:S-SMT
- ⑤ Row No.-Pin No.: XX-02P~16P
- ⑥ Material : 9T-PA9T 94V-0
- ⑦ Plating Category: Sn-Bright Tin Plating;SW-Matte Tin

Poles	Dimensions(mm)			Poles	Dimensions(mm)		
	A	B	C		A	B	C
02	2.00	8.00	4.50	10	18.0	24.0	20.5
03	4.00	10.0	6.50	11	20.0	26.0	22.5
04	6.00	12.0	8.50	12	22.0	28.0	24.5
05	8.00	14.0	10.5	13	24.0	30.0	26.5
06	10.0	16.0	12.5	14	26.0	32.0	28.5
07	12.0	18.0	14.5	15	28.0	34.0	30.5
08	14.0	20.0	16.5	16	30.0	36.0	32.5
09	16.0	22.0	18.5				

X2000WVS-XX-9TSW	PA9T UL 94V-0	Brass	Matte Tin	X2000H
X2000WVS-XX-9TSN			Tin Plating	
PART NO	Material	Material(pin)	Finish(pin)	Suitable XKB Terminal

广东星坤科技股份有限公司

生效

ΔX	日期
ΔX	日期
ΔX	日期
MARK	DESCRIPTION

REVISIONS

DATE REVISED APPROVED UNSPECIFIED TOLERANCES

文件工程章

www.xk-dg.cn

www.helloxkb.com www.helloxkb.cn

DSND	DATE	SCALE: N/A	MODEL TYPE: X2000WVS-XX-9TSN
DWN	DATE	VIEW:	PART NO.: 2.0mm Crimp Style Connectors
CHKD	DATE	UNIT: mm/in	DWG NO.:
APPD	DATE	SIZE: A4	
XKB INDUSTRIAL PRECISION CO., LIMITED			WEIGHT 1.0g
			SHEET 1/1
			REVISION A0