


P.C.B LATOUT



X2508 WR-XX-N0 SN

① ②③ ④ ⑤ ⑥

- ① Series No.
- ② Category:
- ③ Welding Board Angle:
- ④ Row No. -Pin No.
- ⑤ Material:
- ⑥ Planting Category

W-WAFER
R-Right Angle 90°
XX-02-20P
N0 -PA66 94V-0
SN-Bright Tin Plating

Specifications:

规格:
Voltage rating: 250V AC/DC
额定电压: 250V AC/DC
Current rating:
额定电流:
Withstanding voltage: 1000V AC/minute
耐压电压: 1000V AC/minute
Temperature range: -25°C ~ +85°C
温度范围: -25°C ~ +85°C
Insulation resistance: ≥500MΩ
绝缘电阻: ≥500MΩ
Contact resistance: ≤10mΩ
接触电阻: ≤10mΩ
After environmental testing: ≤20mΩ
环境测试后: ≤20mΩ

Poles	Dimensions(mm)	
	A	B
2	2.50	7.50
3	5.00	10.00
4	7.50	12.50
5	10.00	15.00
6	12.50	17.50
7	15.00	20.00
8	17.50	22.50
9	20.00	25.00
10	22.50	27.50
11	25.00	30.00
12	27.50	32.00
13	30.00	35.00
14	32.50	37.50
20	47.50	52.50

X2508WR-XX-N0SN	Nylon 66 UL 94V-0	Brass	Tin-Plated	X2508H
PART NO	Material	Material(Pin)	Finish(Pin)	Suitable XKB Terminal

广东星坤科技股份有限公司

生
發

日
期

文件工程章

REVISIONS

www.xkb.com www.hellixkb.com

ANGULAR	±5°
L ≤ 4	±0.2
4 < L ≤ 16	±0.3
16 < L ≤ 63	±0.4
L > 63	±0.5

UNSPECIFIED TOLERANCES

DSND	DATE	SCALE: N/A	MODEL TYPE:
DWVN	DATE	VIEW:	PART NO.: 2.50 mm Crimp Style Connectors
CHKD	DATE	UNIT: mm/in	DWG NO.:
APPD	DATE	SIZE: A4	X2508WR-XX-N0SN
XKB INDUSTRIAL PRECISION CO., LIMITED			WEIGHT 1.0g
			SHEET 1/1
			REVISION A0