



PC Board Layout
Component Side Shown

NOTES:

MATERIAL :

- 1 HOUSING MATERIAL : GLASS FILLED POLYESTER UL94V-0.
- 2 CONTACT MATERIAL : PHOSPHOR BRONZE φ0.46mm
- 3 PLATING : GOLD PLATING OVER NICKEL.

ELECTRICAL:

- 1 VOLTAGE RATING : 25 VAC RMS.
- 2 CURRENT RATING : 1.5 AMP.
- 3 CONTACT RESISTANCE : 30 MILLIOHMS MAX.
- 4 INSULATION RESISTANCE : 500 MEGOHMS MIN @ 500V DC.
- 5 DIELECTRIC WITHSTANDING RESISTANCE : 1000V AC RMS 50HZ 1MIN.

MECHANICAL:

- 1 DURABILITY : 750 CYCLES MIN.
- 2 PCB RETENTION PRE-SOLDER : 1 LB MIN.

ENVIRONMENTAL:

- 1 STORAGE : -40°~+85°
- 2 OPERATION : 0° TO 70° C

TOLERANCE TABLE

.0	±0.30
.00	±0.20
.000	±0.05

APPROVED:	DATE:	C 深圳市灿科盟实业有限公司 kmtw CHANKEMENG INDUSTRYCO., LTD	TITLE:							
CHECKED:	DATE:		RJ11-4P/4C 90度弯插 无耳							
DRAWN:	DATE:	PART. NO.	55A-1X1-4P4C-13H	UNIT	mm	SCALE	free	REV.	A	HY04
Juli-Liu	2016-04-01	FILE NO.	Ckmtw-RJ11-0035	UNIT	mm	SCALE	free	REV.	A	HY04