



PANEL CUT-OUT

Rating :

15A 250V AC T105 UL cUL
10A 250V AC 3C TUV

Insert And Extract Force: 1.36kgf~6.8kgf

Operating Life: ≥5000 cycles

Withstand Voltage: Between all terminals:2500VAC (50-60Hz)1min
terminals to Base:3750V AC (50-60Hz)1min
Leakage Current : 1mA

Insulation Resistance: ≥100MΩ 500V DC

Body Materil: PBT 94V-2~0

| | | | | | | | | | | | | |
|------|------|----------------------|-------|--------------------|---------------|----------|----|-------------|--------------|----------|-------|--------|
| A4 | | | | 普通公差 | 深圳市华灿天禄电子有限公司 | | | | | | | |
| A3 | | | | COMMON TOLERANCE : | | | | | | | | |
| A2 | | | | UP TO 5 | ±0.20 | 单位 | mm | 投影 | 品名 | Ac Inlet | 比例 | Free |
| A1 | | | | ABOVE 5 TO 30 | ±0.30 | UNIT | | PROJECTED | PRODUCT NAME | | SCALE | |
| REV. | DATE | REVISION DESCRIPTION | ISSUE | ABOVE 30 | ±0.50 | 绘图 | | 核对 | 型号 | | | DB-F |
| | | | | ANGULAR | ±5° | DRAWN BY | | CHECKED BY | MODEL NO. | | | DB-F-1 |
| | | | | | | 日期 | | 核准 | 料号 | | | |
| | | | | | | DATE | | APPROVAL BY | PART NO. | | | |