

产品型号	JRS-P0.9	JRS-P1.2	JRS-P1.4	JRS-P1.5	JRS-P1.6	JRS-P1.8	JRS-P1.9	JRS-P2.0	JRS-P2.5
像素点间距	0.9mm	1.2mm	1.4mm	1.5mm	1.6mm	1.8mm	1.9mm	2.0mm	2.5mm
箱体尺寸	480*270	480*270	480*270	400*300	400*300	480*480	400*300	512*512	480*480
箱体材质	压铸铝	压铸铝	压铸铝	压铸铝	压铸铝	压铸铝	压铸铝	压铸铝	压铸铝
峰值功耗 (w/m²)	≤950	≤700	≤700	≤600	≤600	≤760	≤760	≤760	≤760
平均功耗 (w/m²)	≤350	≤295	≤295	≤200	≤200	≤300	≤300	≤300	≤300
亮度	0~1200 (cd/m²) 区间逐级可调								
灰度	16bit@700cd/m², 13bit@240cd/m²								
对比度	5000:1								
刷新频率 (Hz)	≥3840								
平整度	≤0.1mm								
水平视角	170°								
垂直视角	170°								
色温 (K)	1000~10000 可调								
换帧频率	50Hz&60Hz								
亮度均匀性	≥97%								
色度均匀性	±0.003 Cx, Cy 之内								
发光点中心距偏差	<3%								
校正	支持亮度与色度逐点校正								
使用寿命	≥100000 H								
平均无故障时间	≥50000 H								
防护等级	IP40/IP21								
维护方式	兼容前后维护								
工作温度范围	-20℃~+50℃								
工作湿度范围	10%RH~90%RH, 无凝结								