



REV.	ECN NO OR DESCRIPTION	REVISED	DATE

Specification:

- Electrical Characteristics:
 - Current rating: 1,5PIN 1.8A Max/2,3,4PIN 1A Max.
 - Dielectric withstanding voltage: 100 V(ac) for 1 min.
 - Insulation Resistance: 100 MΩ Minimum.
 - Contact Resistance: 30 mΩ Maximum.
- Environmental:
 - Operating Temperature: -30° C~+80° C.
- Mechanical Characteristics:
 - Total mating force: 3.57 Kgf Max.
 - Total unmating force: 1.0 Kgf Min.
- Material:
 - Insulator: HI-Temp Plastic UL 94V-0 Rated.
 - Contact: Copper Alloy (t=0.15mm).
 - Shell: Copper Alloy/C2680 (t=0.20mm).

UNLESS OTHERWISE SPECIFIED TOLERANCES		东莞市汉博电子科技有限公司 DONGGUAN HANBO TECHNOLOGY CO., LTD		
DECIMALS:	ANGLES:	TITLE MICRO USB 5P 5.9前插后贴有柱5.0壳长直边		
X :±0.20	X :±2°	DWN	xiong	PART NO. MC-605S-AWT
X.X :±0.15	X.X :±1°	CHKD	lee	SCALE:1:1 UNIT: mm
X.XX :±0.10		APVD	wang	SIZE: A4 SHEET:10F 1 REV: A4
CUSTOMER COPY				